§1301.72

(15) The applicability of the security requirements contained in all Federal, State, and local laws and regulations governing the management of waste.

(c) When physical security controls become inadequate as a result of a controlled substance being transferred to a different schedule, or as a result of a noncontrolled substance being listed on any schedule, or as a result of a significant increase in the quantity of controlled substances in the possession of the registrant during normal business operations, the physical security controls shall be expanded and extended accordingly. A registrant may adjust physical security controls within the requirements set forth in §§1301.72-1301.76 when the need for such controls decreases as a result of a controlled substance being transferred to a different schedule, or a result of a controlled substance being removed from control, or as a result of a significant decrease in the quantity of controlled substances in the possession of the registrant during normal business operations.

(d) Any registrant or applicant desiring to determine whether a proposed security system substantially complies with, or is the structural equivalent of, the requirements set forth in §§ 1301.72– 1301.76 may submit any plans, blueprints, sketches or other materials regarding the proposed security system either to the Special Agent in Charge in the region in which the system will be used, or to the Diversion Operations Section, Drug Enforcement Administration, Department of Justice, Washington, DC 20537.

(e) Physical security controls of locations registered under the Harrison Narcotic Act or the Narcotics Manufacturing Act of 1960 on April 30, 1971, shall be deemed to comply substantially with the standards set forth in §§1301.72, 1301.73 and 1301.75. Any new facilities or work or storage areas constructed or utilized for controlled substances, which facilities or work or storage areas have not been previously approved by the Administration, shall not necessarily be deemed to comply substantially with the standards set forth in §§1301.72, 1301.73 and 1301.75, notwithstanding that such facilities or work or storage areas have physical se-

21 CFR Ch. II (4–1–05 Edition)

curity controls similar to those previously approved by the Administration.

[36 FR 18729, Sept. 21, 1971. Redesignated at 38 FR 26609, Sept. 24, 1973, and amended at 46 FR 28841, May 29, 1981; 47 FR 41735, Sept. 22, 1982; 51 FR 5319, Feb. 13, 1986; 68 FR 41228, July 11, 2003]

§ 1301.72 Physical security controls for non-practitioners; narcotic treatment programs and compounders for narcotic treatment programs; storage areas.

(a) Schedules I and II. Raw material, bulk materials awaiting further processing, and finished products which are controlled substances listed in Schedule I or II (except GHB that is manufactured or distributed in accordance with an exemption under section 505(i) of the FFDCA which shall be subject to the requirements of paragraph (b) of this section) shall be stored in one of the following secured areas:

(1) Where small quantities permit, a safe or steel cabinet;

(i) Which safe or steel cabinet shall have the following specifications or the equivalent: 30 man-minutes against surreptitious entry, 10 man-minutes against forced entry, 20 man-hours against lock manipulation, and 20 manhours against radiological techniques;

(ii) Which safe or steel cabinet, if it weighs less than 750 pounds, is bolted or cemented to the floor or wall in such a way that it cannot be readily removed; and

(iii) Which safe or steel cabinet, if necessary, depending upon the quantities and type of controlled substances stored, is equipped with an alarm system which, upon attempted unauthorized entry, shall transmit a signal directly to a central protection company or a local or State police agency which has a legal duty to respond, or a 24hour control station operated by the registrant, or such other protection as the Administrator may approve.

(2) A vault constructed before, or under construction on, September 1, 1971, which is of substantial construction with a steel door, combination or key lock, and an alarm system; or

(3) A vault constructed after September 1, 1971:

(i) The walls, floors, and ceilings of which vault are constructed of at least

Drug Enforcement Administration, Justice

8 inches of reinforced concrete or other substantial masonry, reinforced vertically and horizontally with ½-inch steel rods tied 6 inches on center, or the structural equivalent to such reinforced walls, floors, and ceilings;

(ii) The door and frame unit of which vault shall conform to the following specifications or the equivalent: 30 man-minutes against surreptitious entry, 10 man-minutes against forced entry, 20 man-hours against lock manipulation, and 20 man-hours against radiological techniques;

(iii) Which vault, if operations require it to remain open for frequent access, is equipped with a "day-gate" which is self-closing and self-locking, or the equivalent, for use during the hours of operation in which the vault door is open;

(iv) The walls or perimeter of which vault are equipped with an alarm, which upon unauthorized entry shall transmit a signal directly to a central station protection company, or a local or State police agency which has a legal duty to respond, or a 24-hour control station operated by the registrant, or such other protection as the Administrator may approve, and, if necessary, holdup buttons at strategic points of entry to the perimeter area of the vault;

(v) The door of which vault is equipped with contact switches; and

(vi) Which vault has one of the following: Complete electrical lacing of the walls, floor and ceilings; sensitive ultrasonic equipment within the vault; a sensitive sound accumulator system; or such other device designed to detect illegal entry as may be approved by the Administration.

(b) Schedules III, IV and V. Raw material, bulk materials awaiting further processing, and finished products which are controlled substances listed in Schedules III, IV, and V, and GHB when it is manufactured or distributed in accordance with an exemption under section 505(i) of the FFDCA, shall be stored in the following secure storage areas:

(1) A safe or steel cabinet as described in paragraph (a)(1) of this section;

(2) A vault as described in paragraph (a)(2) or (3) of this section equipped with an alarm system as described in paragraph (b)(4)(v) of this section;

(3) A building used for storage of Schedules III through V controlled substances with perimeter security which limits access during working hours and provides security after working hours and meets the following specifications:

(i) Has an electronic alarm system as described in paragraph (b)(4)(v) of this section,

(ii) Is equipped with self-closing, selflocking doors constructed of substantial material commensurate with the type of building construction, provided, however, a door which is kept closed and locked at all times when not in use and when in use is kept under direct observation of a responsible employee or agent of the registrant is permitted in lieu of a self-closing, self-locking door. Doors may be sliding or hinged. Regarding hinged doors, where hinges are mounted on the outside, such hinges shall be sealed, welded or otherwise constructed to inhibit removal. Locking devices for such doors shall be either of the multiple-position combination or key lock type and:

(a) In the case of key locks, shall require key control which limits access to a limited number of employees, or;

(b) In the case of combination locks, the combination shall be limited to a minimum number of employees and can be changed upon termination of employment of an employee having knowledge of the combination;

(4) A cage, located within a building on the premises, meeting the following specifications:

(i) Having walls constructed of not less than No. 10 gauge steel fabric mounted on steel posts, which posts are:

(*a*) At least one inch in diameter;

(b) Set in concrete or installed with lag bolts that are pinned or brazed; and

(c) Which are placed no more than ten feet apart with horizontal one and one-half inch reinforcements every sixty inches;

(ii) Having a mesh construction with openings of not more than two and onehalf inches across the square,

(iii) Having a ceiling constructed of the same material, or in the alternative, a cage shall be erected which reaches and is securely attached to the structural ceiling of the building. A lighter gauge mesh may be used for the ceilings of large enclosed areas if walls are at least 14 feet in height,

(iv) Is equipped with a door constructed of No. 10 gauge steel fabric on a metal door frame in a metal door flange, and in all other respects conforms to all the requirements of 21 CFR 1301.72(b)(3)(ii), and

(v) Is equipped with an alarm system which upon unauthorized entry shall transmit a signal directly to a central station protection agency or a local or state police agency, each having a legal duty to respond, or to a 24-hour control station operated by the registrant, or to such other source of protection as the Administrator may approve;

(5) An enclosure of masonry or other material, approved in writing by the Administrator as providing security comparable to a cage;

(6) A building or enclosure within a building which has been inspected and approved by DEA or its predecessor agency, BND, and continues to provide adequate security against the diversion of Schedule III through V controlled substances, of which fact written acknowledgment has been made by the Special Agent in Charge of DEA for the area in which such building or enclosure is situated;

(7) Such other secure storage areas as may be approved by the Administrator after considering the factors listed in \$1301.71(b);

(8)(i) Schedule III through V controlled substances may be stored with Schedules I and II controlled substances under security measures provided by 21 CFR 1301.72(a);

(ii) Non-controlled drugs, substances and other materials may be stored with Schedule III through V controlled substances in any of the secure storage areas required by 21 CFR 1301.72(b), provided that permission for such storage of non-controlled items is obtained in advance, in writing, from the Special Agent in Charge of DEA for the area in which such storage area is situated. Any such permission tendered must be upon the Special Agent in Charge's written determination that such non-segregated storage does not diminish security effectiveness for 21 CFR Ch. II (4-1-05 Edition)

Schedules III through V controlled substances.

(c) Multiple storage areas. Where several types or classes of controlled substances are handled separately by the registrant or applicant for different purposes (e.g., returned goods, or goods in process), the controlled substances may be stored separately, provided that each storage area complies with the requirements set forth in this section.

(d) Accessibility to storage areas. The controlled substances storage areas shall be accessible only to an absolute minimum number of specifically authorized employees. When it is necessary for employee maintenance personnel, nonemployee maintenance personnel, business guests, or visitors to be present in or pass through controlled substances storage areas, the registrant shall provide for adequate observation of the area by an employee specifically authorized in writing.

[36 FR 18730, Sept. 21, 1971, as amended at 37 FR 15919, Aug. 8, 1972. Redesignated at 38 FR 26609, Sept. 24, 1973]

EDITORIAL NOTE: For FEDERAL REGISTER citations affecting §1301.72, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and on GPO Access.

§ 1301.73 Physical security controls for non-practitioners; compounders for narcotic treatment programs; manufacturing and compounding areas.

All manufacturing activities (including processing, packaging and labeling) involving controlled substances listed in any schedule and all activities of compounders shall be conducted in accordance with the following:

(a) All in-process substances shall be returned to the controlled substances storage area at the termination of the process. If the process is not terminated at the end of a workday (except where a continuous process or other manufacturing operation normal should not be interrupted), the processing area or tanks, vessels, bins or bulk containers containing such substances shall be securely locked, with adequate security for the area or building. If such security requires an alarm, such alarm, upon unauthorized entry, shall transmit a signal directly to a