

Environmental Protection Agency

§ 63.550

(D) The reference method shall be an National Institute of Standards and Technology calibrated reference thermocouple-potentiometer system or an alternate reference, subject to the approval of the Administrator.

(iii) The owner or operator of a blast furnace or a collocated blast furnace and reverberatory furnace subject to the total hydrocarbon emission standards shall monitor and record the temperature of the afterburner or the combined blast furnace and reverberatory furnace exhaust streams every 15 minutes during the total hydrocarbon compliance test and determine an arithmetic average for the recorded temperature measurements.

(iv) To remain in compliance with the standards for total hydrocarbons, the owner or operator must maintain an afterburner or combined exhaust temperature such that the average temperature in any 3-hour period does not fall more than 28 °C (50 °F) below the average established in paragraph (j)(1)(iii) of this section. An average temperature in any 3-hour period that falls more than 28 °C (50 °F) below the average established in paragraph (j)(1)(iii) of this section, shall constitute a violation of the applicable emission standard for total hydrocarbons under § 63.543 (c), (d), or (e).

(2) *Continuous Monitoring of Total Hydrocarbon Emissions.* (i) The owner or operator of a secondary lead smelter shall install, operate, and maintain a total hydrocarbon continuous monitoring system and comply with all of the requirements for continuous monitoring systems found in subpart A, General Provisions.

(ii) Prior to or in conjunction with the initial compliance test to determine compliance with § 63.543 (c), (d), or (e), the owner or operator shall conduct a performance evaluation for the total hydrocarbon continuous monitoring system according to § 63.8(e) of the General Provisions. The monitor shall meet the performance specifications of Performance Specification 8, 40 CFR Part 60, Appendix B.

(iii) Allowing the 3-hour average total hydrocarbon concentration to exceed the applicable total hydrocarbon emission limit under § 63.543 shall constitute a violation of the applicable

emission standard for total hydrocarbons under § 63.543 (c), (d), or (e).

(k) The owner or operator of a secondary lead smelter who uses pressurized dryer breaching seals in order to comply with the requirements of § 63.544(g) shall equip each seal with an alarm that will “sound” or “go off” if the pressurized dryer breaching seal malfunctions.

[62 FR 32216, June 13, 1997, as amended at 63 FR 45011, Aug. 24, 1998]

§ 63.549 Notification requirements.

(a) The owner or operator of a secondary lead smelter shall comply with all of the notification requirements of § 63.9 of subpart A, General Provisions.

(b) The owner or operator of a secondary lead smelter shall submit the fugitive dust control standard operating procedures manual required under § 63.545(a) and the standard operating procedures manual for baghouses required under § 63.548(a) to the Administrator or delegated authority along with a notification that the smelter is seeking review and approval of these plans and procedures. Owners or operators of existing secondary lead smelters shall submit this notification no later than July 23, 1997. The owner or operator of a secondary lead smelter that commences construction or reconstruction after June 9, 1994, shall submit this notification no later than 180 days before startup of the constructed or reconstructed secondary lead smelter, but no sooner than June 13, 1997. An affected source that has received a construction permit from the Administrator or delegated authority on or before June 23, 1995, shall submit this notification no later than July 23, 1997.

§ 63.550 Recordkeeping and reporting requirements.

(a) The owner or operator of a secondary lead smelter shall comply with all of the recordkeeping requirements under § 63.10 of the General Provisions. In addition, each owner or operator of a secondary lead smelter shall maintain for a period of 5 years, records of the information listed in paragraphs (a)(1) through (a)(6) of this section.

(1) An identification of the date and time of all bag leak detection system