

§ 63.323

40 CFR Ch. I (7-1-08 Edition)

(1) The owner or operator of a dry cleaning system shall inspect the components listed in paragraph (k) of this section for vapor leaks monthly while the component is in operation.

(i) Area sources shall conduct the inspections using a halogenated hydrocarbon detector or PCE gas analyzer that is operated according to the manufacturer's instructions. The operator shall place the probe inlet at the surface of each component interface where leakage could occur and move it slowly along the interface periphery.

(ii) Major sources shall conduct the inspections using a PCE gas analyzer operated according to EPA Method 21.

(iii) Any inspection conducted according to this paragraph shall satisfy the requirements to conduct an inspection for perceptible leaks under § 63.322(k) or (l) of this subpart.

(2) The owner or operator of each dry cleaning system installed after December 21, 2005, at an area source shall route the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and pass the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened. The carbon adsorber must be desorbed in accordance with manufacturer's instructions.

(3) The owner or operator of any dry cleaning system shall eliminate any emission of PCE during the transfer of articles between the washer and the dryer(s) or reclaimer(s).

(4) The owner or operator shall eliminate any emission of PCE from any dry cleaning system that is installed (including relocation of a used machine) after December 21, 2005, and that is located in a building with a residence.

(5)(i) After December 21, 2020, the owner or operator shall eliminate any emission of PCE from any dry cleaning system that is located in a building with a residence.

(ii) Sources demonstrating compliance under Section 63.320(b)(2)(ii) shall comply with paragraph (o)(5)(ii)(A) through (C), in addition to the other applicable requirements of this section:

(A) Operate the dry cleaning system inside a vapor barrier enclosure. The exhaust system for the enclosure shall be operated at all times that the dry cleaning system is in operation and during maintenance. The entry door to the enclosure may be open only when a person is entering or exiting the enclosure.

(B) Route the air-perchloroethylene gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and pass the air-perchloroethylene gas-vapor stream from inside the dry cleaning drum through a carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened. The carbon adsorber must be desorbed in accordance with manufacturer's instructions.

(C) Inspect the machine components listed in paragraph (k) of this section for vapor leaks weekly while the component is in operation. These inspections shall be conducted using a halogenated hydrocarbon detector or PCE gas analyzer that is operated according to the manufacturer's instructions. The operator shall place the probe inlet at the surface of each component interface where leakage could occur and move it slowly along the interface periphery.

[58 FR 49376, Sept. 22, 1993, as amended at 61 FR 49265, Sept. 19, 1996; 71 FR 42744, July 27, 2006]

§ 63.323 Test methods and monitoring.

(a) When a refrigerated condenser is used to comply with § 63.322(a)(1) or (b)(1):

(1) The owner or operator shall monitor the following parameters, as applicable, on a weekly basis:

(i) The refrigeration system high pressure and low pressure during the drying phase to determine if they are in the range specified in the manufacturer's operating instructions.

(ii) If the machine is not equipped with refrigeration system pressure gauges, the temperature of the air-perchloroethylene gas-vapor stream on the outlet side of the refrigerated condenser on a dry-to-dry machine, dryer, or reclaimer with a temperature sensor to determine if it is equal to or less than 7.2 °C (45 °F) before the end of the

cool-down or drying cycle while the gas-vapor stream is flowing through the condenser. The temperature sensor shall be used according to the manufacturer's instructions and shall be designed to measure a temperature of 7.2 °C (45 °F) to an accuracy of ± 1.1 °C (± 2 °F).

(2) The owner or operator shall calculate the difference between the temperature of the air-perchloroethylene gas-vapor stream entering the refrigerated condenser on a washer and the temperature of the air-perchloroethylene gas-vapor stream exiting the refrigerated condenser on the washer weekly to determine that the difference is greater than or equal to 11.1 °C (20 °F).

(i) Measurements of the inlet and outlet streams shall be made with a temperature sensor. Each temperature sensor shall be used according to the manufacturer's instructions, and designed to measure at least a temperature range from 0 °C (32 °F) to 48.9 °C (120 °F) to an accuracy of ± 1.1 °C (± 2 °F).

(ii) The difference between the inlet and outlet temperatures shall be calculated weekly from the measured values.

(b) When a carbon adsorber is used to comply with § 63.322(a)(2) or exhaust is passed through a carbon adsorber immediately upon machine door opening to comply with § 63.322(b)(3) or § 63.322(o)(2), the owner or operator shall measure the concentration of PCE in the exhaust of the carbon adsorber weekly with a colorimetric detector tube or PCE gas analyzer. The measurement shall be taken while the dry cleaning machine is venting to that carbon adsorber at the end of the last dry cleaning cycle prior to desorption of that carbon adsorber or removal of the activated carbon to determine that the PCE concentration in the exhaust is equal to or less than 100 parts per million by volume. The owner or operator shall:

(1) Use a colorimetric detector tube or PCE gas analyzer designed to measure a concentration of 100 parts per million by volume of PCE in air to an accuracy of ± 25 parts per million by volume; and

(2) Use the colorimetric detector tube or PCE gas analyzer according to the manufacturer's instructions; and

(3) Provide a sampling port for monitoring within the exhaust outlet of the carbon adsorber that is easily accessible and located at least 8 stack or duct diameters downstream from any flow disturbance such as a bend, expansion, contraction, or outlet; downstream from no other inlet; and 2 stack or duct diameters upstream from any flow disturbance such as a bend, expansion, contraction, inlet, or outlet.

(c) If the air-PCE gas vapor stream is passed through a carbon adsorber prior to machine door opening to comply with § 63.322(b)(3) or § 63.322(o)(2), the owner or operator of an affected facility shall measure the concentration of PCE in the dry cleaning machine drum at the end of the dry cleaning cycle weekly with a colorimetric detector tube or PCE gas analyzer to determine that the PCE concentration is equal to or less than 300 parts per million by volume. The owner or operator shall:

(1) Use a colorimetric detector tube or PCE gas analyzer designed to measure a concentration of 300 parts per million by volume of PCE in air to an accuracy of ± 75 parts per million by volume; and

(2) Use the colorimetric detector tube or PCE gas analyzer according to the manufacturer's instructions; and

(3) Conduct the weekly monitoring by inserting the colorimetric detector or PCE gas analyzer tube into the open space above the articles at the rear of the dry cleaning machine drum immediately upon opening the dry cleaning machine door.

(d) When calculating yearly perchloroethylene consumption for the purpose of demonstrating applicability according to § 63.320, the owner or operator shall perform the following calculation on the first day of every month:

(1) Sum the volume of all perchloroethylene purchases made in each of the previous 12 months, as recorded in the log described in § 63.324(d)(1).

(2) If no perchloroethylene purchases were made in a given month, then the perchloroethylene consumption for that month is zero gallons.

§ 63.324

40 CFR Ch. I (7-1-08 Edition)

(3) The total sum calculated in paragraph (d) of this section is the yearly perchloroethylene consumption at the facility.

[58 FR 49376, Sept. 22, 1993, as amended at 71 FR 42745, July 27, 2006; 71 FR 55280, Sept. 21, 2006]

EFFECTIVE DATE NOTE: At 73 FR 17256, Apr. 1, 2008, § 63.323 was amended by revising paragraphs (a)(1) introductory text, (a)(1)(ii), (b) introductory text and (c) introductory text, effective July 15, 2008. For the convenience of the user, the revised text is set forth as follows:

§ 63.323 Test methods and monitoring.

(a) * * *

(1) The owner or operator shall monitor on a weekly basis the parameters in either paragraph (a)(1)(i) or (ii) of this section.

* * * * *

(ii) The temperature of the air-perchloroethylene gas-vapor stream on the outlet side of the refrigerated condenser on a dry-to-dry machine, dryer, or reclaimer with a temperature sensor to determine if it is equal to or less than 7.2 °C (45 °F) before the end of the cool-down or drying cycle while the gas-vapor stream is flowing through the condenser. The temperature sensor shall be used according to the manufacturer's instructions and shall be designed to measure a temperature of 7.2 °C (45 °F) to an accuracy of ±1.1 °C (±2 °F).

* * * * *

(b) When a carbon adsorber is used to comply with § 63.322(a)(2) or exhaust is passed through a carbon adsorber immediately upon machine door opening to comply with § 63.322(b)(3), the owner or operator shall measure the concentration of PCE in the exhaust of the carbon adsorber weekly with a colorimetric detector tube or PCE gas analyzer. The measurement shall be taken while the dry cleaning machine is venting to that carbon adsorber at the end of the last dry cleaning cycle prior to desorption of that carbon adsorber or removal of the activated carbon to determine that the PCE concentration in the exhaust is equal to or less than 100 parts per million by volume. The owner or operator shall:

* * * * *

(c) If the air-PCE gas vapor stream is passed through a carbon adsorber prior to machine door opening to comply with § 63.322(b)(3), the owner or operator of an affected facility shall measure the concentration of PCE in the dry cleaning machine

drum at the end of the dry cleaning cycle weekly with a colorimetric detector tube or PCE gas analyzer to determine that the PCE concentration is equal to or less than 300 parts per million by volume. The owner or operator shall:

* * * * *

§ 63.324 Reporting and recordkeeping requirements.

(a) Each owner or operator of a dry cleaning facility shall notify the Administrator or delegated State authority in writing within 270 calendar days after September 23, 1993 (i.e., June 18, 1994) and provide the following information:

- (1) The name and address of the owner or operator;
- (2) The address (that is, physical location) of the dry cleaning facility;
- (3) A brief description of the type of each dry cleaning machine at the dry cleaning facility;
- (4) Documentation as described in § 63.323(d) of the yearly perchloroethylene consumption at the dry cleaning facility for the previous year to demonstrate applicability according to § 63.320; or an estimation of perchloroethylene consumption for the previous year to estimate applicability with § 63.320; and
- (5) A description of the type of control device(s) that will be used to achieve compliance with § 63.322 (a) or (b) and whether the control device(s) is currently in use or will be purchased.

(6) Documentation to demonstrate to the Administrator's satisfaction that each room enclosure used to meet the requirements of § 63.322(a)(3) meets the requirements of § 63.322(a)(3) (i) and (ii).

(b) Each owner or operator of a dry cleaning facility shall submit to the Administrator or delegated State authority by registered mail on or before the 30th day following the compliance dates specified in § 63.320 (b) or (c) or June 18, 1994, whichever is later, a notification of compliance status providing the following information and signed by a responsible official who shall certify its accuracy:

- (1) The yearly perchloroethylene solvent consumption limit based upon the yearly solvent consumption calculated according to § 63.323(d);