

(7) The Sabine Neches Canal from mile 262.5 WHL to mile 291.5 WHL.

(8) Bolivar Roads from the Bolivar Assembling Basin at Mile 346 WHL to the Galveston Causeway Bridge at Mile 357.3 WHL.

(9) Freeport Harbor from Surfside Beach Fixed Bridge at Mile 393.8 WHL to the Bryan Beach Pontoon Bridge at Mile 397.6 WHL.

(10) Matagorda Ship Channel area of Matagorda Bay from Range "K" Front Light at Mile 468.7 WHL to the Port O'Connor Jetty at Mile 472.2 WHL.

(11) Corpus Christi Bay from Redfish Bay Day Beacon "55" at Mile 537.4 WHL when in the Gulf Intracoastal Waterway main route or from the north end of Lydia Ann Island Mile 531.1A when in the Gulf Intracoastal Waterway Alternate Route to Corpus Christi Bay LT 76 at Mile 543.7 WHL.

(12) Port Isabel and Brownsville Ship Channel south of the Padre Island Causeway Fixed Bridge at Mile 665.1 WHL.

[CGD 91-050, 58 FR 27625, May 10, 1993]

**PART 90—INLAND RULES:
INTERPRETATIVE RULES**

Sec.

90.1 Purpose.

90.3 Pushing vessel and vessel being pushed:
Composite unit.

90.5 Lights for moored vessels.

90.7 Sidelights for unmanned barges.

AUTHORITY: 33 U.S.C. 2071; 49 CFR 1.46(n)(14).

SOURCE: CGD 83-011, 48 FR 51622, Nov. 10, 1983, unless otherwise noted.

§90.1 Purpose.

This part contains the interpretative rules for the Inland Rules. These interpretative rules are intended as a guide to assist the public and promote compliance with the Inland Rules.

§90.3 Pushing vessel and vessel being pushed: Composite unit.

Rule 24(b) of the Inland Rules states that when a pushing vessel and a vessel being pushed ahead are rigidly connected in a composite unit, they are regarded as a power-driven vessel and must exhibit the lights prescribed in Rule 23. A "composite unit" is interpreted to be the combination of a pushing vessel and a vessel being pushed ahead that are rigidly connected by mechanical means so they react to sea and swell as one vessel. Mechanical means does not include lines, wires, hawsers, or chains.

§90.5 Lights for moored vessels.

A *vessel at anchor* includes a vessel made fast to one or more mooring buoys or other similar device attached to the ocean floor. Such vessels may be lighted as a vessel at anchor in accordance with Rule 30, or may be lighted on the corners in accordance with 33 CFR 88.13.

[CGD 94-011, 63 FR 5732, Feb. 4, 1998]

§90.7 Sidelights for unmanned barges.

An unmanned barge being towed may use the exception of COLREGS Rule 24(h). However, this exception only applies to the vertical sector requirements for sidelights.

[CGD 94-011, 63 FR 5732, Feb. 4, 1998]

INDEX

SUBCHAPTER E—INLAND NAVIGATION RULES

EDITORIAL NOTE: This listing is provided for informational purposes only. It is compiled and kept up-to-date by the Coast Guard, Department of Transportation.

Section

A

Annex I: Positioning and Technical Details of Lights and Shapes.....	Part 84
Annex II: Additional Signals for Fishing Vessels Fishing in Close Proximity.....	Part 85
Annex III: Technical Details of Sound Signal Appliances.....	Part 86
Annex IV: Distress Signals.....	Part 87
Annex V: Pilot Rules.....	Part 88
Application for a Certificate of Alternative Compliance.....	89.5
Approval [Reserved].....	84.25, 86.31

B

Bell or Gong

C

Certificate of Alternative Compliance.....	Subpart A
Certificate of Alternative Compliance: Contents.....	89.9
Certificate of Alternative Compliance: Termination.....	89.17
Color specifications of lights.....	84.13
Combined whistle systems.....	86.13
Construction.....	86.23
Copy of rules.....	88.05

D

Definitions.....	84.01, 88.03, 89.1, 89.23
Details of location of direction-indicating lights for fishing vessels, dredgers, and vessels engaged in underwater operations.....	84.07
Directional properties.....	86.07

E

Exclusive use.....	87.3
--------------------	------

F

Fitting of more than one whistle.....	86.11
Frequencies and range of audibility.....	86.01

H

Horizontal positioning and spacing of lights.....	84.05
Horizontal sectors.....	84.17

Index

I

Inland Navigation Rules: Implementing Rules.....	Part 89
Inland Navigation Rules: Interpretative Rules	Part 90
Intensity of lights.....	84.15
Intensity of non-electric lights.....	84.21
Intensity of signal	86.21

L

Law enforcement vessels	88.11
Lights on barges at bank or dock	88.13
Lights on dredge pipelines.....	88.15
Limits of fundamental frequencies.....	86.03

M

Maneuvering light	84.23
-------------------------	-------

N

Need of assistance	87.1
--------------------------	------

P

Positioning of whistles	86.09
Public safety activities.....	88.12
Purpose and applicability	88.01
Pushing vessel and vessel being pushed: Composite unit	90.3

R

Record of certification of vessels of special construction or purpose.....	89.18
----------------------------------------------------------------------------	-------

S

Screens	84.09
Shapes.....	84.11
Signal for purse seiners.....	85.5
Signal for trawlers	85.3
Sound signal intensity and range of audibility	86.05
Supplemental signals	87.5

T

Temporary exemption from light and shape requirements when operat- ing under bridges	88.09
Towing vessel whistles.....	86.15

V

Vertical positioning and spacing of lights.....	84.03
Vertical sectors	84.19

W

Waters Upon Which Certain Inland Navigation Rules Apply.....	89.25, 89.27
Whistles	