

than the worst anticipated service condition of the cargo loading.

(f) In the design and testing of the independent cargo tanks, consideration shall be given to the possibility of the independent tanks being subjected to external loads.

[CGFR 66-33, 31 FR 15269, Dec. 6, 1966, as amended by CGD 85-061, 54 FR 50962, Dec. 11, 1989]

§ 38.25-3 Nondestructive testing—TB/ALL.

(a) Before nondestructive testing may be conducted to meet § 38.25-1 (a)(4) and (a)(5), the owner shall submit a proposal to the Officer in Charge, Marine Inspection for acceptance that includes—

(1) The test methods and procedures to be used, all of which must meet section V of the ASME Boiler and Pressure Vessel Code (1986);

(2) Each location on the tank to be tested; and

(3) The test method and procedure to be conducted at each location on the tank.

(b) If the Officer in Charge, Marine Inspection rejects the proposal, the Officer in Charge, Marine Inspection informs the owner of the reasons why the proposal is rejected.

(c) If the Officer in Charge, Marine Inspection accepts the proposal, then the owner shall ensure that—

(1) The proposal is followed; and

(2) Nondestructive testing is performed by personnel meeting ASNT "Recommended Practice No. SNT-TC-1A (1988), Personnel Qualification and Certification in Nondestructive Testing."

(d) Within 30 days after completing the nondestructive test, the owner shall submit a written report of the results to the Officer in Charge, Marine Inspection.

[CGD 85-061, 54 FR 50963, Dec. 11, 1989]

§ 38.25-5 Removal of defective tanks—TB/ALL.

If a tank fails to pass the tests prescribed in this subpart, it shall be removed from service unless otherwise authorized by the Commandant.

§ 38.25-10 Safety relief valves—TB/ALL.

(a) The cargo tank safety relief valves shall be inspected at least once in every 2 years.

(b) The safety relief valve discs must be lifted from their seats in the presence of a marine inspector by either liquid, gas, or vapor pressure at least once every 5 years to determine the accuracy of adjustment and, if necessary, must be reset.

[CGFR 66-33, 31 FR 15269, Dec. 6, 1966, as amended by CGD 95-027, 61 FR 26000, May 23, 1996]

PART 39—VAPOR CONTROL SYSTEMS

Subpart 39.10—General

Sec.

39.10-1 Applicability—TB/ALL.

39.10-3 Definitions—TB/ALL.

39.10-5 Incorporation by reference—TB/ALL.

39.10-9 Vessel vapor processing unit—TB/ALL.

39.10-11 Personnel training—TB/ALL.

39.10-13 Submission of vapor control system designs—TB/ALL.

Subpart 39.20—Design and Equipment

39.20-1 Vapor collection system—TB/ALL.

39.20-3 Cargo gauging system—TB/ALL.

39.20-7 Tankship liquid overflow protection—T/ALL.

39.20-9 Tank barge liquid overflow protection—B/ALL.

39.20-11 Vapor overpressure and vacuum protection—TB/ALL.

39.20-13 High and low vapor pressure protection for tankships—T/ALL.

Subpart 39.30—Operations

39.30-1 Operational requirements—TB/ALL.

Subpart 39.40—Lightering and Topping-Off Operations with Vapor Balancing

39.40-1 General requirements for vapor balancing—TB/ALL.

39.40-3 Design and equipment for vapor balancing—TB/ALL.

39.40-5 Operational requirements for vapor balancing—TB/ALL.

AUTHORITY: 33 U.S.C. 1231; 46 U.S.C. 3306, 3703, 3715(b); 45 FR 58801, 3 CFR, 1980 Comp., p. 277; 49 CFR 1.46.

SOURCE: CGD 88-102, 55 FR 25446, June 21, 1990, unless otherwise noted.

Subpart 39.10—General

§ 39.10-1 Applicability—TB/ALL.

(a) Except as specified by paragraph (c) of this section, this part applies to each tank vessel operating in the navigable waters of the United States, when collecting vapors of crude oil, gasoline blends, or benzene emitted from a vessel's cargo tanks through a vapor control system.

(b) A tank vessel which transfers vapors of flammable or combustible cargoes other than crude oil, gasoline blends, or benzene, to a facility covered by 33 CFR part 154 must meet the requirements prescribed by the Commandant (G-MSO).

(c) A tank vessel with an existing vapor collection system specifically approved by the Coast Guard for the collection of cargo vapor which was operating prior to July 23, 1990, is subject only to § 39.30-1 and § 39.40-5 of this part as long as it transfers cargo vapor only to the specific facilities for which it was approved.

(d) This part does not apply to the collection of vapors of liquefied flammable gases as defined in § 30.10-39 of this subchapter.

[CGD 88-102, 55 FR 25446, June 21, 1990, as amended by CGD 95-072, 60 FR 50462, Sept. 29, 1995; CGD 96-041, 61 FR 50727, Sept. 27, 1996]

§ 39.10-3 Definitions—TB/ALL.

As used in this part:

Cargo deck area means that part of the weather deck that is directly over the cargo tanks.

Existing vapor collection system means a vapor collection system which was operating prior to July 23, 1990.

Facility vapor connection means the point in a facility's fixed vapor collection system where it connects with the vapor collection hose or the base of the vapor collection arm.

Independent as applied to two systems means that one system will operate with a failure of any part of the other system except power sources and electrical feeder panels.

Inerted means the oxygen content of the vapor space in a cargo tank is reduced to 8 percent by volume or less in accordance with the inert gas requirements of § 32.53 or § 153.500 of this chapter.

Lightering or lightering operation means the transfer of a bulk liquid cargo from a tank vessel to a service vessel.

Marine Safety Center means the Commanding Officer, U.S. Coast Guard Marine Safety Center, 400 Seventh Street, SW., Washington, DC 20590-0001.

Maximum allowable transfer rate means the maximum volumetric rate at which a vessel may receive cargo or ballast.

New vapor collection system means a vapor collection system which is not an existing vapor collection system.

Service vessel means a vessel which transports bulk liquid cargo between a facility and another vessel.

Topping-off operation means the transfer of a bulk liquid cargo from a service vessel to another vessel in order to load the receiving vessel to a deeper draft.

Vapor balancing means the transfer of vapor displaced by incoming cargo from the tank of a vessel receiving cargo into a tank of the vessel or facility delivering cargo via a vapor collection system.

Vapor collection system means an arrangement of piping and hoses used to collect vapor emitted from a vessel's cargo tanks and to transport the vapor to a vapor processing unit.

Vapor control system means an arrangement of piping and equipment used to control vapor emissions collected from a vessel. It includes the vapor collection system and vapor processing unit.

Vapor processing unit means the components of a vapor control system that recovers, destroys, or disperses vapor collected from a vessel.

Vessel vapor connection means the point in a vessel's fixed vapor collection system where it connects with the vapor collection hose or arm.

§ 39.10-5 Incorporation by reference—TB/ALL.

(a) Certain materials are incorporated by reference into this part with the approval of the Director of the FEDERAL REGISTER in accordance with 5 U.S.C. 552(a). To enforce any edition other than the one listed in paragraph (b) of this section, notice of change

must be published in the FEDERAL REGISTER and the material made available to the public. All approved material is on file at the Office of the Federal Register, 800 North Capitol Street, NW., suite 700, Washington, DC and at the U.S. Coast Guard, Office of Operating and Environmental Standards (G-MSO), 2100 Second Street, SW., Washington, DC 20593-0001, and is available from the sources indicated in paragraph (b) of this section.

(b) The material approved for incorporation by reference in this part, and the sections affected are:

American Petroleum Institute (API), 1220 L Street NW., Washington, DC 20005
 API Standard 2000, Venting Atmospheric and Low-Pressure Storage Tanks (Non-refrigerated and Refrigerated), Third Edition, January 1982 (reaffirmed December 1987) 39.20-11

American National Standards Institute (ANSI), 11 West 42nd Street, New York, NY 10036
 ANSI B16.5, Steel Pipe Flanges and Flanged Fittings, 1981 ... 39.20-1

American Society for Testing and Materials (ASTM), 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959
 ASTM F1271—Standard Specification for Spill Valves for Use in Marine Tank Liquid Overpressure Protection Applications, December 29, 1989 39.20-9

International Electrotechnical Commission (IEC), Bureau Central de la Commission Electrotechnique Internationale, 1 rue de Varembe', Geneva, Switzerland
 IEC 309-1—Plugs, Socket-Outlets and Couplers for Industrial Purposes: Part 1, General Requirements, 1979 39.20-9
 IEC 309-2—Plugs, Socket-Outlets and Couplers for Industrial Purposes: Part 2, Dimensional Interchangeability Requirements for Pin and Contact-tube Accessories, 1981 39.20-9

National Electrical Manufacturers Association (NEMA), 2101 L St. NW., Washington, DC 20036
 ANSI/NEMA WD6—Wiring Devices, Dimensional Requirements, 1988 39.20-9

National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02269
 NFPA 70—National Electrical Code, 1987 39.20-9

Oil Companies International Marine Forum (OCIMF), 15th Floor, 96 Victoria Street, London SW1E 5JW, England
 International Safety Guide for Oil Tankers and Terminals, Third Edition, 1988 39.30-1

[CGD 88-102, 55 FR 25446, June 21, 1990, as amended by CGD 95-072, 60 FR 50462, Sept. 29, 1995; CGD 96-041, 61 FR 50727, Sept. 27, 1996; CGD 97-057, 62 FR 51043, Sept. 30, 1997]

§ 39.10-9 Vessel vapor processing unit—TB/ALL.

Each vessel which has a vapor processing unit located on board must meet the requirements of 33 CFR part 154, subpart E to the satisfaction of the Commandant (G-MSO) in addition to complying with the requirements of this part.

[CGD 88-102, 55 FR 25446, June 21, 1990, as amended by CGD 95-072, 60 FR 50462, Sept. 29, 1995; CGD 96-041, 61 FR 50727, Sept. 27, 1996]

§ 39.10-11 Personnel training—TB/ALL.

(a) A person in charge of a transfer operation utilizing a vapor collection system must have completed a training program covering the particular system installed on the vessel. Training must include drills or demonstrations using the installed vapor control system covering normal operations and emergency procedures.

(b) The training program required by paragraph (a) of this section must cover the following subjects:

- (1) Purpose of a vapor control system;
- (2) Principles of the vapor control system;
- (3) Components of the vapor control system;
- (4) Hazards associated with the vapor control system;
- (5) Coast Guard regulations in this part;
- (6) Operating procedures, including:
 - (i) Testing and inspection requirements,
 - (ii) Pre-transfer procedures,
 - (iii) Connection sequence,
 - (iv) Start-up procedures, and

- (v) Normal operations; and
- (7) Emergency procedures.

[CGD 88-102, 55 FR 25446, June 21, 1990; 55 FR 39270, Sept. 26, 1990]

§ 39.10-13 Submission of vapor control system designs—TB/ALL.

(a) Plans, calculations, and specifications for a new vessel vapor collection system must be submitted to the Marine Safety Center for approval prior to installation.

(b) An existing vapor collection system installation that has been Coast Guard approved to transfer cargo vapor to specific facilities must be reviewed and approved by the Marine Safety Center prior to transferring vapors to other facilities.

(c) The owners/operators of a foreign flag vessel may submit certification by the classification society which classes the vessel that the vessel meets the requirements of this part as an alternative to meeting the requirements in paragraphs (a) and (b) of this section.

(d) Upon satisfactory completion of plan review and inspection of the vapor collection system or receipt of the certification provided for in paragraph (d) of this section, the Officer in Charge, Marine Inspection, shall endorse the Certificate of Inspection for U.S. flag vessels, or the Certificate of Compliance for foreign flag vessels, that the vessel is acceptable for collecting the vapor from crude oil, gasoline blends, and benzene, or any other vapor it is found acceptable to collect.

[CGD 88-102, 55 FR 25446, June 21, 1990, as amended by CGD 95-028, 62 FR 51200, Sept. 30, 1997]

Subpart 39.20—Design and Equipment

§ 39.20-1 Vapor collection system—TB/ALL.

(a) Each vapor collection system must meet the following requirements:

- (1) Except as allowed by paragraph (a)(3) of this section or the Commandant (G-MSO), vapor collection piping must be permanently installed, with the vessel's vapor connection located as close as practical to the loading manifold;

(2) If the vessel collects vapors from incompatible cargoes simultaneously, it must keep the incompatible vapors separate throughout the entire vapor collection system;

(3) A vessel certified to carry cargo listed in Table 151.05 of part 151 or Table 1 of part 153 of this chapter may have vapor connections located in the vicinity of each tank in order to preserve segregation of cargo systems, in lieu of common header piping;

(4) A means must be provided to eliminate liquid condensate which may collect in the system, such as draining and collecting liquid from each low point in the line;

(5) Vapor collection piping must be electrically bonded to the hull and must be electrically continuous; and

(6) An inerted tankship must have a means to isolate the inert gas supply from the vapor collection system. The inert gas main isolation valve required by SOLAS 74, as amended, chapter II-2, Regulation 62.10.8 may be used to satisfy this requirement.

(b) The vapor collection system must not interfere with the proper operation of the cargo tank venting system.

(c) An isolation valve capable of manual operation must be provided at the vessel vapor connection. The valve must have an indicator to show clearly whether the valve is in the open or closed position, unless the valve position can be readily determined from the valve handle or valve stem.

(d) The last 1.0 meter (3.3 feet) of vapor piping before the vessel vapor connection must be:

- (1) Painted red/yellow/red with:
 - (i) The red bands 0.1 meter (0.33 feet) wide, and
 - (ii) The middle yellow band 0.8 meter (2.64 feet) wide; and
- (2) Labeled "VAPOR" in black letters at least 50 millimeters (2 inches) high.

(e) Each vessel vapor connection flange must have a permanently attached 0.5 inch diameter stud at least 1.0 inch long projecting outward from the flange face. The stud must be located at the top of the flange, midway between bolt holes, and in line with the bolt hole pattern.

(f) Each hose used for transferring vapors must:

(1) Have a design burst pressure of at least 25 psig;

(2) Have a maximum allowable working pressure of at least 5 psig;

(3) Be capable of withstanding at least 2.0 psi vacuum without collapsing or constricting;

(4) Be electrically continuous with a maximum resistance of ten thousand (10,000) ohms;

(5) Have flanges with:

(i) A bolt hole arrangement complying with the requirements for 150 pound class ANSI B16.5 flanges, and

(ii) One or more 0.625 inch diameter holes in the flange located midway between bolt holes and in line with the bolt hole pattern;

(6) Be abrasion resistant and resistant to kinking; and

(7) Have the last 1.0 meter (3.3 feet) of each end of the vapor hose marked in accordance with paragraph (d) of this section.

(g) Vapor hose handling equipment must be provided with hose saddles which provide adequate support to prevent kinking or collapse of hoses.

[CGD 88-102, 55 FR 25446, June 21, 1990, as amended by CGD 95-072, 60 FR 50462, Sept. 29, 1995; CGD 96-041, 61 FR 50727, Sept. 27, 1996]

§39.20-3 Cargo gauging system—TB/ALL.

(a) Each cargo tank of a tank vessel that is connected to a vapor collection system must be equipped with a cargo gauging device which:

(1) Provides a closed gauging arrangement as defined in §151.15.10 of this chapter that does not require opening the tank to the atmosphere during cargo transfer;

(2) Allows the operator to determine the liquid level in the tank for the full range of liquid levels in the tank;

(3) Indicates the liquid level in the tank at the location where cargo transfer is controlled; and

(4) If portable, is installed on the tank during the entire transfer operation.

(b) Except when a tank barge complies with §39.20-9(a) of this part, each cargo tank of a barge must have a high level indicating device that:

(1) Provides a visual indication of the liquid level in the cargo tank when the

cargo level is within 1.0 meter (3.28 feet) of the tank top;

(2) Has the maximum liquid level permitted under §39.30-1(e) of this part at even keel conditions conspicuously and permanently marked on the indicating device; and

(3) Is visible from all cargo control areas on the tank barge.

§39.20-7 Tankship liquid overfill protection—T/ALL.

(a) Each cargo tank of a tankship must be equipped with an intrinsically safe high level alarm and a tank overfill alarm.

(b) The high level alarm and tank overfill alarm required by paragraph (a) of this section, if installed after July 23, 1990 must:

(1) Be independent of each other;

(2) Alarm in the event of loss of power to the alarm system or failure of electrical circuitry to the tank level sensor; and

(3) Be able to be checked at the tank for proper operation prior to each transfer or contain an electronic self-testing feature which monitors the condition of the alarm circuitry and sensor.

(c) The high level alarm required by paragraph (a) of this section must:

(1) Alarm before the tank overfill alarm, but no lower than 95 percent of tank capacity;

(2) Be identified with the legend "High Level Alarm" in black letters at least 50 millimeters (2 inches) high on a white background; and

(3) Have audible and visible alarm indications that can be seen and heard on the vessel where cargo transfer is controlled.

(d) The tank overfill alarm required by paragraph (a) of this section must:

(1) Be independent of the cargo gauging system;

(2) Have audible and visible alarm indications that can be seen and heard on the vessel where cargo transfer is controlled and in the cargo deck area;

(3) Be identified with the legend "TANK OVERFILL ALARM" in black letters at least 50 millimeters (2 inches) high on a white background; and

(4) Alarm early enough to allow the person in charge of transfer operations

to stop the transfer operation before the cargo tank overflows.

(e) If a spill valve is installed on a cargo tank fitted with a vapor collection system, it must meet the requirements of § 39.20-9(c) of this part.

(f) If a rupture disk is installed on a cargo tank fitted with a vapor collection system, it must meet the requirements of § 39.20-9(d) of this part.

§ 39.20-9 Tank barge liquid overflow protection—B/ALL.

Each cargo tank of a tank barge must have one of the following liquid overflow protection arrangements.

(a) A system meeting the requirements of § 39.20-7 of this part which:

(1) Includes a self-contained power supply;

(2) Is powered by generators installed on the barge; or

(3) Receives power from a facility and is fitted with a shore tie cable and a 120 volt 20 amp explosion-proof plug which meets:

(i) ANSI/NEMA WD6;

(ii) NFPA 70, Articles 410-57 and 501-12; and

(iii) § 111.105-9 of this chapter.

(b) An intrinsically safe overflow control system which:

(1) Is independent of the cargo gauging device required by § 39.20-3(a) of this part;

(2) Actuates an alarm and automatic shutdown system at the facility overflow control panel, or on the vessel to be lightered if a lightering operation, 60 seconds before the tank becomes 100 percent liquid full;

(3) Is able to be checked at the tank for proper operation prior to each loading;

(4) Consists of components which, individually or in series, will not generate or store a total of more than 1.2 V, 0.1 A, 25 mW, or 20 microjoules;

(5) Has at least one tank overflow sensor switch with normally closed contacts per cargo tank;

(6) Has all tank overflow sensor switches connected in series;

(7) Has interconnecting cabling that meets § 111.105-15(b) of this chapter; and

(8) Has a male plug with a 5 wire, 16 amp connector body meeting IEC 309-1/309-2 which is:

(i) Configured with pins S2 and R1 for the tank overflow sensor circuit, pin G connected to the cabling shield, and pins N and T3 reserved for an optional high level alarm circuit meeting the requirements of this paragraph; and

(ii) Labeled "Connector for Barge Overflow Control System" and with the total inductance and capacitance of the connected switches and cabling.

(c) A spill valve which:

(1) Meets ASTM F1271;

(2) Relieves at a pressure higher than the pressure at which the pressure relief valves meeting the requirements of § 39.20-11 operate;

(3) Limits the maximum pressure at the cargo tank top during liquid overflow, at the maximum loading rate for the tank, to not more than the maximum design working pressure for the tank; and

(4) If the vessel is in ocean or coastwise service, has provisions to prevent opening due to cargo sloshing.

(d) A rupture disk arrangement which meets paragraphs (c)(2), (c)(3) and (c)(4) of this section and is approved by the Commandant (G-MSO).

[CGD 88-102, 55 FR 25446, June 21, 1990, as amended by CGD 95-072, 60 FR 50462, Sept. 29, 1995; CGD 96-041, 61 FR 50727, Sept. 27, 1996]

§ 39.20-11 Vapor overpressure and vacuum protection—TB/ALL.

(a) The cargo tank venting system required by § 32.55 of this chapter must:

(1) Be capable of discharging cargo vapor at 1.25 times the maximum transfer rate such that the pressure in the vapor space of each tank connected to the vapor collection system does not exceed:

(i) The maximum design working pressure for the tank, or

(ii) If a spill valve or rupture disk is fitted, the pressure at which the device operates;

(2) Not relieve at a pressure corresponding to a pressure in the cargo tank vapor space of less than 1.0 psig;

(3) Prevent a vacuum in the cargo tank vapor space, whether generated by withdrawal of cargo or vapor at maximum rates, that exceeds the maximum design vacuum for any tank connected to the vapor collection system; and

(4) Not relieve at a vacuum corresponding to a vacuum in the cargo tank vapor space of less than 0.5 psi below atmospheric pressure.

(b) Each pressure-vacuum relief valve must:

(1) Be tested for venting capacity in accordance with paragraph 1.5.1.3 of API 2000; and

(2) Have a means to check that the device operates freely and does not remain in the open position, if installed after July 23, 1991.

(c) The relieving capacity test required by paragraph (b)(1) of this section must be carried out with a flame screen fitted at the vacuum relief opening and at the discharge opening if the pressure-vacuum relief valve is not designed to ensure a minimum vapor discharge velocity of 30 meters (98.4 ft.) per second.

§ 39.20-13 High and low vapor pressure protection for tankships—T/ALL.

Each tankship vapor collection system must be fitted with a pressure sensing device that senses the pressure in the main vapor collection line, which:

(a) Has a pressure indicator located on the vessel where the cargo transfer is controlled; and

(b) Has a high pressure and a low pressure alarm that:

(1) Is audible and visible on the vessel where cargo transfer is controlled;

(2) Alarms at a high pressure of not more than 90 percent of the lowest pressure relief valve setting in the cargo tank venting system; and

(3) Alarms at a low pressure of not less than four inches water gauge (0.144 psig) for an inerted tankship, or the lowest vacuum relief valve setting in the cargo tank venting system for a non-inerted tankship.

Subpart 39.30—Operations

§ 39.30-1 Operational requirements—TB/ALL.

(a) Vapor from a tank vessel may not be transferred to:

(1) A facility in the United States which does not have its letter of adequacy endorsed as meeting the requirements of 33 CFR part 154, subpart E; or

(2) In the case of a lightering or topping off operation, a vessel which does not have its certificate of inspection or certificate of compliance endorsed as meeting the requirements of this part.

(b) The pressure drop through the vapor collection system from the most remote cargo tank to the vessel vapor connection must be:

(1) Determined for each cargo handled by the vapor collection system at the maximum transfer rate and at lesser transfer rates;

(2) Based on a 50 percent cargo vapor and air mixture, and a vapor growth rate appropriate for the cargo being loaded; and

(3) Included in the vessel's oil transfer procedures as a table or graph showing the liquid transfer rate versus the pressure drop.

(c) If a vessel carries vapor hoses, the pressure drop through the hoses must be included in the pressure drop calculations required by paragraph (b) of this section.

(d) The rate of cargo transfer must not exceed the maximum allowable transfer rate as determined by the lesser of the following:

(1) Eighty (80) percent of the total venting capacity of the pressure relief valves in the cargo tank venting system when relieving at the set pressure required by § 39.20-11(a) of this part;

(2) The total vacuum relieving capacity of the vacuum relief valves in the cargo tank venting system when relieving at the set pressure required by § 39.20-11(a) of this part;

(3) The rate based on pressure drop calculations at which, for a given pressure at the facility vapor connection, or if lightering at the vapor connection of the vessel receiving cargo, the pressure in any cargo tank connected to the vapor collection system exceeds 80 percent of the setting of any pressure relief valve in the cargo tank venting system.

(e) A cargo tank must not be filled higher than:

(1) 98.5 percent of the cargo tank volume; or

(2) The level at which an overflow alarm complying with § 39.20-7 or § 39.20-9(b)(2) of this part is set.

(f) A cargo tank must not be opened to the atmosphere during cargo transfer operations except as provided in paragraph (g) of this section.

(g) A cargo tank may be opened to the atmosphere for gauging or sampling while a tank vessel is connected to a vapor control system if the following conditions are met:

- (1) The cargo tank is not being filled;
- (2) Except when the tank is inerted, any pressure in the cargo tank vapor space is first reduced to atmospheric pressure by the vapor control system;
- (3) The cargo is not required to be closed or restricted gauged by Table 151.05 of part 151 or Table 1 in part 153 of this chapter; and
- (4) For static accumulating cargo, all metallic equipment used in sampling or gauging is electrically bonded to the vessel before it is put into the tank, remains bonded to the vessel until it is removed from the tank, and if the tank is not inerted, a period of 30 minutes has elapsed since loading of the tank was completed.

(h) For static accumulating cargo the initial transfer rate must be controlled in accordance with Section 7.4 of the OCIMF, International Safety Guide for Oil Tankers and Terminals, in order to minimize the development of a static electrical charge.

(i) If cargo vapor is collected by a facility that requires the vapor from the vessel to be inerted in accordance with 33 CFR 154.820(a) or (b), the oxygen content in the vapor space of each cargo tank connected to the vapor collection system must not exceed 8 percent by volume at the start of cargo transfer. The oxygen content of each tank must be measured at a point one meter (3.28 feet) below the tanktop and at a point equal to one-half of the ullage. Where tanks have partial bulkheads, the oxygen content of each area of that tank formed by each partial bulkhead must be measured at a point one meter (3.28 feet) below the tanktop and at a point equal to one-half of the ullage.

(j) If the vessel is equipped with an inert gas system, the isolation valve required by §39.20-1(a)(6) of this part must remain closed during vapor transfer.

(k) Unless equipped with an automatic self-test and circuit monitoring

feature, each high level alarm and tank overfill alarm required by §39.20-7 or §39.20-9 of this part, on a cargo tank being loaded, must be tested at the tank for proper operation within 24 hours prior to the start of cargo transfer.

[CGD 88-102, 55 FR 25446, June 21, 1990; 55 FR 39270, Sept. 26, 1990]

Subpart 39.40—Lightering and Topping-Off Operations with Vapor Balancing

§39.40-1 General requirements for vapor balancing—TB/ALL.

(a) Except as provided in paragraph (b) of this section, each vessel which uses vapor balancing while conducting a lightering or topping-off operation must meet the requirements of this subpart in addition to the requirements of subparts 39.10, 39.20, and 39.30 of this part.

(b) An arrangement to control vapor emissions during a lightering or topping-off operation which does not use vapor balancing must receive approval from the Commandant (G-MSO).

(c) A vapor balancing operation must not use a compressor or blower to assist vapor transfer without approval from the Commandant (G-MSO).

(d) Vapor balancing is prohibited when the cargo tanks on a vessel discharging cargo are inerted and the cargo tanks on a vessel receiving cargo are not inerted.

(e) A vessel which intends to engage in a lightering or topping-off operation while collecting cargo vapor from other than crude oil, gasoline, or benzene must receive specific approval from the Commandant (G-MSO).

[CGD 88-102, 55 FR 25446, June 21, 1990; 55 FR 39270, Sept. 26, 1990, as amended by CGD 95-072, 60 FR 50462, Sept. 29, 1995; CGD 96-041, 61 FR 50727, Sept. 27, 1996]

§39.40-3 Design and equipment for vapor balancing—TB/ALL.

(a) If the cargo tanks on a vessel discharging cargo and a vessel receiving cargo are inerted, the service vessel must:

- (1) Have a means to inert the vapor transfer hose prior to transferring cargo vapor; and

(2) Have an oxygen analyzer with a sensor or sampling connection fitted within 3 meters (9.74 ft.) of the vessel vapor connection which:

(i) Activates an audible and visible alarm at a location on the service vessel where cargo transfer is controlled when the oxygen content in the vapor collection system exceeds 8 percent by volume;

(ii) Has an oxygen concentration indicator located on the service vessel where the cargo transfer is controlled; and

(iii) Has a connection for injecting a span gas of known concentration for calibration and testing of the oxygen analyzer.

(b) If the cargo tanks on a vessel discharging cargo are not inerted, the vapor collection line on the service vessel must be fitted with a detonation arrester that meets the requirements of 33 CFR 154.822(a) located within 3 meters (9.74 ft.) of the vessel vapor connection.

(c) An electrical insulating flange or one length of non-conductive hose must be provided between the vessel vapor connection on the service vessel and the vapor connection on the vessel being lightered or topped-off.

§ 39.40-5 Operational requirements for vapor balancing—TB/ALL.

(a) During a lightering or topping-off operation each cargo tank being loaded must be connected by the vapor collection system to a cargo tank which is being discharged.

(b) If the cargo tanks on both the vessel discharging cargo and the vessel receiving cargo are inerted, the following requirements must be met:

(1) Each tank on a vessel receiving cargo which is connected to the vapor collection system must be tested prior to cargo transfer to ensure that the oxygen content in the vapor space does not exceed 8 percent by volume. The oxygen content of each tank must be measured at a point one meter (3.28 feet) below the tanktop and at a point equal to one-half of the ullage. Where tanks have partial bulkheads, the oxy-

gen content of each area of that tank formed by each partial bulkhead must be measured at a point one meter (3.28 feet) below the tanktop and at a point equal to one-half of the ullage;

(2) The oxygen analyzer required by § 39.40-3(a) must be tested for proper operation prior to the start of each transfer operation;

(3) The oxygen content of vapors being transferred must be continuously monitored during the transfer operation;

(4) Cargo transfer must be terminated if the oxygen content exceeds 8 percent by volume and must not be restarted until the oxygen content in the tanks of the vessel receiving cargo is reduced to 8 percent by volume or less; and

(5) The vapor transfer hose must be purged of air and inerted prior to starting vapor transfer.

(c) The isolation valve, required by § 39.20-1(c) of this part, located on the service vessel must not be opened until the pressure in the vapor collection system on the vessel receiving cargo exceeds the pressure in the vapor collection system on the vessel discharging cargo.

(d) The cargo transfer rate must be controlled from the vessel discharging cargo, and must not exceed the maximum allowable transfer rate for the vessel receiving cargo.

(e) The pressure in the vapor space of any cargo tank connected to the vapor collection line on either the vessel receiving cargo or the vessel discharging cargo must not exceed 80 percent of the lowest setting of any pressure relief valve during ballasting or cargo transfer.

(f) All impressed current cathodic protection systems must be deenergized during cargo transfer operations.

(g) Tank washing is prohibited unless the cargo tanks on both the vessel discharging cargo and the vessel receiving cargo are inerted or the tank is isolated from the vapor collection line.

[CGD 88-102, 55 FR 25446, June 21, 1990; 55 FR 39270, Sept. 26, 1990]

INDEX

SUBCHAPTER D—TANK VESSELS

EDITORIAL NOTE: This listing is provided for informational purposes only. It is compiled and kept current by the Coast Guard, Department of Transportation.

Part, subpart, or section

A

Accident or casualty report	Subpart 35.15
Accommodations for crew	Subpart 32.40
Application	32.40-1
Construction	32.40-15
Heating and cooling	32.40-50
Hospital space	32.40-35
Insect screens	32.40-55
Location of Crew spaces	32.40-10
Messrooms	32.40-30
On tankships constructed before June 15, 1987	32.40-65
On tankships of less than 100 gross tons and manned tank barges	32.40-60
Other spaces	32.40-40
Sleeping Accommodations	32.40-20
Washrooms and toilet rooms	32.40-25
Aids to Navigation:	
Charts or information regarding	35.20-1
Coast pilots	35.20-1
Current tables	35.20-1
Light lists	35.20-1
Nautical publications	35.20-1
Notice to Mariners	35.20-1
Sailing directions	35.20-1
Tide tables	35.20-1
Air compressor	32.35-15, 35.35-85
Alarm bells	32.25
Marking required	35.40-5
Switches, markings of	35.40-1
Alarm systems Subpart	32.25
Alcohol or drugs, used by crew	35.05-25
Alterations and repairs, regulations governing	30.01-10, 31.10-25
American Bureau of Shipping	31.10-1
Annual inspection:	
Application for:	31.01-15
Fire extinguishers	31.10-18
Anode installations, sacrificial	35.01-25
Appeal right of	30.20-50
Application for inspection	31.01-15, 31.1-20
Application, electrical installations Subpart	32.45
Application of regulations:	
Governing alterations and repairs	30.01-10
Vessels on an international voyage	30.01-6
Approved, definition	30.10-3

46 CFR Ch. I (10-1-98 Edition)

Arresters, flame.....	30.10-23, 32.20-10
Assignment of functions.....	31.01-10
Auto pilot.....	35.20-45
Auxiliary machinery:	
Design.....	32.35-1
Construction.....	32.35-1
Installation of internal combustion engines.....	32.35-5
Axes, fire.....	34.05-20, 34.60

B

Ballasting.....	31.10-32
Bell, alarm Subpart.....	32.25
Bell signals.....	32.30-5
Bilge injection valves.....	31.10-20
Bilge systems Subpart.....	32.52
Bills of lading required.....	35.01-10
Boilerroom, fire extinguishing systems for.....	34.05-5
Boilers:	
Accident report by chief engineer.....	35.25-5
Examination by engineer.....	35.25-1
Safety rules for fires.....	35.30-5
Breeches buoy, poster containing instruction regarding use of.....	Subpart 35.12
Breathing apparatus, fresh air.....	35.30-20, 35.40-20
Butterworth plates, safety rules regarding.....	35.30-10

C

Carbon dioxide extinguishing systems:	
Alarms.....	34.15-30
Amount of carbon dioxide required.....	34.15-5
Application.....	34.15-1
Controls.....	34.15-10
Discharge outlets.....	34.15-25
Dry cargo spaces.....	34.15-5
Enclosed ventilation systems for rotating electrical propulsion equip- ment.....	34.15-5
Enclosure openings.....	34.15-35
Installation contracted for prior to January 1, 1962.....	34.15-90
Machinery spaces pumprooms paint lockers and similar spaces.....	34.15-5
Piping.....	34.15-15
Pressure relief.....	34.15-40
Quantity, pipe sizes, and discharge rates.....	34.15-5
Storage.....	34.15-20
Total available supply.....	34.15-5
Cargo definition.....	30.10-5
Cargo discharge.....	32.5-3
Cargoes elevated temperatures.....	Part 36
Cargoes regulated.....	Subpart 30.25
Cargo gear certificates or registers.....	31.10-16, Subpart 31.37
Cargo gear inspection.....	31.10-16, 31.37
Cargo handling:	
Equipment maintenance.....	35.35-70
General.....	35.35
Liquefied petroleum gases.....	Subpart 38.15
Loading information.....	35.35
Safety requirements.....	35.30
Unmanned tank barges.....	35.35-1

Subchapter D Index

Cargo handling room, definitions	30.10-6
Cargo hose	35.35-15, 35.35-70, 38.15-5
Cargo piping	40.15-1, 38.10-10
Cargo pumps	Subpart 32.50
Cargo pump relief valves	36.10-1
Cargo pump, testing of	35.35-70
Cargo tank hatches, ullage holes and Butterworth plates, safety rules re- garding	35.30-10
Cargo tanks:	
Construction and testing of	32.60-40, 32.65-40, 32.70-25, 32.75-10
Design and installation of	38.05
Electric bonding and grounding of	32.75-15
Filling densities	38.15-1
Fire extinguishing systems for	34.05-5
Hydrostatic test of	38.25-1
Installation for carrying liquids at elevated temperatures	36.05-1
Independent	32.60-30, 32.65-30, 32.70-25, 32.75-10
Lagging	38.05-20
Liquid level gauging devices	38.10-20, 32.20-20
Liquefied petroleum gases	Part 38
Marking of	38.05-5
Periodic test	38.25-1
Piping	38.10-10
Refrigeration system used with	38.05-25
Removal from service	38.25-5
Venting of	Subpart 32.55, 38.20-1, 38.20-5
Cargo transfer:	
Approval of	35.35-25
Conditions affecting	35.35-40
Connecting of cargo hose	35.35-15
Declaration of inspection	35.35-30
Duties of senior deck officer	35.35-35
Electric bonding	35.35-5
Filling densities	38.15-1
Handling of packaged goods, etc	35.35-55
Inspection prior to	35.35-20
Liquefied flammable gases	38.15-5
Maintenance of equipment	35.35-70
Men on duty	35.35-1
Tank barges	35.35-60
Termination of	35.35-50
Towing vessels furnishing steam, air or electricity	35.35-45
Vapor control systems	Part 39
Vessels coming alongside during	35.35-42
Carriage of person other than crew	35.01-15
Casualty or accident report Subpart	35.15
Certificate of class	31.10-5
Certificate of inspection:	
Application for	31.01-15, 31.01-20
Cargoes of elevated temperatures, carriage of	36.01-5
Delivery of	31.05-1
Endorsed for liquefied flammable gas	38.01-5
Indication of water traveled on	31.20-1
Ocean or unlimited coastwise vessels on inland and Great Lakes Routes-TB/OC	30.01-7
Posting of	31.05-5
Terms, endorsements	31.05-15
Certificates regarding shipboard cargo gear	31.10-16, 31.37

46 CFR Ch. I (10–1–98 Edition)

Certificates under International Convention for Safety of Life at Sea.....	31.10–16, 31.37
1960 American Bureau of Shipping	31.40–45
Application	31.40–1
Cargo Ship Safety Construction Certificate	31.40–5
Cargo Ship Safety Equipment Certificate.....	31.40–10
Cargo Ship Safety Radiotelegraphy Certificate.....	31.40–15
Cargo Ship Safety Radiotelephony Certificate	31.40–20
Duration of Convention Certificate.....	31.40–40
Exemption Certificate.....	31.40–25
Posting of Convention Certificates	31.40–35
Certified crewmembers	31.15–1
Certified definition	30.10–7
Charts of navigable waters required	35.20–1
Chief Engineer:	
Repairs of boilers and unfired pressure vessels and reports or acci- dents	35.25–5
Class, certificate of.....	31.10–5
Classification requirements, definition	30.10–9
CO2 fire apparatus, marking required	35.40–10
Coast Guard District Commander	30.10–19
Coast pilots.....	35.20–1
Coastwise, definition.....	30.10–11
Cofferdam:	
Definition of.....	30.10–13
Location of.....	32.60–10, 32.65–15, 32.70–10
Requirements of	32.70–10
Venting of	32.55–45
Combustible gas indicator.....	35.30–15
Combustible liquids, definition	30.10–15
Commadant, definition	30.10–17
Commodities regulated.....	Subpart 30.25
Communication, interior system	Subpart 32.30
Construction and testing of cargo tanks and bulkheads on tank vessels.....	32.65–40, 32.60–40, 32.75–10
Construction of tank barges of materials other than steel or iron, re- quirements.....	32.80–1
Construction of tank vessels:	
Cargo spaces segregated from cargo tanks.....	32.57–10, 32.60
Ceilings	32.57–1
Deck	32.57–10
Enclosed spaces	32.60–10
General cargo spaces	32.60–15
Hatch covers.....	32.57–10
Hull requirements.....	32.60, 32.65, 32.70, 32.75
Lamp Lockers	32.57–10
Living quarters	32.60–25, 32.65–25
Location of cargo tank spaces.....	32.60–10
Location of independent tanks.....	32.60–30
Machinery.....	32.35–1
Paint lockers.....	32.57–10
Requirements for scantlings, material and workmanship	32.60–1, 32.65–1, 32.70– 5, 32.75–5
Segregation of cargo	32.60–10
Stowage spaces.....	32.60–10
Subdivision of cargo space	32.60–5, 32.65–10
Testing of cargo tanks and bulkheads	32.60–40, 32.65–40, 32.70–25, 32.75–10

Subchapter D Index

Construction of vessels for liquefied gases	38.05-1
Construction of wood hull tank vessels:	
Application of regulations	32.75-1
Electric bonding and grounding of cargo tanks	32.75-15
Hold spaces.....	32.75-20
Independent cargo tanks	32.75-10
Convention certificates.....	Subpart 31.40
Conversion of vessels to tank vessels	31.10-10
Crew:	
Certified members of	31.15-1
Illness of.....	35.05-25
Licensed officers	31.15-1
Physical condition of	35.05-20
Required for cargo handling	35.35-1
Crew accommodations:	
Inspection of.....	31.10-45
Requirements for	Subpart 32.40
Sanitary condition of.....	35.01-5
Current tables.....	35.20-1

D

Deck foam system.....	Subpart 34.20
Declaration of inspection prior to bulk cargo transfer	35.35-30
Definition of term	Subpart 30.10
Delivery of certificate of inspection	31.05-1
Design:	
Cargo tanks	38.05-2
Main and auxiliary machinery	32.35-1
Vapor control system.....	Subpart 39.20
Devices, spark producing.....	35.30-35
Display of Plans.....	35.10-3
Draft marks	32.05-1, 35.20-5
Drills:	
Boat	35.10-5
Fire	35.10-5
Line throwing appliance	35.10-1
Drydock or hauling out	31.10-20

E

Effective date of regulation	30.01-15
Electric bonding and grounding	32.75-15, 35.35-5
Electrical installations.....	31.35, 32.45
Elevated temperature cargoes:	
Cargo pump relief valves	36.10-1
Certificate of inspection	36.01-5
Flame Screens, vents and ventilations.....	36.20-1
Installation of cargo tanks	36.05-1
Lagged tanks, periodic inspections.....	36.30-1
Protection of personnel	36.05-10
Ventilation of pumproom	36.20-5
Emergency:	
Authority of senior officer	35.35-75
Breathing equipment, marking.....	35.40-20
Lighting and power systems.....	35.10-15
Outfit.....	35.30-20
Repairs to firefighting equipment.....	35.01-35

46 CFR Ch. I (10-1-98 Edition)

Signals.....	35.10-5
Training.....	35.10-1
Enclosed ventilating system, fire extinguishing system.....	34.05-5
Enforcement.....	30.20-1
Engineering, electrical.....	31.35, 32.45
Engineering, marine Subpart.....	31.30
Equipment:	
Cargo handling.....	Subpart 32.50
Emergency.....	35.30-20
Fire and emergency, marking.....	Subpart 35.40, 35.40-40
Installed but not required.....	34.01-5
Portable electrical.....	35.30-30
Previously approved.....	30.01-15
Equipment installations Subpart.....	32.20
Equipment installations on vessels during World War II.....	32.20-1
Equipment, navigation Subpart.....	32.15
Equivalentents.....	30.15-1
Escape, means of.....	32.02-1
Examination of tail shaft.....	61.15-15
Examination of sea chests, sea valves, sea strainers, and bilge injection valves.....	31.10-20
Exemption certificate.....	31.40-25
Explosives, transportation of.....	35.30-25

F

Fire axes.....	34.05-20, 34.60
Location of.....	34.60-10
Number required.....	34.60-5
Fire drills.....	35.10-5
Fire extinguishers, portable and semiportable:	
Application.....	34.50-1
Classification.....	34.50-5
Location.....	34.50-10
Spare charges.....	34.50-15
Vessels contracted for prior to January 1, 1962.....	34.50-90
Fire extinguishing deck foam system:	
Application.....	34.20-1
Area protected.....	34.20-5
Cargo area definitions.....	34.20-3
Controls.....	34.20-10
Discharge outlets.....	34.20-20
Installations contracted for prior to January 1, 1970.....	34.20-90
Marking.....	35.40-10
Piping.....	34.20-15
Quantity of foam required.....	34.20-5
Rate of application.....	34.20-5
Separate supply of foam-producing material.....	34.20-5
Supply of foam producing material.....	34.20-5
Water supply.....	34.20-5
Fire extinguishing fixed foam systems:	
Additional protection required.....	34.17-25
Application.....	34.17-1
Area protected.....	34.17-5
Controls.....	34.17-10
Discharge outlets.....	34.17-20
Installations contracted for prior to January 1, 1962.....	34.17-90
Piping.....	34.17-15

Subchapter D Index

Rate of Application.....	34.17-5
Separate supply of foam-producing material	34.17-5
Supply of foam producing material	34.17-5
Water supply for required pumps.....	34.17-5
Fire extinguishing systems:	
Boilerrooms	34.05-5
Carbon dioxide	34.15
Cargo tanks	34.05-5
Dry cargo compartments	34.05-5
Enclosed ventilating systems	34.05-5
Foam, deck.....	Subpart 34.20
Foam, fixed	Subpart 34.17
Installations contracted for prior to January 1, 1962	34.10-90
Lamp, paint lockers and similar pages.....	34.05-5
Machinery spaces.....	34.05-5
Marking.....	35.40-10
Piping.....	34.10-15
Pumprooms	34.05-5
Fire extinguishing system, steam smothering:	
Application	34.13-1
Installations contracted for prior to January 1, 1962	34.17-90
Firefighting equipment:	
Application	34.01-1
Fire axes.....	34.05-20, 34.60
Fire main system.....	34.05-1
Hose.....	34.10-10
Nozzles	35.40-10
Hydrants.....	35.40-15
Installed but not required.....	34.01-5
Portable, vessel's name on	35.40-40
Protection for unusual arrangements or special products	34.01-10
Testing and inspection.....	31.10-18, 31.10-19
Fire main system:	
Application	34.10-1
Fire pumps.....	34.10-5
Fire station hydrants hose and nozzles.....	34.10-10
Fire, matches and smoking safety rules.....	35.30-5
Fire protection, structural, for tank vessels contracted for on or after	
January 1, 1963	Subpart 32.57
Fire protection, structural for ships with a keel laying date on or after	
January 1, 1975	Subpart 32.56
Fire station	34.10-10
Fitting and piping for liquefied petroleum gases	38.10-10
Fittings, cargo	Subpart 32.50
Flame arresters	30.10-23, 32.20-10
Flame screen	30.10-25, 36.20-1
Flammable liquid, definition	30.10-22
Flammable liquid and gas fuels as ships' stores.....	35.30-40
Flammable or inflammable, definition.....	30.10.21
Flashpoint, definition	30.10-27
Foam hose/monitor stations.....	35.40-17
Fresh air breathing apparatus	35.30-20, 35.40-20
Fuel oil, requirements.....	35.25-10
Fuels, flammable liquid and gas.....	35.30-40
Functions, assignment of.....	30.01-3

G

Galley fires, safety rules.....	35.30–5
Gangway signs	35.30–1
Gas chemist certified by American Bureau of Shipping	35.01–1
Gas free, definition.....	30.10–29
Gauge, liquid level	32.20–20, 38.10–20, 39.20–3
Gear, shipboard cargo, certificates or registers	31.10–16, 31.37
General alarm switch, marking of.....	35.40–1
General alarm systems:	
Alarm bells for tankships constructed on or after September 15, 1943	32–25–1
Alarm bells for tankships constructed prior to September 15, 1943	32.25
Alarm bells for manned barges	32.25
General rules and regulations	30.10–31
Grade D, combustible liquid.....	30.10–15
Grade E, combustible liquid.....	30.10–15
Great Lakes.....	30.10–33

H

Hauling out or drydocking	31.10–20
Headquarters.....	30.10–35
Hose, cargo	32.50–30
Hospital accommodations.....	32.40–1
Hull and cargo tank requirements:	
Alternative arrangements	32.63–8
Application	32.63–1
Barge hull classifications	32.63–5
Cargo tanks and supports.....	32.63–25
Hull structure	32.63–20
Rakes and coamings.....	32.63–10
Hull requirements.....	32.60, 32.63, 32.65, 32.70, 32.75, 32.80
Hydrostatic test for cargo tanks	38.25–1

I

Independent cargo tanks	32.60–30, 32.60–35, 32.65–30, 32.70–25 32.75–10
Inert gas system.....	Subpart 32.53
Inspection:	
Alternations and repairs	31.10–25
Bilges	31.10–50
Certificate of.....	Subpart 31.05
Conversion of a vessel to a tank vessel, application for.....	31.01–20
Crew accommodations.....	31.10–45
During trial trip.....	31.10–40
General requirements	Subpart 31.01
Initial, scope of.....	31.01–5
Lagged tanks	36.30–1
New tank vessel.....	31.01–20, 31.10–5
Plans and specifications	31.10–5
Recognized classification society	31.10–1
Required	31.01–1
Required before making repairs.....	35.01–1
Required, liquefied, petroleum gas tanks	38.25–1
Required on new tank vessels	31.01–1
Safety valves	38.25–10
Two years.....	31.10–15, 31.10–17
Inspection and certification of cargo gear	31.10–16

Subchapter D Index

Inspection and test, periodic, of independent cargo tanks	38.25
Inspection of cargo gear:	
Additions to gear.....	31.37-60
Advance notice that cargo gear testing is desired	31.37-80
Alterations, renewals, or repairs of cargo gear	31.37-65
Annealing	31.37-55
Cargo gear plans.....	31.37-15
Certification.....	31.10-16
Definitions of terms.....	31.37-3
Dismantling or disassembling	31.37-3
Factors of safety	31.37-25
Loose gear certificates and tests.....	31.37-30
Marking of booms and cranes.....	31.37-45
Proof test of cargo gear as a unit.....	31.37-40
Records.....	31.37-75
Responsibility for conducting required tests and examinations	31.37-85
Responsibility of ship's officer for inspection of cargo gear	31.37-70
Safe working load	31.37-3
Tests and examinations of shipboard cargo gear	31.37-5
Thorough examination	31.37-3
Ton.....	31.37-3
When made.....	31.37-1
Installation of cargo tanks.....	38.05-10
Installation of internal combustion engines	32.35-5
Installations made during the Unlimited National Emergency	32.20-1
Internal combustion installations, fire extinguishing systems.....	34.05-5
International voyage	30.01-6
Interior communications system:	
Bell signals between engine room and pilothouse	32.30-5
Inspection of	32.30
Telegraph systems	32.30
Telephone equipment.....	32.30-1
Voice tubes	32.30-1
Issuance of certificates of inspection	31.05-1

L

Lagging for independent cargo tanks.....	38.05-20
Lakes, bays and sounds	30.10-41
Lamp and paintrooms:	
Fire extinguishing system for	34.05-5
Fireproofing of.....	32.85-1
Licensed officers required.....	31.15-1
Lifeboat drills.....	35.10-5
Lifesaving Appliances and Approaches	Subpart 31.36
Actions to be required.....	35.07-10
Certificate of inspection regulation	31.05-1
Drills.....	35.10-1
Inspections required	31.01-1
Musters	35.10-5
Lights, flashing the ray of.....	35.20-30
Light List	35.20-1
Liquid, flammable	30.10-22
Liquid level gauging devices.....	32.20-20, 38.10-1, 38.10-20, 39.20-3
Liquefied flammable gas	30.10-39
Cargo hose	38.15-5
Cargo piping	38.10-10
Certificate of inspection	38.01-5

46 CFR Ch. I (10–1–98 Edition)

Design and construction of cargo tanks	38.05–2
Design and construction of nonpressure vessel type cargo tanks.....	38.05–4
Design and construction of pressure vessel type cargo tanks.....	38.05–3
Design and construction of vessels, general	38.05–1
Electrical installations	38.15–15
Filling and discharge pipes.....	38.10–5
Filling of tanks.....	38.15–1
Installation of cargo tanks.....	38.05–10
Insulation.....	38.05–20
Leak detection systems.....	38.15–10
Liquid level gauging devices	38.10–20
Markings.....	38.05–5
Refrigerated systems.....	38.05–25
Remote shutdowns	38.15–20
Removal of defective tanks	38.25–5
Safety relief valves	38.25–10
Safety relief valves for pressure vessel type tanks	38.10–15
Scope of regulations	38.01–1
Tests and inspections.....	38.25–1
Transportation of	Part 38
Transportation of portable cylinders or portable tanks containing or having previously contained liquefied flammable gases in dry cargo spaces.....	38.01–2
Valves, fittings, and accessories.....	38.10–1
Vapor control system	Part 39
Ventilation.....	38.20–10
Venting.....	38.20–1, 38.20–5
Living quarters	32.60–25, 32.65–25
Load lines Subpart.....	31.25
Loading information	31.10–32
Logbook entries:	
Actions required to be logged.....	35.07–10
Application	35.07–1
Draft of tank ship	35.20–5
Fire and lifeboat drills.....	35.10–5
Fuel oil requirements.....	35.25–10
Logbooks and records	35.07–5
Steering gear tests.....	35.20–10

M

Machinery spaces, fire extinguishing systems for	34.05–5
Machinery, main and auxiliary:	
Accident report by chief engineer.....	35.25–5
Air compressors.....	32.35–15
Construction.....	32.35–1
Design	32.35–1
Examination by engineer.....	32.25–1
Installation of internal combustion engines	32.35–5
Steering apparatus.....	32.35–10
Maneuvering characteristics, display of	35.20–40
Manning:	
Tank vessels	31.15, 35.35–1
Marine engineering and material specifications.....	Subpart 31.30
Marine inspector, authority of.....	31.01–10
Markings:	
Booms and cranes.....	31.37–45
CO ₂ alarm	35.40–7

Subchapter D Index

Draft marks	32.05-1
Emergency breathing apparatus	35.40-20
Emergency lights	35.40-6
Fire and emergency equipment	Subpart 35.40
Firehose stations	35.40-15
General alarm bell	35.40-5
General alarm bell switch	35.40-1
Lifesaving equipment	35.40-40
Portable fire extinguishers	35.40-25
Steam, foam or CO ₂ apparatus	35.40-10
Steering station	35.40-35
Tanks for liquefied flammable gas, marking of	38.05-5
Vapor control system piping	39.20-1
Vessel's name	32.05-10, 32.05-15
Vessel's name on equipment	32.05-5
Master:	
Casualty or accident report	35.15-1
Licensed officer	35.05-1
Station bills and muster list	35.10-1, 35.10-5
Master's and officer's responsibility	35.20-20
Matches:	
Use of	35.30-5
Materials specification	Subpart 31.30
Material, scantlings and workmanship	32.60-1, 32.65-1
Means of escape	32.02-1
Muster list	35.10-1, 35.10-5

N

Nautical publications	35.20-1
Navigation, use of Auto Pilot	35.20-45
Navigation equipment:	
Anchors for seagoing barges	32.15-15
Magnetic compass and gyro compass	32.15-35
Radar	32.15-30
Sounding machines	32.15-10
Whistles	32.15-5
New tank vessels, inspection of	31.10-5
New tank vessels, plans for inspection of	31.10-5(a)
Notice to mariners	35.20-1

O

Ocean, definition	30.10-45
Officer in Charge, Marine Inspection	30.10-47
Officers required on tank vessels	Subpart 35.05
Open hopper type barges	35.01-45
Overfill protection, liquid, tank barge	39.20-9
Overfill protection, liquid, tank ship	39.20-7
Overpressure and vacuum protection, vapor, tank barge and ship	39.20-11
Oxygen breathing apparatus, marking of	35.40-20

P

Paintrooms	Subparts 32.85, 34.05-05
Penalties for violations of regulations	30.20-10
Period covered by certificate of inspection	31.05-10
Permit definition	30.10-49

46 CFR Ch. I (10-1-98 Edition)

Permit to proceed to another port for repairs.....	31.10-35
Piping:	
Fire extinguishing systems	34.10-10, 34.10-15, 34.10-90, 34.15-15 34.17-15, 34.20-15, 34.25-15
Piping, bilge.....	32.52-5
Piping, cargo.....	Subpart 32.50
Cargo tanks.....	38.10-10
Steering apparatus.....	32.35-10
Placard of lifesaving signals and breeches buoy instructions.....	Subpart 35.12
Application.....	35.12-1
Availability.....	35.12-5
Plans, Display of.....	35.10-3
Plans for inspection of new tank vessels.....	31.10-5(a)
Portable and semiportable extinguishers.....	34.05-10, 34.50
Portable tanks-interpretive rulings.....	30.01-20
Portable electrical equipment.....	35.30-30
Posting of certificate of inspection.....	31.05-5
Pressure-vacuum relief valve.....	30.10-55, 32.20-5
Prevention of oil pollution.....	35.01-40
Proof test of cargo gear as a unit.....	31.37-40
Protection for personnel.....	36.05-10
Pumprooms:	
Electrical installations.....	32.60-20
Fire extinguishing systems for.....	34.05-5
Lighting.....	32.60-20
Location of.....	32.60-20, 32.65-20
Requirements for.....	32.70-15, 32.70-20
Ventilation.....	32.60-20, 36.20-5
Pumps, bilge.....	32.60-20, 36.20-5
Pumps, cargo.....	32.52-1

Q

Quarters, living.....	32.60-25, 32.65-25
-----------------------	--------------------

R

Radar.....	32.15-30
Radio room warning signs.....	35.30-1
Recognized classification society, definition.....	30.10-57
Refrigerated systems.....	38.05-25
Registers regarding shipboard cargo gear.....	31.10-16, Subpart 31-37
Regulations:	
Application of.....	30.01-5
Authority vested in Commandant.....	30.01-1
Effective date.....	30.01-15
Explanation of vessel description.....	30.01-5
Governing alterations and repairs.....	30.01-10
Liquefied flammable gas.....	Part 38
Scope of.....	36.01-1
Vapor control system.....	Part 39
Reid vapor pressure, definition.....	30.10-59
Reinspection.....	31.10-17
Relief valves:	
Cargo pump.....	36.10-1
Cargo pump, testing of.....	35.35-70
Cargo tanks.....	38.10-15
Repairs:	

Subchapter D Index

Application of regulations	30.01-10
Firefighting equipment	35.01-35
Inspection before making	35.01-1
Involving hot work	35.01-1
Permit to proceed to another port	31.10-35
Reports of engineers	35.25-5
Right of appeal	30.20-50
Rivers, definition	30.10-61
Rudder:	
Indicators	35.40-35

S

Safety requirements:	
Means of escape	32.02-1
Safety relief valves for cargo tanks	38.10-15
Safety rules.....	Subpart 35.30
Safety valve seal, breaking of	35.25-20
Sailing directions	35.20-1
Sanitary inspection by master and chief engineer	35.01-5
Scantlings, material and workmanship.....	32.60-1, 32.65-5
Scuppers, closing of.....	35.35-10
Sea chests, examination of.....	31.10-20
Sea strainers, examination of	31.10-20
Sea valves, closing of	35.35-10
Segregation of spaces containing the emergency source of electric power.....	32.60-45
Shipboard cargo gear, certificates or registers	31.10-16, Subpart 31.37
Shipping papers required.....	35.01-10
Sleeping quarters.....	Subpart 32.40
Smoking safety rules.....	35.30-5
Sounding machines	32.15-10
Spark arrester.....	30.10-63
Spark producing devices	35.30-35
Spray nozzles.....	34.10-10
Specifications, material.....	Subpart 31.30
Special operating requirements.....	Subpart 35.01
Special operating requirements for tank barges carrying certain dangerous bulk cargoes.....	35.01-50
Stability requirements.....	31.10-30
Station bills required.....	35.10-1
Steam fire extinguishing systems, marking of	35.40-10
Steam, carrying of excess	35.25-15
Steam smothering system	Subpart 34.13
Steel hull tank vessels	Subparts 32.70, 32.60, 32.63, 32.65
Steering apparatus on tank vessel	32.35-10
Steering gear, instruction for changing	35.40-30
Steering gear test.....	35.20-10
Steering orders, marking	35.40-35
Stowage of package and general cargo.....	35.35-55
Subdivision of cargo spaces.....	32.60-5, 32.65-10

T

Tank barge:	
Carrying bulk cargoes having dangerous characteristics in addition to flammability and combustibility	35.01-50
Definition	30.10-65
Watchman for	35.05-15

46 CFR Ch. I (10–1–98 Edition)

Tankerman, definition	30.10–71
Tankship:	
Definition	30.10–67
Licensed officers and crew	35.05–1
Tanks, portable–interpretive rulings	30.01–20
Tank vessel:	
Definition	30.10–69
Laid up or dismantled	31.01–1
Telegraph equipment, engine order	Subpart 32.30
Telephone equipment, sound powered	Subpart 32.30
Testing of firefighting equipment	31.10–19
Tide tables	35.20–1
Toilet facilities	32.40–25
Towing vessels	31.15–10, 35.35–45
Trial trip inspection	31.10–40

U

Ullage holes, safety rules regarding	35.30–10
--------------------------------------------	----------

V

Valves:	
Back pressure check type	38.10–1, 38.10–5
Excess flow	38.10–1, 38.10–5
Liquefied flammable gas	38.10–1, 38.10–5
Pressure vacuum relief	30.10.55, 32.20.5
Relief	35.35–70, 38.10–1, 38.10–10, 38.10–15
Shutoff	38.10–1
Vapor balancing:	
design of equipment	39.40–3
general requirements	39.40–1
operational requirements	39.40–5
Vapor collection system	39.20–1
Vapor control systems	Part 39
Applicability	39.10–1
Cargo gauging system	39.20–3
Definitions	39.10–3
Design and equipment	Subpart 39.20
General requirements	Subpart 39.10
Lightering and topping–off operations with vapor balancing	Subpart 39.40
Operational requirements	39.30–1
Operations	Subpart 39.30
Personnel training	39.10–11
Submission of vapor control system designs	39.10–13
Tank barge and ship vapor overpressure and vacuum protection	39.20–11
Tank barge liquid overfill protection	39.20–9
Tankship high and low vapor pressure protection	39.20–13
Vessel vapor processing units	39.10–9
Ventilation and venting:	
Cargo tanks	Subpart 32.55
Cargo tanks, independent	Subpart 38.20
Cofferdams	Subpart 32.55
Flame screen	36.20–1
Hold spaces	32.55–15
Pumproom	36.20–5
Tank ships with a keel laying date on or after January 1, 1975	32.55–50
Vessels coming alongside	35.35–42

Subchapter D Index

Vessels converted to tank vessels	31.10-10
Vessel's name on equipment	35.40-40
Vessel's name	32.05-10, 32.05-15
Voice tubes	32.30-1

W

Warning signals and signs.....	35.30-1
Warning signs	35.30-1
Washing facilities.....	32.40-25
Watchman for tank barge.....	35.05-15
Water spray extinguishing systems, details	Subpart 34-25
Application	34.25-1
Capacity and arrangement	34.25-5
Controls.....	34.25-10
Installations contracted for prior to January 1, 1964	34.25-90
Piping.....	34.25-15
Spray nozzles.....	34.25-20
Water spray systems, marking of.....	35.40-18
Waters, travel permitted on.....	Subpart 31.20
Welding repairs.....	35.01-1
Whistles	32.15-5
Whistle signals for drills.....	35.10-5
Whistling, unnecessary	35.20-35
Wire rope	31.37-35, 31.37-50
Work vests:	
Application of.....	35.03-1
Approved unicellular plastic foam.....	35.03-5
Shipboard inspection.....	35.03-20
Shipboard stowage	35.03-15
Use.....	35.03-10
Workmanship, material, and scantlings	32.60-1, 32.65-5