

§ 307.3

9 CFR Ch. III (1-1-00 Edition)

rooms or compartments for these purposes shall be secure and susceptible of being kept clean, including a sanitary disposal of the floor liquids; establishment employees shall not enter any retention rooms or compartments or open any retention receptacles unless authorized by Program employees);

(i) Adequate facilities, including denaturing materials, for the proper disposal of condemned articles in accordance with the regulations in this subchapter (tanks or other rendering equipment which, under the regulations in this subchapter, must be sealed, shall be properly equipped for sealing as specified by the regulations in part 314 of this subchapter or by the circuit supervisor in specific cases);

(j) Docks and receiving rooms, to be designated by the operator of the official establishment, with the circuit supervisor, for the receipt and inspection of all products as provided in §318.3 of this subchapter.

(k) Suitable lockers in which brands bearing the official inspection legend and other official devices (excluding labels) and official certificates shall be kept when not in use (all such lockers shall be equipped for sealing or locking with locks or seals to be supplied by the Department; the keys of such locks shall not leave the custody of Program employees);

(l) Sanitary facilities and accommodations as prescribed by §416.2(c), (d), (e), (f), and (h) of this chapter.

(m) In addition to any facilities required to accomplish sanitary dressing procedures, the following inspection station facilities for cattle and swine slaughter lines described in §310.1(b) of this subchapter are required:

(1) An inspection station consisting of 5 feet of unobstructed line space for each head or carcass inspector and, for viscera table kills, 8 feet for each viscera inspector on the inspector's side of the table.

(2) A minimum of 50 foot candles of shadow-free lighting at the inspection surfaces of the head, viscera, and carcass.

(3) A handwash lavatory (other than one which is hand operated), furnished with soap, towels, and hot and cold water, and located adjacent to the inspector's work area. In addition, for

each head and viscera inspector on cattle slaughter lines, and each head inspector on swine slaughter lines, a sterilizer located adjacent to the inspector's work area.

(4) For mechanized operations, a line control switch located adjacent to each inspection station.

(5) Facilities to position tally sheets or other recording devices, such as digital counters, and facilities to contain condemned brands.

(6) For swine slaughter lines requiring three or more inspectors, and for those one- and two-inspector configurations where the establishment installs a mirror: At the carcass inspection station one glass or plastic, distortion-free mirror, at least 5 feet×5 feet, mounted far enough away from the vertical axis of the moving line to allow the carcass to be turned, but not over 3 feet away, and so mounted that any inspector standing at the carcass inspection station can readily view the back of the carcass.

[35 FR 15560, Oct. 3, 1970, as amended at 47 FR 33676, Aug. 4, 1982; 50 FR 19902, May 13, 1985; 64 FR 56415, Oct. 20, 1999]

EFFECTIVE DATE NOTE: At 64 FR 56415, Oct. 20, 1999, §307.2, paragraph (l) was revised, effective Jan. 25, 2000. For the convenience of the user, the superseded text is set forth as follows:

§ 307.2 Other facilities and conditions to be provided by establishment.

* * * * *

(l) Sanitary facilities and accommodations as prescribed by §308.4 of this subchapter.

* * * * *

§ 307.3 Inspectors to furnish and maintain implements in a sanitary condition.

Inspectors shall furnish their own work clothing and implements, such as flashlights and triers, for conducting inspection and shall maintain their implements in sanitary condition as prescribed by §416.3(a) of this chapter.

[64 FR 56415, Oct. 20, 1999]

EFFECTIVE DATE NOTE: At 64 FR 56415, Oct. 20, 1999 §307.3 was revised, effective Jan. 25, 2000. For the convenience of the user, the superseded text is set forth as follows: