AUTHENTICATED
U.S. GOVERNMENT
INFORMATION
GPO

ceases to function before it exceeds these frequency stability limits.

Subpart E—Broadband PCS

SOURCE: 59 FR 32854, June 24, 1994, unless otherwise noted.

§ 24.200 Scope.

This subpart sets out the regulations governing the licensing and operations of personal communications services authorized in the 1850–1910 and 1930–1990 MHz bands.

§ 24.202 Service areas.

Broadband PCS service areas are Major Trading Areas (MTAs) and Basic Trading Areas (BTAs) as defined in this section. MTAs and BTAs are based on the Rand McNally 1992 Commercial Atlas & Marketing Guide, 123rd Edition, at pages 38–39 (''BTA/MTA Map''). Rand McNally organizes the 50 states and the District of Columbia into 47 MTAs and 487 BTAs. The BTA/MTA Map is available for public inspection at the Office of Engineering and Technology's Technical Information Center, 445 12th Street, SW, Washington, DC 20554.

(a) The MTA service areas are based on the Rand McNally *1992 Commercial Atlas & Marketing Guide*, 123rd Edition, at pages 38–39, with the following exceptions and additions:

(1) Alaska is separated from the Seattle MTA and is licensed separately.

(2) Guam and the Northern Mariana Islands are licensed as a single MTA-like area.

(3) Puerto Rico and the United States Virgin Islands are licensed as a single MTA-like area.

(4) American Samoa is licensed as a single MTA-like area.

(b) The BTA service areas are based on the Rand McNally *1992 Commercial Atlas & Marketing Guide*, 123rd Edition, at pages 38–39, with the following additions licensed separately as BTA-like areas: American Samoa; Guam; Northern Mariana Islands; Mayagüez/Aguadilla-Ponce, Puerto Rico; San Juan, Puerto Rico; and the United States Virgin Islands. The Mayagüez/Aguadilla-Ponce BTA-like service area consists of the following municipios: Adjuntas, Aguada, Aguadilla, Añasco, Arroyo, Cabo Rojo, Coamo, Guánica, Guayama, Guayanilla, Hormigueros, Isabela, Jayuya, Juana Díaz, Lajas, Las Marías, Mayagüez, Maricao, Maunabo, Moca, Patillas, Peñuelas, Ponce, Quebradillas, Rincón, Sabana Grande, Salinas, San Germán, Santa Isabel, Villalba, and Yauco. The San Juan BTA-like service area consists of all other municipios in Puerto Rico.

[59 FR 32854, June 24, 1994; 59 FR 40835, Aug. 10, 1994; 63 FR 68952, Dec. 14, 1998; 65 FR 53636, Sept. 5, 2000]

§ 24.203 Construction requirements.

(a) Licensees of 30 MHz blocks must serve with a signal level sufficient to provide adequate service to at least one-third of the population in their licensed area within five years of being licensed and two-thirds of the population in their licensed area within 10 years of being licensed. Licensees may choose to define population using the 1990 census or the 2000 census. Failure by any licensee to meet these requirements will result in forfeiture or nonrenewal of the license and the licensee will be ineligible to regain it.

(b) Licensees of 10 MHz blocks, including 10 MHz C block licenses reconfigured pursuant to Amendment of the Commission's Rules Regarding Installment Payment Financing for Personal Communications Services (PCS) Licensees, WT Docket No. 97–82, *Sixth Report and Order*, FCC 00–313, and 15 MHz blocks resulting from the disaggregation option as provided in the Commission's Rules Regarding Installment payment Financing for Personal Communications Services (PCS) Licensees, Second Report and Order and Further Notice of Proposed Rule Making, WT Docket 97–82, 12 FCC Rcd 16436 (1997), as modified by Order on Reconsideration of the Second Report and Order, WT Docket 97–82, 13 FCC Rcd 8345 (1998), must serve with a signal level sufficient to provide adequate service to at least one-quarter of the population in their licensed area within five years of being licensed, or make a showing of substantial service in their licensed area within five years of being licensed. Population is defined as the 1990 population census. Licensees may elect to use the 2000 population

census to determine the five-year construction requirement. Failure by any licensee to meet these requirements will result in forfeiture of the license and the licensee will be ineligible to regain it.

(c) Licensees must file maps and other supporting documents showing compliance with the respective construction requirements within the appropriate five- and ten-year benchmarks of the date of their initial licenses.

[58 FR 59183, Nov. 8, 1993, as amended at 64 FR 26890, May 18, 1999; 65 FR 53636, Sept. 5, 2000]

§ 24.229 Frequencies.

The frequencies available in the Broadband PCS service are listed in this section in accordance with the frequency allocations table of § 2.106 of this chapter.

(a) The following frequency blocks are available for assignment on an MTA basis:

Block A: 1850–1865 MHz paired with 1930–1945 MHz; and

Block B: 1870–1885 MHz paired with 1950–1965 MHz.

(b) The following frequency blocks are available for assignment on a BTA basis:

Block C: 1895–1910 MHz paired with 1975–1990 MHz;

Pursuant to Amendment of the Commission's Rules Regarding Installment Payment Financing for Personal Communications Services (PCS) Licensees, WT Docket No. 97–82, *Sixth Report and Order*, FCC 00–313, all 30 MHz Block C licenses available for auction in Auction No. 35 or any subsequent auction will be reconfigured into three 10 MHz C block licenses as follows: 1895–1900 MHz paired with 1975–1980 MHz, 1900–1905 MHz paired with 1980–1985 MHz, 1905–1910 MHz paired with 1985–1990 MHz;

Block D: 1865–1870 MHz paired with 1945–1950 MHz;

Block E: 1885–1890 MHz paired with 1965–1970 MHz;

Block F: 1890–1895 MHz paired with 1970–1975 MHz;

[59 FR 32854, June 24, 1994, as amended at 60 FR 13917, Mar. 15, 1995; 60 FR 26375, May 17, 1995; 61 FR 33868, July 1, 1996; 62 FR 660, Jan. 6, 1997; 65 FR 53637, Sept. 5, 2000]

§ 24.232 Power and antenna height limits.

(a) Base stations are limited to 1640 watts peak equivalent isotropically radiated power (e.i.r.p.) with an antenna height up to 300 meters HAAT. See § 24.53 for HAAT calculation method. Base station antenna heights may exceed 300 meters with a corresponding reduction in power; see Table 1 of this section. In no case may the peak output power of a base station transmitter exceed 100 watts. The service area boundary limit and microwave protection criteria specified in § 24.236 and § 24.237 apply.

TABLE 1.—REDUCED POWER FOR BASE STATION ANTENNA HEIGHTS OVER 300 METERS

HAAT in meters	Maximum e.i.r.p. (watts)
≤300	1,640
≤500	1,070
≤1,000	490
≤1,500	270
≤2,000	160

(b) Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

(c) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, *etc.*, so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.