

§ 56.66

7 CFR Ch. I (1-1-02 Edition)

samples plus an equal number of samples.

(b) When the original samples are not available, the appeal sample size for the lot shall consist of double the samples required in § 56.4(b).

(c) Shell eggs shall not have been moved from the original place of grading and must have been maintained under adequate refrigeration and humidity conditions.

[35 FR 9918, June 17, 1970. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981, as amended at 47 FR 46070, Oct. 15, 1982; 47 FR 54421, Dec. 3, 1982]

§ 56.66 Appeal grading certificates.

Immediately after an appeal grading is completed, an appeal certificate shall be issued to show that the original grading was sustained or was not sustained. Such certificate shall supersede any previously issued certificate for the product involved and shall clearly identify the number and date of the superseded certificate. The issuance of the appeal certificate may be withheld until any previously issued certificate and all copies have been returned when such action is deemed necessary to protect the interest of the Government. When the appeal grader assigns a different grade to the lot, the existing grade mark shall be changed or obliterated as necessary. When the appeal grader assigns a different class or quantity designation to the lot, the labeling shall be corrected.

FACILITY REQUIREMENTS

§ 56.75 Applicability of facility and operating requirements.

The provisions of § 56.76 shall be applicable to any grading service that is provided on a resident basis.

[28 FR 6345, June 20, 1963. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981]

§ 56.76 Minimum facility and operating requirements for shell egg grading and packing plants.

(a) *General requirements for buildings and plant facilities.* (1) Buildings shall be of sound construction so as to prevent, insofar as practicable, the entrance or harboring of vermin.

(2) Grading and packing rooms shall be of sufficient size to permit installation of necessary equipment and the conduct of grading and packing in a sanitary manner. These rooms shall be kept reasonably clean during grading and packing operations and shall be thoroughly cleaned at the end of each operating day.

(3) Adequate lavatory and toilet accommodations shall be provided. Toilet and locker rooms shall be maintained in a clean and sanitary condition. Hot and cold running water shall be provided. Rooms shall be ventilated to the outside of the building. Signs shall be posted in the rest rooms instructing employees to wash their hands before returning to work.

(4) A separate refuse room or a designated area for the accumulation of trash must be provided in plants which do not have a system for the daily removal or destruction of such trash.

(5) Wood benches, platforms, etc., in areas which are subjected to moisture and which develop odors shall be replaced with equipment of metal construction. Wood walls or partitions which develop odors shall be replaced with materials impervious to moisture. Newly constructed plants should be equipped with metal benches, platforms, etc., in areas which are subjected to moisture.

(b) *Grading room requirements.* (1) The egg grading or candling area shall be adequately darkened to make possible the accurate quality determination of the candled appearance of eggs. There shall be no other light source or reflections of light that interfere with, or prohibit the accurate quality determination of eggs in the grading or candling area.

(2) The grading and candling equipment shall provide adequate light to facilitate quality determinations. Other light sources and equipment or facilities shall be provided to permit the detection and removal of stained and dirty eggs or other undergrade eggs.

(3) Adequate facilities, equipment, and light sources shall be provided to determine the condition of packing material.

(4) Egg weighing equipment shall be provided. The egg weighing equipment