

for the product involved and shall clearly identify the number and date of the superseded certificate. The issuance of the appeal certificate may be withheld until any previously issued certificate and all copies have been returned when such action is deemed necessary to protect the interest of the Government. When the appeal grader assigns a different grade to the lot, the existing grade mark shall be changed or obliterated as necessary. When the appeal grader assigns a different class or quantity designation to the lot, the labeling shall be corrected.

FACILITY REQUIREMENTS

§ 56.75 Applicability of facility and operating requirements.

The provisions of § 56.76 shall be applicable to any grading service that is provided on a resident or temporary basis.

[69 FR 76376, Dec. 21, 2004]

§ 56.76 Minimum facility and operating requirements for shell egg grading and packing plants.

(a) Applicants must comply with all applicable Federal, State and local government occupational safety and health regulations.

(b) *General requirements for premises, buildings and plant facilities.* (1) The outside premises shall be free from refuse, rubbish, waste, unused equipment, and other materials and conditions which constitute a source of odors or a harbor for insects, rodents, and other vermin.

(2) The outside premises adjacent to grading, packing, cooler, and storage rooms must be properly graded and well drained to prevent conditions that may constitute a source of odors or propagate insects or rodents.

(3) Buildings shall be of sound construction so as to prevent, insofar as practicable, the entrance or harboring of vermin.

(4) Grading and packing rooms shall be of sufficient size to permit installation of necessary equipment and conduct grading and packing in a sanitary manner. These rooms shall be kept reasonably clean during grading and packing operations and shall be thoroughly

cleaned at the end of each operating day.

(5) The floors, walls, ceilings, partitions, and other parts of the grading and packing rooms including benches and platforms shall be constructed of materials that are readily cleanable, maintained in a sanitary condition, and impervious to moisture in areas exposed to cleaning solutions or moist conditions. The floors shall be constructed as to provide proper drainage.

(6) Adequate toilet accommodations which are conveniently located and separated from the grading and packing rooms are to be provided. Handwashing facilities shall be provided with hot and cold running water, an acceptable handwashing detergent, and a sanitary method for drying hands. Toilet rooms shall be ventilated to the outside of the building and be maintained in a clean and sanitary condition. Signs shall be posted in the toilet rooms instructing employees to wash their hands before returning to work. In new or remodeled construction, toilet rooms shall be located in areas that do not open directly into processing rooms.

(7) A separate refuse room or a designated area for the accumulation of trash must be provided in plants which do not have a system for the daily removal or destruction of such trash.

(8) Adequate packing and packaging storage areas are to be provided that protect packaging materials and are dry and maintained in a clean and sanitary condition.

(c) *Grading and packing room requirements.* (1) The egg grading or candling area shall be adequately darkened to make possible the accurate quality determination of the candled appearance of eggs. There shall be no other light source or reflection of light that interfere with, or prohibit the accurate quality determination of eggs in the grading or candling areas.

(2) The grading and candling equipment shall provide adequate light to facilitate quality determinations. When needed, other light sources and equipment or facilities shall be provided to permit the detection and removal of stained and dirty eggs or other undergrade eggs.