

as provided in §1915.51(c)(3), or when an employee is working alone in an isolated location, frequent checks shall be made to ensure the safety of the employees.

§ 1915.95 Ship repairing and shipbuilding work on or in the vicinity of radar and radio.

The provisions of this section shall apply to ship repairing and shipbuilding.

(a) No employees other than radar or radio repairmen shall be permitted to work on masts, king posts or other aloft areas unless the radar and radio are secured or otherwise made incapable of radiation. In either event, the radio and radar shall be appropriately tagged.

(b) Testing of radar or radio shall not be done until the employer can schedule such tests at a time when no work is in progress aloft or personnel can be cleared from the danger area according to minimum safe distances established for and based on the type, model, and power of the equipment.

[47 FR 16986, Apr. 20, 1982, as amended at 49 FR 18295, Apr. 30, 1984; 54 FR 24334, June 7, 1989]

§ 1915.96 Work in or on lifeboats.

The provisions of this section shall apply to ship repairing, shipbuilding, and shipbreaking except that paragraph (b) of this section applies to ship repairing and shipbuilding only.

(a) Before employees are permitted to work in or on a lifeboat, either stowed or in a suspended position, the employer shall ensure that the boat is secured independently of the releasing gear to prevent the boat from falling due to accidental tripping of the releasing gear and movement of the davits or capsizing of a boat in chocks.

(b) Employees shall not be permitted to remain in boats while the boats are being hoisted into final stowed position.

(c) Employees shall not be permitted to work on the outboard side of lifeboats stowed on their chocks unless the boats are secured by gripes or otherwise secured to prevent them from swinging outboard.

§ 1915.97 Health and sanitation.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking, except where indicated otherwise.

(a) The employer shall provide all necessary controls, and the employees shall be protected by suitable personal protective equipment against the hazards identified in §1915.1200 of this part and those hazards for which specific precautions are required in subparts B, C, and D of this part.

(b) The employer shall provide adequate washing facilities for employees engaged in the application of paints or coatings or in other operations where contaminants can, by ingestion or absorption, be detrimental to the health of the employees. The employer shall encourage good personal hygiene practices by informing the employees of the need for removing surface contaminants by thorough washing of hands and face prior to eating or smoking.

(c) The employer shall not permit employees to eat or smoke in areas undergoing surface preparation or preservation or where shipbreaking operations produce atmospheric contaminants.

(d) The employer shall not permit employees engaged in ship repair work on a vessel to work in the immediate vicinity of uncovered garbage and shall ensure that employees working beneath or on the outboard side of a vessel are not subject to contamination by drainage or waste from overboard discharges.

(e) No minor under 18 years of age shall be employed in shipbreaking or related employments.

[52 FR 31886, Aug. 24, 1987, as amended at 67 FR 44543, July 3, 2002]

§ 1915.98 First aid.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking.

(a) Unless a first aid room and a qualified attendant are close at hand and prepared to render first aid to employees on behalf of the employer, the employer shall furnish a first aid kit for each vessel on which work is being performed, except that when work is being performed on more than one

§ 1915.100

29 CFR Ch. XVII (7-1-10 Edition)

small vessel at one pier, only one kit shall be required. The kit, when required, shall be kept close to the vessel and at least one employee, close at hand, shall be qualified to administer first aid to the injured.

(b) The first aid kit shall consist of a weatherproof container with individual sealed packages for each type of item. The contents of such kit shall contain a sufficient quantity of at least the following types of items:

- Gauze roller bandages, 1 inch and 2 inch.
- Gauze compress bandages, 4 inch.
- Adhesive bandages, 1 inch.
- Triangular bandage, 40 inch.
- Ammonia inhalants and ampules.
- Antiseptic applicators or swabs.
- Burn dressing.
- Eye dressing.
- Wire or thin board splints.
- Forceps and tourniquet.

(c) The contents of the first aid kit shall be checked before being sent out on each job and at least weekly on each job to ensure that the expended items are replaced.

(d) There shall be available for each vessel on which ten (10) or more employees are working one Stokes basket stretcher, or equivalent, permanently equipped with bridles for attaching to the hoisting gear, except that no more than two stretchers are required on each job location. A blanket or other liner suitable for transferring the patient to and from the stretcher shall be provided. Stretchers shall be kept close to the vessels. This paragraph does not apply where ambulance services which are available are known to carry such stretchers.

§ 1915.100 Retention of DOT markings, placards and labels.

(a) Any employer who receives a package of hazardous material which is required to be marked, labeled or placarded in accordance with the U. S. Department of Transportation's Hazardous Materials Regulations (49 CFR parts 171 through 180) shall retain those markings, labels and placards on the package until the packaging is sufficiently cleaned of residue and purged of vapors to remove any potential hazards.

(b) Any employer who receives a freight container, rail freight car,

motor vehicle, or transport vehicle that is required to be marked or placarded in accordance with the Hazardous Materials Regulations shall retain those markings and placards on the freight container, rail freight car, motor vehicle or transport vehicle until the hazardous materials which require the marking or placarding are sufficiently removed to prevent any potential hazards.

(c) Markings, placards and labels shall be maintained in a manner that ensures that they are readily visible.

(d) For non-bulk packages which will not be reshipped, the provisions of this section are met if a label or other acceptable marking is affixed in accordance with the Hazard Communication Standard (29 CFR 1910.1200).

(e) For the purposes of this section, the term "hazardous material" and any other terms not defined in this section have the same definition as in the Hazardous Materials Regulations (49 CFR parts 171 through 180).

[59 FR 36700, July 19, 1994]

Subpart G—Gear and Equipment for Rigging and Materials Handling

§ 1915.111 Inspection.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking.

(a) All gear and equipment provided by the employer for rigging and materials handling shall be inspected before each shift and when necessary, at intervals during its use to ensure that it is safe. Defective gear shall be removed and repaired or replaced before further use.

(b) The safe working load of gear as specified in §§ 1915.112 and 1915.113 shall not be exceeded.

§ 1915.112 Ropes, chains and slings.

The provisions of this section shall apply to ship repairing, shipbuilding and shipbreaking.

(a) *Manila rope and manila rope slings.*
(1) Table G-1 in § 1915.118 shall be used to determine the safe working load of various sizes of manila rope and manila rope slings at various angles, except