

§ 63.1342

Rolling average means the average of all one-minute averages over the averaging period.

Run average means the average of the one-minute parameter values for a run.

TEQ means the international method of expressing toxicity equivalents for dioxins and furans as defined in U.S. EPA, Interim Procedures for Estimating Risks Associated with Exposures to Mixtures of Chlorinated Dibenzo-p-dioxins and -dibenzofurans (CDDs and CDFs) and 1989 Update, March 1989.

[64 FR 31925, June 14, 1999, as amended at 67 FR 16619, Apr. 5, 2002]

EMISSION STANDARDS AND OPERATING LIMITS

§ 63.1342 Standards: General.

Table 1 to this subpart provides cross references to the 40 CFR part 63, subpart A, general provisions, indicating the applicability of the general provisions requirements to subpart LLL.

[71 FR 76549, Dec. 20, 2006]

§ 63.1343 Standards for kilns and in-line kiln/raw mills.

(a) *General.* The provisions in this section apply to each kiln, each in-line kiln/raw mill, and any alkali bypass associated with that kiln or in-line kiln/raw mill. All gaseous, mercury and D/F emission limits are on a dry basis, corrected to 7 percent oxygen. All total hydrocarbon (THC) emission limits are measured as propane. The block averaging periods to demonstrate compliance are hourly for 20 ppmv total hydrocarbon (THC) limits and monthly for the 50 ppmv THC limit.

(b) *Existing kilns located at major sources.* No owner or operator of an existing kiln or an existing kiln/raw mill located at a facility that is a major source subject to the provisions of this subpart shall cause to be discharged into the atmosphere from these affected sources, any gases which:

(1) Contain particulate matter (PM) in excess of 0.15 kg per Mg (0.30 lb per ton) of feed (dry basis) to the kiln. When there is an alkali bypass associated with a kiln or in-line kiln/raw mill, the combined particulate matter emissions from the kiln or in-line kiln/

40 CFR Ch. I (7-1-09 Edition)

raw mill and the alkali bypass are subject to this emission limit.

(2) Exhibit opacity greater than 20 percent.

(3) Contain D/F in excess of:

(i) 0.20 ng per dscm (8.7×10^{-11} gr per dscf) (TEQ); or
(ii) 0.40 ng per dscm (1.7×10^{-10} gr per dscf) (TEQ) when the average of the performance test run average temperatures at the inlet to the particulate matter control device is 204 °C (400 °F) or less.

(c) *Reconstructed or new kilns located at major sources.* No owner or operator of a reconstructed or new kiln or reconstructed or new inline kiln/raw mill located at a facility which is a major source subject to the provisions of this subpart shall cause to be discharged into the atmosphere from these affected sources any gases which:

(1) Contain particulate matter in excess of 0.15 kg per Mg (0.30 lb per ton) of feed (dry basis) to the kiln. When there is an alkali bypass associated with a kiln or in-line kiln/raw mill, the combined particulate matter emissions from the kiln or in-line kiln/raw mill and the bypass stack are subject to this emission limit.

(2) Exhibit opacity greater than 20 percent.

(3) Contain D/F in excess of:

(i) 0.20 ng per dscm (8.7×10^{-11} gr per dscf) (TEQ); or
(ii) 0.40 ng per dscm (1.7×10^{-10} gr per dscf) (TEQ) when the average of the performance test run average temperatures at the inlet to the particulate matter control device is 204 °C (400 °F) or less.

(4) Contain total hydrocarbons (THC), from the main exhaust of the kiln, or main exhaust of the in-line kiln/raw mill, in excess of 20 ppmv if the source is a new or reconstructed source that commenced construction after December 2, 2005. As an alternative to meeting the 20 ppmv standard you may demonstrate a 98 percent reduction of THC emissions from the exit of the kiln to discharge to the atmosphere. If the source is a greenfield kiln that commenced construction on or prior to December 2, 2005, then the THC limit is 50 ppmv.

(5) Contain mercury from the main exhaust of the kiln, or main exhaust of