

of this section and established during the performance test, with or without the raw mill operating, is not exceeded.

(b) The temperature limit for affected sources meeting the limits of paragraph (a) of this section or paragraphs (a)(1) through (a)(3) of this section is determined in accordance with § 63.1349(b)(3)(iv).

(c) The owner or operator of an affected source subject to a mercury, THC or D/F emission limitation under § 63.1343 that employs carbon injection as an emission control technique must operate the carbon injection system in accordance with paragraphs (c)(1) and (c)(2) of this section.

(1) The three-hour rolling average activated carbon injection rate shall be equal to or greater than the activated carbon injection rate determined in accordance with § 63.1349(b)(3)(vi).

(2) The owner or operator shall either:

(i) Maintain the minimum activated carbon injection carrier gas flow rate, as a three-hour rolling average, based on the manufacturer's specifications. These specifications must be documented in the test plan developed in accordance with § 63.7(c), or

(ii) Maintain the minimum activated carbon injection carrier gas pressure drop, as a three-hour rolling average, based on the manufacturer's specifications. These specifications must be documented in the test plan developed in accordance with § 63.7(c).

(d) Except as provided in paragraph (e) of this section, the owner or operator of an affected source subject to a mercury, THC or D/F emission limitation under § 63.1343 that employs carbon injection as an emission control technique must specify and use the brand and type of activated carbon used during the performance test until a subsequent performance test is conducted, unless the site-specific performance test plan contains documentation of key parameters that affect adsorption and the owner or operator establishes limits based on those parameters, and the limits on these parameters are maintained.

(e) The owner or operator of an affected source subject to a D/F, THC, or mercury emission limitation under § 63.1343 that employs carbon injection

as an emission control technique may substitute, at any time, a different brand or type of activated carbon provided that the replacement has equivalent or improved properties compared to the activated carbon specified in the site-specific performance test plan and used in the performance test. The owner or operator must maintain documentation that the substitute activated carbon will provide the same or better level of control as the original activated carbon.

(f) Existing kilns and in-line kilns/raw mills must implement good combustion practices (GCP) designed to minimize THC from fuel combustion. GCP include training all operators and supervisors to operate and maintain the kiln and calciner, and the pollution control systems in accordance with good engineering practices. The training shall include methods for minimizing excess emissions.

(g) No kiln and in-line kiln/raw mill may use as a raw material or fuel any fly ash where the mercury content of the fly ash has been increased through the use of activated carbon, or any other sorbent unless the facility can demonstrate that the use of that fly ash will not result in an increase in mercury emissions over baseline emissions (i.e. emissions not using the fly ash). The facility has the burden of proving there has been no emissions increase over baseline.

(h) All kilns and in-line kilns/raw mills must remove (i.e. not recycle to the kiln) from the kiln system sufficient cement kiln dust to maintain the desired product quality.

(i) New and reconstructed kilns and in-line kilns/raw mills must not exceed the average hourly CKD recycle rate measured during mercury performance testing. Any exceedance of this average hourly rate is considered a violation of the standard.

[64 FR 31925, June 14, 1999, as amended at 67 FR 72585, Dec. 6, 2002; 71 FR 76550, Dec. 20, 2006]

§ 63.1345 Standards for clinker coolers.

(a) No owner or operator of a new or existing clinker cooler at a facility which is a major source subject to the provisions of this subpart shall cause to be discharged into the atmosphere

Environmental Protection Agency

§ 63.1349

from the clinker cooler any gases which:

(1) Contain particulate matter in excess of 0.050 kg per Mg (0.10 lb per ton) of feed (dry basis) to the kiln.

(2) Exhibit opacity greater than ten percent.

(b) [Reserved]

§ 63.1346 Standards for new or reconstructed raw material dryers.

(a) New or reconstructed raw material dryers located at facilities that are major sources can not discharge to the atmosphere any gases which:

(1) Exhibit opacity greater than ten percent, or

(2) Contain THC in excess of 20 ppmv, on a dry basis as propane corrected to 7 percent oxygen if the source commenced construction after December 2, 2005. As an alternative to the 20 ppmv standard, you may demonstrate a 98 percent reduction in THC emissions from the exit of the raw materials dryer to discharge to the atmosphere. If the source is a greenfield dryer constructed on or prior to December 2, 2005, then the THC limit is 50 ppmv, on a dry basis corrected to 7 percent oxygen.

(b) New or reconstructed raw materials dryers located at a facility that is an area source cannot discharge to the atmosphere any gases which contain THC in excess of 20 ppmv, on a dry basis as propane corrected to 7 percent oxygen if the source commenced construction after December 2, 2005. As an alternative to the 20 ppmv standard, you may demonstrate a 98 percent reduction in THC emissions from the exit of the raw materials dryer to discharge to the atmosphere. If the source is a greenfield dryer constructed on or prior to December 2, 2005, then the THC limit is 50 ppmv, on a dry basis corrected to 7 percent oxygen.

[71 FR 76551, Dec. 20, 2006]

§ 63.1347 Standards for raw and finish mills.

The owner or operator of each new or existing raw mill or finish mill at a facility which is a major source subject to the provisions of this subpart shall not cause to be discharged from the mill sweep or air separator air pollution control devices of these affected

sources any gases which exhibit opacity in excess of ten percent.

§ 63.1348 Standards for affected sources other than kilns; in-line kiln/raw mills; clinker coolers; new and reconstructed raw material dryers; and raw and finish mills.

The owner or operator of each new or existing raw material, clinker, or finished product storage bin; conveying system transfer point; bagging system; and bulk loading or unloading system; and each existing raw material dryer, at a facility which is a major source subject to the provisions of this subpart shall not cause to be discharged any gases from these affected sources which exhibit opacity in excess of ten percent.

MONITORING AND COMPLIANCE PROVISIONS

§ 63.1349 Performance testing requirements.

(a) The owner or operator of an affected source subject to this subpart shall demonstrate initial compliance with the emission limits of § 63.1343 and §§ 63.1345 through 63.1348 using the test methods and procedures in paragraph (b) of this section and § 63.7. Performance test results shall be documented in complete test reports that contain the information required by paragraphs (a)(1) through (a)(10) of this section, as well as all other relevant information. The plan to be followed during testing shall be made available to the Administrator prior to testing, if requested.

(1) A brief description of the process and the air pollution control system;

(2) Sampling location description(s);

(3) A description of sampling and analytical procedures and any modifications to standard procedures;

(4) Test results;

(5) Quality assurance procedures and results;

(6) Records of operating conditions during the test, preparation of standards, and calibration procedures;

(7) Raw data sheets for field sampling and field and laboratory analyses;

(8) Documentation of calculations;

(9) All data recorded and used to establish parameters for compliance monitoring; and