(16) Air Cleaner Filter Element. (i) The emission-critical parameters for Air Cleaner Filter Elements are: (A) Pressure drop.

(B) Efficiency.

(ii) For the purpose of this paragraph:

(A) "Air Cleaner Filter Element" means a device to remove particulates from the primary air that enters the air induction system of the engine.

(B) "Pressure Drop" means a measure, in kilopascals, of the difference in static pressure measured immediately upstream and downstream of the air filter element.

(C) "Efficiency" means the ability of the air cleaner or the unit under test to remove contaminant.

(17) Electronic Inductive Ignition System and Components. [Reserved]

(18) Electronic Inductive Distributors. [Reserved]

(b) Additional part standards. [Reserved]

[45 FR 78462, Nov. 25, 1980, as amended at 54 FR 32593, Aug. 8, 1989]

§85.2123 Treatment of confidential information.

(a) Any manufacturer may assert that some or all of the information submitted pursuant to this subpart is entitled to confidential treatment as provided by 40 CFR part 2, subpart B.

(b) Any claim of confidentiality must accompany the information at the time it is submitted to EPA.

(c) To assert that information submitted pursuant to this subpart is confidential, a manufacturer must indicate clearly the items of information claimed confidential by marking, circling, bracketing, stamping, or otherwise specifying the confidential information. Furthermore, EPA requests, but does not require, that the submitter also provide a second copy of its submittal from which all confidential information shall be deleted. If a need arises to publicly release nonconfidential information, EPA will assume that the submitter has accurately deleted all confidential information from this second copy.

(d) If a claim is made that some or all of the information submitted pursuant to this subpart is entitled to confidential treatment, the information cov40 CFR Ch. I (7-1-10 Edition)

ered by that confidentiality claim will be disclosed by the Administrator only to the extent and by means of the procedures set forth in part 2, subpart B, of this chapter.

(e) Information provided without a claim of confidentiality at the time of submission may be made available to the public by EPA without further notice to the submitter, in accordance with 40 CFR 2.204(c)(2)(i)(A).

[50 FR 34798, Aug. 27, 1985]

APPENDIX I TO SUBPART V OF PART 85-RECOMMENDED TEST PROCEDURES AND TEST CRITERIA AND REC-OMMENDED DURABILITY PROCEDURES TO DEMONSTRATE COMPLIANCE WITH EMISSION CRITICAL PARAMETERS

A. CARBURETOR VACUUM BREAK (CHOKE PULL-OFF)

1. Test Procedure and Criteria

a. Vacuum leakage: Apply 457 ± 13 mm (18.0 ±0.5 inches) Hg. vacuum to the vacuum unit to achieve full diaphragm displacement. Seal vacuum source to unit. There shall be no visible loss of diaphragm displacement or drop in vacuum gauge reading after a 15 second observation. Vacuum purge system and diaphragm displacement adjusting screw holes should be temporarily sealed during this test when applicable.

b. Diaphragm displacement: At stabilized temperature of -29 °C and 121 °C (-20 °F and 250 °F) with 457 ± 13 mm (18.0 ± 0.5 inches) Hg. vacuum applied to unit, the diaphragm displacement shall be within ± 1 mm (0.04 inches) of the nominal original equipment displacement. The vacuum purge system must be open during this test when applicable. Adjusting screws that limit displacement should be temporarily removed and adjusting screw holes temporarily sealed during this test.

c. Timed delay (when applicable): With 457 ± 13 mm (18.0 ± 0.5 inches) Hg. applied to the unit, the vacuum break diaphragm displacement shall occur within $\pm 20\%$ of the original equipment time over the specified range of displacement. The diaphragm displacement shall be timed over the same distance for the original equipment as the replacement part and shall not be less than 60% of the total displacement range. The vacuum purge system must be open and the adjusting screw holes should be temporarily sealed during this test when applicable.

d. Modulated stem displacement (when applicable): With a force sufficient to extend the modulated stem to its full displacement. the displacement shall be within ± 0.8 mm $(\pm 0.03 \text{ inches})$ of the original equipment specification.