

**§ 408.93**

**§ 408.93 [Reserved]**

**§ 408.94 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
pH .....	No limitation.
Oil and grease .....	Do.
TSS .....	Do.

[40 FR 6438, Feb. 11, 1975, as amended at 60 FR 33942, June 29, 1995]

**§ 408.95 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kkg of seafood)	
TSS .....	270	180
Oil and grease .....	45	15
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (lb/1,000 lb of seafood)	
TSS .....	270	180
Oil and grease .....	45	15
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

**§ 408.96 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned

treatment works must comply with 40 CFR part 403.

[60 FR 33942, June 29, 1995]

**§ 408.97 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 408.92 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

**Subpart J—Remote Alaskan Shrimp Processing Subcategory**

**§ 408.100 Applicability; description of the remote Alaskan shrimp processing subcategory.**

The provisions of this subpart are applicable to discharges resulting from the processing of shrimp in remote Alaska. The effluent limitations contained in this subpart J are applicable to facilities not covered under subpart I of this part.

[40 FR 55781, Dec. 1, 1975]

**§ 408.101 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

(b) The term *oil and grease* shall mean those components of a waste water amenable to measurement by the method described in Methods for Chemical Analysis of Water and Wastes, 1971, Environmental Protection Agency, Analytical Quality Control Laboratory, page 217.

(c) The term *seafood* shall mean the raw material, including freshwater and

**Environmental Protection Agency**

**§ 408.111**

saltwater fish and shellfish, to be processed, in the form in which it is received at the processing plant.

ceed 1.27 cm (0.5 inch) in any dimension.

[40 FR 55781, Dec. 1, 1975]

**§ 408.102 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

**§ 408.106 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33942, June 29, 1995]

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): No pollutants may be discharged which exceed 1.27 cm (0.5 inch) in any dimension.

**§ 408.107 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in §401.16) in §408.102 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24997, July 9, 1986]

[60 FR 33942, June 29, 1995]

**§ 408.103 [Reserved]**

**§ 408.104 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
pH .....	No limitation.
Oil and grease .....	Do.
TSS .....	Do.

[40 FR 6439, Feb. 11, 1975, as amended at 60 FR 33942, June 29, 1995]

**§ 408.105 Standards of performance for new sources.**

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart: No pollutants may be discharged which ex-

**Subpart K—Northern Shrimp Processing in the Contiguous States Subcategory**

**§ 408.110 Applicability; description of the Northern shrimp processing in the contiguous States subcategory.**

The provisions of this subpart are applicable to discharges resulting from the processing of shrimp in the Northern contiguous States, including Washington, Oregon, California, Maine, New Hampshire, and Massachusetts. The effluent limitations contained in this subpart K are applicable to existing facilities processing more than 908 kg (2000 lbs) of raw material per day on any day during a calendar year and all new sources.

[40 FR 55781, Dec. 1, 1975]

**§ 408.111 Specialized definitions.**

For the purpose of this subpart: