

**§ 408.272**

(b) The term *product* shall mean the weight of the oyster meat after shucking.

**§ 408.272 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kkg of product)	
TSS .....	270	190
Oil and grease .....	2.3	1.7
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (lb/1,000 lb of product)	
TSS .....	270	190
Oil and grease .....	2.3	1.7
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55794, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

**§ 408.273 [Reserved]**

**§ 408.274 Pretreatment standards for existing sources.**

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a point source subject to the provisions of this subpart.

Pollutant or pollutant property	Pretreatment standard
BOD5 .....	No limitation.
TSS .....	Do.
pH .....	Do.
Oil and grease .....	Do.

**40 CFR Ch. I (7-1-09 Edition)**

[40 FR 55794, Dec. 1, 1975, as amended at 60 FR 33947, June 29, 1995]

**§ 408.275 Standards of performance for new sources.**

Except for those steamed and canned oyster processing facilities which utilize air flotation treatment systems to meet the shrimp processing standards of performance for new sources under §§ 408.115, 408.125, or 408.135 and for which standards of performance should be derived on a case-by-case basis, the following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new source subject to the provisions of this subpart:

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kkg of product)	
BOD5 .....	67	17
TSS .....	56	39
Oil and grease .....	0.84	0.42
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (lb/1,000 lb of product)	
BOD5 .....	67	17
TSS .....	56	39
Oil and grease .....	0.64	0.42
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

[40 FR 55794, Dec. 1, 1975, as amended at 42 FR 6813, Feb. 4, 1977]

**§ 408.276 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403. In addition, the following pretreatment standard establishes the quantity or quality of pollutants or pollutant properties controlled by this section which may be discharged to a publicly owned treatment works by a new source subject to the provisions of this subpart:

Pollutant or pollutant property	Pretreatment standard
BOD5 .....	No limitation.
TSS .....	Do.
pH .....	Do.