

**Environmental Protection Agency**

**§415.281**

**§415.242 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).**

(a) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart and reacting anhydrous ammonia with hydrogen chloride gas must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process wastewater pollutants to navigable waters.

(b) Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart and using the recovery process from Solvay process wastes must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

**SUBPART X—AMMONIUM CHLORIDE SOLVAY PROCESS**

Pollutant or pollutant property	BPT limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
Ammonia (as N) .....	8.8	4.4
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

**Subpart Y—Ammonium Hydroxide Production Subcategory [Reserved]**

**Subpart Z—Barium Carbonate Production Subcategory [Reserved]**

**Subpart AA—Borax Production Subcategory**

**§415.270 Applicability; description of the borax production subcategory.**

The provisions of this subpart are applicable to discharges resulting from

the production of borax by the ore-mining process and by the Trona process.

**§415.271 Specialized definitions. [Reserved]**

**§415.272 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process wastewater pollutants to navigable waters, except that residual brine and depleted liquor may be returned to the body of water from which the process brine solution was originally withdrawn.

**§§415.273–415.275 [Reserved]**

**§415.276 Pretreatment standards for new sources (PSNS).**

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): The limitations are the same as specified in §415.272.

[49 FR 33421, Aug. 22, 1984]

**Subpart AB—Boric Acid Production Subcategory**

**§415.280 Applicability; description of the boric acid production subcategory.**

The provisions of this subpart are applicable to discharges resulting from the production of boric acid from ore-mined borax and from borax produced by the Trona process.

**§415.281 Specialized definitions.**

(a) Except as provided below, the general definitions, abbreviations and