

## SUBPART L

Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (pounds per 1,000 lb) of product	
TSS .....	0.175	0.0751
O&G .....	0.0751	0.0250
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

(2) [Reserved]

(b) *Galvanizing and other coatings*—(1) *Wire products and fasteners.*

## SUBPART L

Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (pounds per 1,000 lb) of product	
TSS .....	0.701	0.300
O&G .....	0.300	0.100
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

(2) [Reserved]

(c) *Fume scrubbers.*

## SUBPART L BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	BCT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kilograms per day	
TSS .....	38.1	16.3
O&G .....	16.3	5.45
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 6.0 to 9.0.

The above limitations shall be applicable to each fume scrubber associated with any of the coating operations specified above.

### Subpart M—Other Operations Subcategory

SOURCE: 67 FR 64268, Oct. 17, 2002, unless otherwise noted.

## § 420.130 Applicability.

The provisions of this subpart are applicable to discharges to waters of the U.S. and the introduction of pollutants into publicly owned treatment works resulting from production of direct-reduced iron and from briquetting and forging operations.

## § 420.131 Specialized definitions.

As used in this subpart:

(a) The term *briquetting operations* means a hot or cold process that agglomerates (presses together) iron-bearing materials into small lumps without melting or fusion. Used as a concentrated iron ore substitute for scrap in electric furnaces.

(b) The term *direct-reduced iron (DRI)* means iron produced by reduction of iron ore (pellets or briquettes) using gaseous (carbon monoxide-carbon dioxide, hydrogen) or solid reactants.

(c) The term *forging* means the hot-working of heated steel shapes (e.g., ingots, blooms, billets, slabs) by hammering or hydraulic presses, performed at iron and steel mills.

(d) For briquetting operations, the term product means the amount in tons of briquettes manufactured by hot or cold agglomeration processes.

(e) For direct reduced iron (DRI), the term product means the amount of direct reduced iron and any fines that are produced and sold commercially (as opposed to fines that may be reprocessed on site).

(f) For forging, the term product means the tons of finished steel forgings produced by hot working steel shapes.

(g) The term *O&G (as HEM)* means total recoverable oil & grease measured as n-hexane extractable materials.

### § 420.132 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve, for each applicable segment, the following effluent limitations representing the degree of effluent reduction attainable by the application of