

## Environmental Protection Agency

## § 421.51

### **§ 421.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

(a) Except as provided in 40 CFR 125.30 through 125.32 and paragraph (b) of this section, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): There shall be no discharge of process wastewater pollutants to navigable waters.

(b) A process wastewater impoundment which is designed, constructed, and operated so as to contain the precipitation from the 10-year, 24-hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration, for the area in which such impoundment is located may discharge that volume of process wastewater which is equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 10-year, 24-hour rainfall event, when such event occurs.

### **§ 421.43 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Subject to the provisions of paragraph (b) of this section, there shall be no discharge of process wastewater pollutants into navigable waters.

(b) A process wastewater impoundment which is designed, constructed, and operated so as to contain the precipitation from the 25-year, 24-hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration, for the area in which such impoundment is located may discharge that volume of process wastewater which is

equivalent to the volume of precipitation that falls within the impoundment in excess of that attributable to the 25-year, 24-hour rainfall event, when such event occurs.

[49 FR 8800, Mar. 8, 1984; 49 FR 26739, June 29, 1984]

### **§ 421.44 Standards of performance for new sources.**

Any new source subject to this subpart shall achieve the following new source performance standards: There shall be discharge of process wastewater pollutants into navigable waters.

### **§ 421.45 [Reserved]**

### **§ 421.46 Pretreatment standards for new sources.**

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources. The mass of wastewater pollutants in primary copper smelting process wastewater introduced into a POTW shall not exceed the following values: There shall be no discharge of process wastewater pollutants into a publicly owned treatment works.

### **§ 421.47 [Reserved]**

## **Subpart E—Primary Electrolytic Copper Refining Subcategory**

SOURCE: 49 FR 8801, Mar. 8, 1984, unless otherwise noted.

### **§ 421.50 Applicability: Description of the primary electrolytic copper refining subcategory.**

The provisions of this subpart apply to process wastewater discharges resulting from the electrolytic refining of primary copper, including, but not limited to, anode casting performed at refineries which are not located on-site with a smelter, product casting, and by-product recovery.

### **§ 421.51 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations, and