

**§ 421.91**

acid at primary copper smelters, primary zinc facilities, primary lead facilities, and primary molybdenum facilities, including any associated air pollution control or gas-conditioning systems for sulfur dioxide off-gases from pyrometallurgical operations.

[49 FR 8811, Mar. 8, 1984, as amended at 50 FR 38342, Sept. 20, 1985]

**§ 421.91 Specialized definitions.**

(a) Except as provided below, the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 apply to this subpart.

(b) The term *product* means 100 percent equivalent sulfuric acid, H<sub>2</sub> SO<sub>4</sub> capacity.

[50 FR 38342, Sept. 20, 1985]

**§ 421.92 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

**SUBPART I—METALLURGICAL ACID PLANT**

Pollutant or pollutant property	BPT effluent limitations	
	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds of 100% sulfuric acid capacity)	
Cadmium .....	0.180	0.090
Copper .....	5.000	2.000
Lead .....	1.800	0.790
Zinc .....	3.600	0.900
Fluoride <sup>1</sup> .....	212.800	121.000
Molybdenum <sup>1</sup> .....	40.180	20.790
Total suspended solids .....	304.000	152.000
pH .....	<sup>2</sup>	

<sup>1</sup> For Molybdenum Acid Plants Only.  
<sup>2</sup> Within the range of 6.0 to 9.0 at all times.

[50 FR 38342, Sept. 20, 1985; 50 FR 52776, Dec. 26, 1985]

**40 CFR Ch. I (7-1-09 Edition)**

**§ 421.93 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

**SUBPART I—METALLURGICAL ACID PLANT—BAT EFFLUENT LIMITATIONS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of 100 pct sulfuric acid capacity	
Arsenic .....	3.550	1.584
Cadmium .....	0.511	0.204
Copper .....	3.269	1.558
Lead .....	0.715	0.332
Zinc .....	2.605	1.073
Fluoride <sup>1</sup> .....	89.390	50.820
Molybdenum <sup>1</sup> .....	[Reserved]	[Reserved].

<sup>1</sup> For Molybdenum acid plants only.

[50 FR 38343, Sept. 20, 1985, as amended at 55 FR 31697, Aug. 3, 1990]

**§ 421.94 Standards of performance for new sources.**

Any new source subject to this subpart shall achieve the following new source performance standards:

**SUBPART I—METALLURGICAL ACID PLANT—NSPS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of 100 pct sulfuric acid capacity	
Arsenic .....	3.550	1.584
Cadmium .....	0.511	0.204
Copper .....	3.269	1.558
Lead .....	0.715	0.332
Zinc .....	2.605	1.073
Fluoride <sup>1</sup> .....	89.390	50.820
Molybdenum <sup>1</sup> .....	[Reserved]	[Reserved].
Total suspended solids .....	38.310	30.650
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> For Molybdenum acid plants only.  
<sup>2</sup> Within the range of 7.5 to 10.0 at all times.

[50 FR 38343, Sept. 20, 1985, as amended at 55 FR 31697, Aug. 3, 1990]