§425.83

§425.83 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT): The effluent limitations are those for Total Chromium contained in §425.81.

§425.84 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

	NSI	SPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly aver- age	
	Kg/kkg (or pounds per 1,000 lb) of raw material		
BOD5	5.8	2.6	
188	8.3	3.8	
Oil and grease	2.4	1.1	
Total chromium	0.15	0.05	
рН	(1)	(¹)	

¹ Within the range 6.0 to 9.0.

§425.85 Pretreatment standards for existing sources (PSES).

Except as provided in §425.04 and 40 CFR 403.7 and §403.13, any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403, and achieve the following pretreatment standards:

	PSES	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Milligrams per liter (mg/l)	
Sulfide	24	
I otal chromium	12	8
рН	(1)	(1)

¹Not less than 7.0.

[47 FR 52870, Nov. 23, 1982, as amended at 61 FR 35685, July 8, 1996]

40 CFR Ch. I (7–1–10 Edition)

§425.86 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7 and 425.04, any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403, and achieve the pretreatment standards contained in §425.85.

Subpart I—Retan-Wet Finish-Splits Subcategory

§ 425.90 Applicability; description of the retan-wet finish-splits subcategory.

The provisions of this subpart are applicable to process wastewater discharges resulting from any tannery which processes previously unhaired and tanned splits into finished leather by retan-wet finishing.

§ 425.91 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

	BPT limitations	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Kg/kkg (or pounds per 1,000 pounds) of raw material	
BOD ₅	5.8	2.6
TSS	8.3	3.8
Oil & Grease	2.4	1.1
Total Chromium	0.15	0.05
рН	(1)	(¹)

¹ Within the range of 6.0 to 9.0.

 $[47\ {\rm FR}\ 52870,\ {\rm Nov.}\ 23,\ 1982,\ {\rm as}\ {\rm amended}\ {\rm at}\ 53\ {\rm FR}\ 9183,\ {\rm Mar.}\ 21,\ 1988]$