

**§ 426.66**

| Effluent characteristic | Effluent limitations                      |   |
|-------------------------|---|---|
|                         | Maximum for any 1 day                     | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (q/sq m of product)          |   |
| TSS .....               | 0.24                                      | 0.24  |
| Oil .....               | 0.49                                      | .49   |
| pH .....                | ( <sup>1</sup> )                          | ( <sup>1</sup> )  |
|                         | English units (lb/1,000 sq ft of product) |   |
| TSS .....               | 0.05                                      | 0.05  |
| Oil .....               | 0.10                                      | .10   |
| pH .....                | ( <sup>1</sup> )                          | ( <sup>1</sup> )  |

<sup>1</sup> Within the range 6.0 to 9.0.

**§ 426.66 Pretreatment standards for new sources.**

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33959, June 29, 1995]

**§ 426.67 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 426.62 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 25000, July 9, 1986]

**Subpart G—Automotive Glass Laminating Subcategory**

SOURCE: 39 FR 5714, Feb. 14, 1974, unless otherwise noted.

**40 CFR Ch. I (7–1–10 Edition)**

**§ 426.70 Applicability; description of the automotive glass laminating subcategory.**

The provisions of this subpart are applicable to discharges of pollutants resulting from the processes which laminate a plastic sheet between two layers of glass, and which prepare the glass for lamination such as cutting, bending and washing, to produce automobile windshields.

**§ 426.71 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

**§ 426.72 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic | Effluent limitations                      |   |
|-------------------------|---|---|
|                         | Maximum for any 1 day                     | Average of daily values for 30 consecutive days shall not exceed— |
|                         | Metric units (q/sq m of product)          |   |
| TSS .....               | 4.40                                      | 4.40  |
| Oil .....               | 1.76                                      | 1.76  |
| Phosphorus .....        | 1.07                                      | 1.07  |
| pH .....                | ( <sup>1</sup> )                          | ( <sup>1</sup> )  |
|                         | English units (lb/1,000 sq ft of product) |   |
| TSS .....               | 0.90                                      | 0.90  |
| Oil .....               | 0.36                                      | .36   |
| Phosphorus .....        | 0.22                                      | .22   |
| pH .....                | ( <sup>1</sup> )                          | ( <sup>1</sup> )  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 5714, Feb. 14, 1974, as amended at 60 FR 33959, June 29, 1995]