

**§ 436.100**

(b) Only that volume of water resulting from precipitation that exceeds the maximum safe surge capacity of a process waste water impoundment may be discharged from that impoundment. The height difference between the maximum safe surge capacity level and the normal operating level must be greater than the inches of rain representing the 10-year, 24-hour rainfall event as established by the National Climatic Center, National Oceanic and Atmospheric Administration for the locality in which such impoundment is located.

[40 FR 48657, Oct. 16, 1975, as amended at 60 FR 33967, June 29, 1995]

**Subpart H—Lightweight Aggregates Subcategory [Reserved]**

**Subpart I—Mica and Sericite Subcategory [Reserved]**

**Subpart J—Barite Subcategory**

**§ 436.100 Applicability; description of the barite subcategory.**

The provisions of this subpart are applicable to the processing of barite.

**§ 436.101 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

**§ 436.102 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): For operations not employing wet processes or flotation processes there shall be no discharge of process gen-

**40 CFR Ch. I (7-1-10 Edition)**

erated waste water pollutants into navigable waters.

[60 FR 33967, June 29, 1995]

**Subpart K—Fluorspar Subcategory**

**§ 436.110 Applicability; description of the fluorspar subcategory.**

The provisions of this subpart are applicable to the processing of fluorspar.

**§ 436.111 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.

**§ 436.112 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.**

Except as provided in §§125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT): For operations not employing heavy media separation or flotation processes there shall be no discharge of process generated waste water pollutants into navigable waters.

[60 FR 33967, June 29, 1995]

**Subpart L—Salines From Brine Lakes Subcategory**

**§ 436.120 Applicability; description of the salines from brine lakes subcategory.**

The provisions of this subpart are applicable to the processing of salines from brine lakes.

**§ 436.121 Specialized definitions.**

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in part 401 of this chapter shall apply to this subpart.