## **Environmental Protection Agency**

## **PSNS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	kg/1,000 kkg (pounds per million pounds) of metal poured	
Copper (T)	0.0527 0.0964 0.178 0.0257	0.0291 0.0473 0.0673 0.00838
monitoring)	5.46	1.82

(2) Applicable to plants that are casting primarily steel, to plants that are casting primarily malleable iron where equal to or less than 3,557 tons of metal are poured per year, and to plants that are casting primarily gray iron where equal to or less than 1,784 tons of metal are poured per year.

## **PSNS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	kg/1,000 kkg (pounds per million pounds) of metal poured	
Copper (T)	0.0527 0.144 0.267 0.0257	0.0291 0.0709 0.102 0.00838
Oil and grease (for alternate monitoring)	5.46	1.82

(i) Wet Sand Reclamation Operations.
(1) Applicable to plants that are casting primarily ductile iron, to plants that are casting primarily malleable iron where greater than 3,557 tons of metal are poured per year, and to plants that are casting primarily gray iron where greater than 1,784 tons of metal are poured per year.

### **PSNS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	kg/1,000 kkg (p lion pounds) claimed	oounds per mil of sand re
Copper (T)	0.217 0.396 0.732 0.642 1.18	0.12 0.194 0.276 0.224 0.386
nate monitoring)	22.4	7.47

(2) Applicable to plants that are casting primarily steel, to plants that are casting primarily malleable iron where equal to or less than 3,557 tons of metal are poured per year, and to plants that are casting primarily gray iron where equal to or less than 1,784 tons of metal are poured per year.

#### **PSNS**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	kg/1,000 kkg (p lion pounds) claimed	oounds per mil- of sand re-
Copper (T) Lead (T)	0.217 0.59 1.10 0.642 1.18	0.12 0.291 0.418 0.224 0.386
nate monitoring)	22.4	7.47

§ 464.37 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology. [Reserved]

# Subpart D—Zinc Casting Subcategory

# § 464.40 Applicability; description of the zinc casting subcategory.

The provisions of this subpart are applicable to discharges to waters of the United States and to the introduction of pollutants into publicly owned treatment works resulting from zinc casting operations as defined in §464.02(d).

# § 464.41 Specialized definitions.

For the purpose of this subpart:

- (a) Total Toxic Organics (TTO). TTO is a regulated parameter under PSES (§464.45) and PSNS (§464.46) for the zinc subcategory and is comprised of a discrete list of toxic organic pollutants for each process segment where it is regulated, as follows:
- (1) Casting Quench ( $\S464.45(a)$ ) and  $\S464.46(a)$ ):
- 21. 2,4,6-trichlorophenol
- 22. para-chloro meta-cresol
- 31. 2,4-dichlorophenol
- 34. 2,4-dimethylphenol
- 39. fluoranthene
- 44. methylene chloride (dichloromethane)
- 65. phenol