# **Environmental Protection Agency**

 $[48\ {\rm FR}\ 49149,\ {\rm Oct.}\ 24,\ 1983;\ 49\ {\rm FR}\ 11631$  and  $11633,\ {\rm Mar.}\ 27,\ 1984]$ 

# § 467.24 New source performance standards.

Any new source subject to this subpart must achieve the following performance standards. The discharge of process wastewater pollutants from the core shall not exceed the values set forth below:

# Subpart B

#### Core

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		illion off-lbs) of lled with emul-
Chromium	0.048	0.020
Cyanide	0.026	0.011
Zinc	0.133	0.055
Aluminum	0.80	0.35
Oil and grease	1.30	1.30
Suspended solids	1.95	1.56
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.0 to 10.0 at all times.

# SUBPART B

# $\begin{array}{c} \textit{Direct Chill Casting Contact Cooling} \\ \textit{Water} \end{array}$

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) o aluminum cast by semicontinuous methods	
Chromium	0.49	0.20
Cyanide	0.27	0.11
Zinc	1.36	0.56
Aluminum	8.12	3.60
Oil and grease	13.29	13.29
Suspended solids	19.94	15.95
pH	(1)	( <sup>1</sup> )

<sup>&</sup>lt;sup>1</sup>The pH shall be maintained within the range of 7.0 to 10.0 at all times except for those situations when this waste stream is discharged separately and without commingling with any other wastewater in which case the pH shall be within the range of 6.0 to 10.0 at all times.

# SUBPART B

# $Solution \ Heat \ Treatment \ Contact \ Cooling \\ Water$

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum quenched	
Chromium	0.76	0.31
Cyanide	0.41	0.17
Zinc	2.08	0.86
Aluminum	12.45	5.52
Oil and grease	20.37	20.37
Suspended solids	30.56	24.45
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.0 to 10.0 at all times.

#### Subpart B

#### Cleaning or Etching Bath

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/m aluminum clea	illion off-lbs) of ined or etched
01 .		
Chromium	0.067	0.027
Cyanide	0.036	0.015
Zinc	0.183	0.075
Aluminum	1.094	0.485
Oil and grease	1.79	1.79
Suspended solids	2.69	2.15
pH	(1)	( <sup>1</sup> )

<sup>&</sup>lt;sup>1</sup> Within the range of 7.0 to 10.0 at all times.

# Subpart B

### Cleaning or Etching Rinse

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium	0.52	0.21
Cyanide	0.28	0.11
Zinc	1.42	0.59
Aluminum	8.50	3.77
Oil and grease	13.91	13.91
Suspended solids	20.87	16.70
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.0 to 10.0 at all times.

 $\label{eq:Subpart B} Subpart \ B$  Cleaning or Etching Scrubber Liquor

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium	0.72	0.29
Cyanide	0.39	0.16
Zinc	1.97	0.81
Aluminum	11.81	5.24
Oil and grease	19.33	19.33
Suspended solids	29.00	23.20
pH	(1)	(1)

<sup>&</sup>lt;sup>1</sup> Within the range of 7.0 to 10.0 at all times.

[48 FR 49149, Oct. 24, 1983; 49 FR 11631 and 11633, Mar. 27, 1984, as amended at 53 FR 52370, Dec. 27, 1988]

# § 467.25 Pretreatment standards for existing sources.

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources. The mass of wastewater pollutants in aluminum forming process wastewater introduced into a POTW shall not exceed the following values:

Subpart B

### Core

Maximum for any 1 day   monthly age   mg/off-kg (lb/million off-laluminum rolled with sions     0.057   Cyanide   0.038   Zinc   0.190   TTO   0.090			
Maximum for any 1 day   monthly age   mg/off-kg (lb/million off-laluminum rolled with sions		PSES	
aluminum rolled with sions	Pollutant or pollutant property		Maximum for monthly average
Cyanide 0.038   Zinc 0.190   TTO 0.090   Oil and grease (alternate 0.090		mg/off-kg (lb/million off-lbs) aluminum rolled with emu sions	
Zinc	Chromium	0.057	0.024
TTO	Cyanide	0.038	0.016
Oil and grease (alternate	Zinc	0.190	0.079
	TTO	0.090	
		6.8	3.4

# SUBPART B

# Direct Chill Casting Contact Cooling Water

	PSES	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) aluminum cast by sem continuous methods	
Chromium	0.59	0.24
Cyanide	0.39	0.16
Zinc	1.94	0.81
TTO	0.92	
Oil and grease (alternate monitoring parameter)	69	35

# SUBPART B

### Solution Heat Treatment Contact Cooling Water

	PSES	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) o aluminum quenched	
Chromium	0.90	0.37
Cyanide	0.59	0.25
Zinc	2.98	1.25
TTO	1.41	
Oil and grease (alternate monitoring parameter)	110	53

# Subpart B

# Cleaning or Etching Bath

	PSES	
Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (lb/million off-lbs) of aluminum cleaned or etched	
Chromium	0.079	0.032
Cyanide	0.052	0.022
Zinc	0.262	0.109
TTO	0.124	
Oil and grease (alternate monitoring parameter)	9.3	4.7