

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/off-kg of copper or copper alloy tumbled or burnished	
	English units—pounds per 1,000,000 off-pounds of copper or copper alloy tumbled or burnished	
Chromium .....	0.215	0.087
Copper .....	0.746	0.355
Lead .....	0.058	0.052
Nickel .....	0.320	0.215
Zinc .....	0.594	0.244
TTO .....	0.198	0.198
Oil and grease <sup>1</sup> .....	5.830	5.830

<sup>1</sup> For alternate monitoring.

(p) Subpart A—Surface Coating PSNS.

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/off-kg of copper or copper alloy surface coated	
	English units—pounds per 1,000,000 off-pounds of copper or copper alloy surface coated	
Chromium .....	0.274	0.111
Copper .....	0.951	0.453
Lead .....	0.074	0.066
Nickel .....	0.408	0.274
Zinc .....	0.757	0.312
TTO .....	0.252	0.252
Oil and grease <sup>1</sup> .....	7.430	7.430

<sup>1</sup> For alternate monitoring.

(q) Subpart A—Miscellaneous Waste Streams PSNS.

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	Metric units—mg/off-kg of copper or copper alloy formed	
	English units—pounds per 1,000,000 off-pounds of copper or copper alloy formed	
Chromium .....	0.008	0.003
Copper .....	0.027	0.013
Lead .....	0.0021	0.0019
Nickel .....	0.011	0.008
Zinc .....	0.022	0.009
TTO .....	0.007	0.007
Oil and grease <sup>1</sup> .....	0.218	0.218

<sup>1</sup> For alternate monitoring.

[48 FR 36957, Aug. 15, 1983; 48 FR 50719, Nov. 3, 1983]

**§ 468.16 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollution control technology (BCT). [Reserved]**

**Subpart B—Beryllium Copper Forming Subcategory**

**§ 468.20 Applicability; description of the beryllium copper forming subcategory.**

This subpart applies to discharges of pollutants to waters of the United States, and introduction of pollutants into publicly owned treatment works from the forming of beryllium copper alloys.

[51 FR 7571, Mar. 5, 1986]

**PART 469—ELECTRICAL AND ELECTRONIC COMPONENTS POINT SOURCE CATEGORY**

**Subpart A—Semiconductor Subcategory**

Sec.

- 469.10 Applicability.
- 469.11 Compliance dates.
- 469.12 Specialized definitions.
- 469.13 Monitoring.
- 469.14 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).
- 469.15 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).
- 469.16 Pretreatment standards for existing sources (PSES).
- 469.17 New source performance standards (NSPS).
- 469.18 Pretreatment standards for new sources (PSNS).
- 469.19 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollution control technology (BCT).

**Subpart B—Electronic Crystals Subcategory**

- 469.20 Applicability.
- 469.21 Compliance dates.
- 469.22 Specialized definitions.
- 469.23 Monitoring.
- 469.24 Effluent limitations representing the degree of effluent reduction attainable