

§ 761.292

grid origin, has sides one grid interval more distant from the grid origin than the inner boundary, and is two grid intervals longer on a side than the inner boundary.

(C) *Taking composite samples from the initial and subsequent compositing areas.*

(1) Select composite sampling areas from the initial compositing area and subsequent compositing areas such that all grid points in the initial compositing area and subsequent compositing areas are part of a composite or individual sample.

(2) A person may include in a single composite sample a maximum of all nine grid points in the initial compositing area. The maximum number of grid points in a composite sample taken from a subsequent compositing area is eight. These eight grid points must be adjacent to one another in the subsequent compositing area, but need not be collinear.

(2) *Compositing from samples taken at grid points or pairs of coordinates in accordance with § 761.283(c).* Samples collected at small sites are based on selecting pairs of coordinates or using the sample site selection procedure for grid sampling with a smaller grid interval.

(i) *Samples collected from a grid having a smaller grid interval.* Use the procedure in paragraph (b)(1)(i) of this section to composite samples and determine the area of inference for composite samples.

(ii) *Samples collected from pairs of coordinates.* All three samples must be composited. The area of inference for the composite is the entire area sampled.

§ 761.292 Chemical extraction and analysis of individual samples and composite samples.

Use either Method 3500B/3540C or Method 3500B/3550B from EPA's SW-846, Test Methods for Evaluating Solid Waste, or a method validated under subpart Q of this part, for chemical extraction of PCBs from individual and composite samples of PCB remediation waste. Use Method 8082 from SW-846, or a method validated under subpart Q of this part, to analyze these extracts for PCBs.

40 CFR Ch. I (7-1-10 Edition)

§ 761.295 Reporting and recordkeeping of the PCB concentrations in samples.

(a) Report all sample concentrations for bulk PCB remediation waste and porous surfaces on a dry weight basis and as micrograms of PCBs per gram of sample (ppm by weight).

(b) Record and keep on file for 3 years the PCB concentration for each sample or composite sample.

§ 761.298 Decisions based on PCB concentration measurements resulting from sampling.

(a) For grid samples which are chemically analyzed individually, the PCB concentration applies to the area of inference as described in § 761.283(d).

(b) For grid samples analyzed as part of a composite sample, the PCB concentration applies to the area of inference of the composite sample as described in § 761.283(d) (i.e., the area of inference is the total of the areas of the individual samples included in the composite).

(c) For coordinate pair samples analyzed as part of a composite sample, in accordance with §§ 761.283(c)(2) and 761.289(b)(2)(ii), the PCB concentration applies to the entire cleanup site.

Subpart P—Sampling Non-Porous Surfaces for Measurement-Based Use, Reuse, and On-Site or Off-Site Disposal Under § 761.61(a)(6) and Decontamination Under § 761.79(b)(3)

SOURCE: 63 FR 35467, June 29, 1998, unless otherwise noted.

§ 761.300 Applicability.

This subpart provides sample site selection procedures for large, nearly flat non-porous surfaces, and for small or irregularly shaped non-porous surfaces. This subpart also provides procedures for analyzing the samples and interpreting the results of the sampling. Any person verifying completion of self-implementing cleanup and on-site disposal of non-porous surfaces under § 761.61(a)(6), or verifying that decontamination standards under

Environmental Protection Agency

§ 761.306

§ 761.79(b)(3) are met, must use these procedures.

§ 761.302 Proportion of the total surface area to sample.

(a) *Large nearly flat surfaces.* Divide the entire surface into approximately 1 meter square portions and mark the portions so that they are clearly identified. Determine the sample location in each portion as directed in § 761.304.

(1) For large nearly flat surfaces contaminated by a single source of PCBs with a uniform concentration, assign each 1 meter square surface a unique sequential number.

(i) For three or fewer 1 meter square areas, sample all of the areas.

(ii) For four or more 1 meter square areas, use a random number generator or table to select a minimum of 10 percent of the areas from the list, or to select three areas, whichever is more.

(2) For other large nearly flat surfaces, sample all of the one meter square areas.

(b) *Small or irregularly shaped surfaces.* For small surfaces having irregular contours, such as hand tools, natural gas pipeline valves, and most exterior surfaces of machine tools, sample the entire surface. Any person may select sampling locations for small, nearly flat surfaces in accordance with § 761.308 with the exception that the maximum area in § 761.308(a) is <1 meter square.

(c) *Preparation of surfaces.* Drain all free-flowing liquids from surfaces and brush off dust or loose grit.

§ 761.304 Determining sample location.

(a) For 1 square meter non-porous surface areas having the same size and shape, it is permissible to sample the same 10 cm by 10 cm location or position in each identical 1 square meter area. This location or position is determined in accordance with § 761.306 or § 761.308.

(b) If some 1 square meter surfaces for a larger non-porous surface area have different sizes and shapes, separately select the 10 cm by 10 cm sampling position for each different 1 square meter surface in accordance with § 761.308.

(c) If non-porous surfaces have been cleaned and the cleaned surfaces do not

meet the applicable standards or levels, surfaces may be recleaned and resampled. When resampling surfaces previously sampled to verify cleanup levels, use the sampling procedures in §§ 761.306 through 761.316 to resample the surfaces. If any sample site selected coincides with a previous sampling site, restart the sample selection process until all resampling sites are different from any previous sampling sites.

§ 761.306 Sampling 1 meter square surfaces by random selection of halves.

(a) Divide each 1 meter square portion where it is necessary to collect a surface wipe test sample into two equal (or as nearly equal as possible) halves. For example, divide the area into top and bottom halves or left and right halves. Choose the top/bottom or left/right division that produces halves having as close to the shape of a circle as possible. For example, a square is closer to the shape of a circle than is a rectangle and a rectangle having a length to width ratio of 2:1 is closer to the shape of a circle than a rectangle having a length to width ratio of 3:1.

(b) Assign a unique identifier to each half and then select one of the halves for further sampling with a random number generator or other device (i.e., by flipping a coin).

(c) Continue selecting progressively smaller halves by dividing the previously selected half, in accordance with paragraphs (a) and (b) of this section, until the final selected half is larger than or equal to 100 cm² and smaller than 200 cm².

(d) Perform a standard PCB wipe test on the final selected halves from each 1 meter square portion.

(e) The following is an example of applying sampling by halves. Assume that the area to sample is a 1 meter square surface area (a square that has sides 1 meter long). Assign each half to one face of a coin. After flipping the coin, the half assigned to the face of the coin that is showing is the half selected.

(1) Selecting the first half:

(i) For a square shape the top/bottom halves have the same shape as the left/right halves when compared to a circle,