

part of the vessel which normally contains sources of vapor ignition, and shall be so located as to minimize the possibility of recirculating contaminated air through the pumproom.

(3) Cargo pumprooms handling Grade D and/or E liquid cargo only shall be fitted with at least two ducts extended to the weather deck, one of which shall be extended to a point near the floor level. This does not preclude installation of power ventilation, if desired.

(4) The ventilation required in this paragraph shall be sufficient to properly ventilate the pumproom with the access openings closed.

(d) *Access.* The access to a cargo pumproom in a tank vessel carrying Grade A, B, C, or D liquid cargo shall be from the open deck.

[CGFR 65-50, 30 FR 16671, Dec. 30, 1965, as amended by CGFR 70-143, 35 FR 19905, Dec. 30, 1970]

§ 32.60-25 Living quarters—TB/ALL.

For living quarters the partitions and sheathing shall be of an approved fire resistive construction. The specification for incombustible materials is in subchapter Q (Specifications) of this chapter.

[CGFR 65-50, 30 FR 16671, Dec. 30, 1965, as amended by CGD 95-028, 62 FR 51198, Sept. 30, 1997]

§ 32.60-30 Tank vessels with independent tanks—TB/ALL.

(a) Independent cargo tanks may be located in hold spaces or in other cargo tanks; however, a working space of at least 15 inches shall be maintained around each independent tank, or else provisions shall be made for moving such tanks to furnish such working space, except that less than 15 inches around such tanks may be permitted if in the judgment of the Officer in Charge, Marine Inspection, having jurisdiction, a satisfactory inspection of the cargo tanks and hull structure can be made.

(b) When an independent cargo tank is located in an enclosed space other than a cargo tank, such enclosed space shall be considered as equivalent to a pumproom and shall be safeguarded as such as required by this subpart.

(c) Cargo tanks independent of the hull structure shall be supported in

saddles or on foundations of steel or other suitable material and securely attached in place to preclude the cargo from being damaged or shifting as a result of collision. The arrangement shall be such as to permit longitudinal and circumferential, or athwartship and vertical, expansion of the cargo tanks. Each tank shall be supported so as to prevent the concentration of excessive loads on the supporting portion of the shell.

§ 32.60-35 Tank vessels carrying Grade A liquid cargo—TB/ALL.

(a) Grade A liquids having a Reid vapor pressure in excess of 25 pounds per square inch shall be transported in cargo tanks which are independent of the hull.

(b) Barges carrying Grade A liquids having a Reid vapor pressure in excess of 25 pounds per square inch shall be of a Type III barge hull as defined in § 32.63-5(b)(3).

[CGFR 70-10, 35 FR 3709, Feb. 25, 1970]

§ 32.60-40 Construction and testing of cargo tanks and bulkheads—TB/ALL.

(a) All cargo tanks vented at gage pressure of 4 pounds per square inch or less shall be constructed and tested as required by standards established by the American Bureau of Shipping or other recognized classification society. The design of cargo tanks integral with the hull and vented at a gage pressure exceeding 4 pounds per square inch but not exceeding 10 pounds per square inch gage pressure will be given special consideration by the Commandant.

(b) Cargo tanks vented at a gage pressure exceeding 10 pounds per square inch are considered to be pressure vessels and shall be of cylindrical or similar design and shall meet the requirements of subchapter F (Marine Engineering) of this chapter.

[CGFR 65-50, 30 FR 16671, Dec. 30, 1965, as amended by CGFR 68-82, 33 FR 18805, Dec. 18, 1968]

§ 32.60-45 Segregation of spaces containing the emergency source of electric power—TB/ALL.

(a) The provisions of this section shall apply to all vessels contracted for on or after October 1, 1958.

(b) When a compartment containing the emergency source of electric power, or vital components thereof, adjoins a space containing either the ship's service generators or machinery necessary for the operation of the ship's service generators, all common bulkheads and/or decks shall be protected by approved "structural insulation" or other approved material. This protection shall be such as to be capable of preventing an excessive temperature rise in the space containing the emergency source of electric power, or vital components thereof, for a period of at least one hour in the event of fire in the adjoining space. Bulkheads or decks meeting Class A-60 requirements, as defined by § 72.05-10 of subchapter H (Passenger Vessels) of this chapter, will be considered as meeting the requirements of this paragraph.

Subpart 32.63—Hull and Cargo Tank Requirements for Tank Barges Constructed or Converted On or After July 1, 1964, and Carrying Certain Dangerous Bulk Cargoes

§ 32.63-1 Application—B/ALL.

(a) The requirements of this subpart shall apply to all tank barges, the construction or conversion of which is started on or after July 1, 1964, and carrying those cargoes listed in Table 30.25-1 which are defined as:

(1) Flammable liquids having a Reid vapor pressure in excess of 25 pounds per square inch, absolute, in independent tanks (part 32).

(2) Liquefied flammable gases (part 38 of this subchapter).

[CGFR 70-10, 35 FR 3709, Feb. 25, 1970]

§ 32.63-5 Barge hull classifications—B/ALL.

(a) Each barge subject to the provision of this subpart shall be assigned a hull type number. The Commandant will designate the barge hull types to be used for carrying cargoes in order to insure that the vessel is designed consistent with the degree and nature of the hazard of the commodity carried.

(b) For this purpose the barge hull types shall be as follows:

(1) *Type I barge hull.* Barge hulls classed as Type I are those designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo to the waterways and/or atmosphere.

(2) *Type II barge hull.* Barge hulls classed as Type II are those designed to carry products which require substantial preventive measures to preclude uncontrolled release to the atmosphere, but whose uncontrolled release to the waterways does not constitute a longlasting public or operating personnel hazard, though local and temporary pollution may occur.

(3) *Type III barge hull.* Barge hulls classed as Type III are those designed to carry products of sufficient hazard to require a moderate degree of control.

§ 32.63-8 Alternative arrangements—B/ALL.

(a) Alternative arrangements, differing from those specifically required by this subpart, may be considered and approved by the Commandant, if it is demonstrated to his satisfaction that a degree of safety is obtained which is consistent with the intent of this subpart.

§ 32.63-10 Rakes and coamings—B/ALL.

(a) Each barge hull shall be constructed with a suitable blow form (length, shape, and height of headlog) to protect against diving at the maximum speed at which the barge is designed to be towed. In any integrated tow, only the lead barge need comply with this requirement. In any case, the operator of the towing vessel shall be guided by appropriate speed limitations.

(b) All open hopper type barge hulls shall be provided with coamings around the hopper space and, additionally, a 36-inch minimum height plowshare breakwater on the forward rake. Coamings shall have a minimum height of 36 inches forward graduated to a minimum height of 24 inches at midlength and 18 inches thereafter.

§ 32.63-20 Hull structure—B/ALL.

(a) *General.* In addition to complying with the requirements of § 32.60-1, as