

CHEST—FLAMMABLE—KEEP LIGHTS AND FIRE AWAY”.

(b) [Reserved]

§ 78.47-75 Ventilation alarm failure.

(a) The alarm required by § 72.15-15 (c)(4) of this subchapter, which indicates the loss of required ventilation in spaces specially suitable for vehicles, shall be marked with a conspicuous sign in at least ¼-inch letters “VENTILATION FAILURE IN VEHICULAR SPACE.”

(b) [Reserved]

[CGFR 66-33, 31 FR 15284, Dec. 6, 1966]

§ 78.47-90 Vessels contracted for prior to November 19, 1952.

(a) Vessels contracted for prior to November 19, 1952, shall meet the requirements of this paragraph.

(1) The requirements of §§ 78.47-5 through 78.47-75 shall be met with the exception that existing signs and markings containing the same general intent, but not necessarily identical wording or exact letter type, size, or color, may be retained so long as they are in good condition to the satisfaction of the Officer in Charge, Marine Inspection.

(2) [Reserved]

(b) [Reserved]

[CGFR 65-50, 30 FR 16955, Dec. 30, 1965, as amended by CGFR 66-33, 31 FR 15284, Dec. 6, 1966]

Subpart 78.50—Markings on Vessels

§ 78.50-1 Application.

(a) The provisions of this subpart shall apply to all vessels except as specifically noted in this subpart.

(b) [Reserved]

§ 78.50-5 Hull markings.

Vessels shall be marked as required by parts 67 and 69 of this chapter.

[CGD 72-104R, 37 FR 14233, July 18, 1972]

§ 78.50-10 Draft marks and draft indicating systems.

(a) All vessels must have draft marks plainly and legibly visible upon the stem and upon the sternpost or rudderpost or any place at the stern of the vessel as may be necessary for easy

observance. The bottom of each mark must indicate the draft.

(b) The draft must be taken from the bottom of the keel to the surface of the water at the location of the marks.

(c) In cases where the keel does not extend forward or aft to the locations of the draft marks, due to raked stem or cut-away skeg, the datum line from which the draft shall be taken shall be obtained by projecting the line of the bottom of keel forward or aft, as the case may be, to the location of the draft marks.

(d) In cases where a vessel may have a skeg or other appendage extending locally below the line of the keel, the draft at the end of the vessel adjacent to such appendage shall be measured to a line tangent to the lowest part of such appendage and parallel to the line of the bottom of the keel.

(e) Draft marks must be separated so that the projections of the marks onto a vertical plane are of uniform height equal to the vertical spacing between consecutive marks.

(f) Draft marks must be painted in contrasting color to the hull.

(g) In cases where draft marks are obscured due to operational constraints or by protrusions, the vessel must be fitted with a reliable draft indicating system from which the bow and stern drafts can be determined.

[CGFR 65-50, 30 FR 16955, Dec. 30, 1965, as amended by CGD 72-104R, 37 FR 14233, July 18, 1972; CGD 89-037, 57 FR 41822, Sept. 11, 1992]

§ 78.50-15 Load line marks.

(a) Vessels assigned a load line shall have the deck line and the load line marks permanently scribed or embossed as required by subchapter E (Load Lines) of this chapter.

(b) [Reserved]

Subpart 78.55—Carrying of Excess Steam

§ 78.55-1 Master and chief engineer responsible.

It shall be the duty of the master and the engineer in charge of the boilers of any vessel to require that a steam pressure is not carried in excess of that allowed by the certificate of inspection, and to require that the safety valves,