

## § 92.25–90

### § 92.25–90 Vessels contracted for prior to July 1, 1969.

(a) Vessels contracted for prior to July 1, 1969, assigned a deeper load line under part 42 of subchapter E (Load Lines) of this chapter shall have efficient guard rails or bulwarks as required by § 92.25–5. Otherwise, existing structure, arrangements, materials, and facilities previously approved will be considered satisfactory so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standards as the original construction. However, in no case will greater departure from the standards of §§ 92.25–5 through 92.25–15 be permitted than presently exists.

[CGFR 69–72, 34 FR 17484, Oct. 29, 1969, as amended by CGD 80–120, 47 FR 5723, Feb. 8, 1982]

## PART 93—STABILITY

AUTHORITY: 46 U.S.C. 3306, 5115; E.O. 12234, 45 FR 58801, 3 CFR, 1980 Comp., p. 277; 49 CFR 1.46.

### Subpart 93.01—Application

#### § 93.01–1 General.

Each vessel must meet the applicable requirements in subchapter S of this chapter.

[CGD 79–023, 48 FR 51008, Nov. 4, 1983]

## PART 95—FIRE PROTECTION EQUIPMENT

### Subpart 95.01—Application

Sec.

95.01–1 General.

95.01–2 Incorporation by reference.

95.01–5 Equipment installed but not required.

### Subpart 95.05—Fire Detecting and Extinguishing Equipment, Where Required

95.05–1 Fire detecting, manual alarm, and supervised patrol systems.

95.05–5 Fire main system.

95.05–10 Fixed fire extinguishing systems.

95.05–15 Hand portable fire extinguishers and semiportable fire extinguishing systems.

## 46 CFR Ch. I (10–1–10 Edition)

### Subpart 95.10—Fire Main System, Details

95.10–1 Application.

95.10–5 Fire pumps.

95.10–10 Fire hydrants and hose.

95.10–15 Piping.

95.10–90 Installations contracted for prior to May 26, 1965.

### Subpart 95.13—Steam Smothering Systems

95.13–1 Application.

### Subpart 95.15—Carbon Dioxide Extinguishing Systems, Details

95.15–1 Application.

95.15–5 Quantity, pipe sizes, and discharge rates.

95.15–10 Controls.

95.15–15 Piping.

95.15–20 Carbon dioxide storage.

95.15–25 Discharge outlets.

95.15–30 Alarms.

95.15–35 Enclosure openings.

95.15–40 Pressure relief.

95.15–90 Installations contracted for prior to November 19, 1952.

### Subpart 95.17—Foam Extinguishing Systems, Details

95.17–1 Application.

95.17–5 Quantity of foam required.

95.17–10 Controls.

95.17–15 Piping.

95.17–20 Discharge outlets.

95.17–25 Additional protection required.

95.17–90 Installations contracted for prior to November 19, 1952.

### Subpart 95.30—Automatic Sprinkler Systems, Details

95.30–1 Application.

### Subpart 95.50—Hand Portable Fire Extinguishers and Semiportable Fire Extinguishing Systems, Arrangements and Details

95.50–1 Application.

95.50–5 Classification.

95.50–10 Location.

95.50–15 Spare charges.

95.50–20 Semiportable fire extinguishers.

95.50–90 Vessels contracted for prior to November 19, 1952.

### Subpart 95.60—Fire Axes

95.60–1 Application.

95.60–5 Number required.

95.60–10 Location.

AUTHORITY: 46 U.S.C. 3306; E.O. 12234, 45 FR 58801, 3 CFR, 1980 Comp., p. 277; Department of Homeland Security Delegation No. 0170.1.