

TABLE E-11—MAXIMUM ERP (WATTS) FOR BASE TRANSMITTERS (HAAT MORE THAN 152 METERS)—Continued

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)					
	152 (500)	305 (1000)	457 (1500)	610 (2000)	762 (2500)	914 (3000)
209 (130) .....	100	48	21	11	7	5
193 (120) .....	50	19	9	5	3	2

See § 22.659(b)(3). This table is for antenna heights of more than 152 meters (500 feet) above average terrain. For intermediate values of height and/or distance, use linear interpolation to obtain the maximum permitted ERP.

TABLE E-12—MAXIMUM ERP (WATTS) FOR BASE TRANSMITTERS

Distance to protected TV station in kilometers (miles)	Antenna height above average terrain in meters (feet)								
	30 (100)	46 (150)	61 (200)	76 (250)	91 (300)	107 (350)	122 (400)	137 (450)	152 (500)
108 (67) .....	1000	1000	1000	1000	1000	1000	1000	1000	1000
106 (66) .....	1000	1000	1000	1000	1000	1000	1000	1000	750
105 (65) .....	1000	1000	1000	1000	1000	1000	825	650	600
103 (64) .....	1000	1000	1000	1000	1000	775	625	500	400
101 (63) .....	1000	1000	1000	1000	440	400	350	320	300
100 (62) .....	1000	1000	1000	525	375	250	200	150	125
98 (61) .....	1000	700	450	250	200	125	100	75	50
97 (60) .....	1000	425	225	125	100	75	50	.....	.....

See § 22.659(c)(2). This table applies to base transmitters in the New York-Northeastern New Jersey urban areas. This table is for antenna heights of 152 meters (500 feet) or less above average terrain. For antenna heights between those in the table, use the next higher antenna height. For distances between those in the table, use the next lower distance.

[59 FR 59507, Nov. 17, 1994, as amended at 63 FR 68947, Dec. 14, 1998]

**Subpart F—Rural Radiotelephone Service**

**§ 22.701 Scope.**

The rules in this subpart govern the licensing and operation of stations and systems in the Rural Radiotelephone Service. The licensing and operation of these stations and systems is also subject to rules elsewhere in this part that apply generally to the Public Mobile Services. In case of conflict, however, the rules in this subpart govern.

**§ 22.702 Eligibility.**

Existing and proposed communications common carriers are eligible to hold authorizations to operate conventional central office, interoffice and rural stations in the Rural Radiotelephone Service. Subscribers are also eligible to hold authorizations to operate rural subscriber stations in the Rural Radiotelephone Service.

[69 FR 75170, Dec. 15, 2004]

**§ 22.703 Separate rural subscriber station authorization not required.**

A separate authorization is not required for rural subscriber stations for

which the effective radiated power does not exceed 60 Watts and for which FAA notification of construction or alteration of the antenna structure is not required (see criteria in § 17.7 of this chapter). Authority to operate such rural subscriber stations is conferred by the authorization of the central office or base station from which they receive service.

**§ 22.705 Rural radiotelephone system configuration.**

Stations in the Rural Radiotelephone Service are authorized to communicate as follows:

(a) Rural subscriber stations are authorized to communicate with and through the central office station(s) with which they are associated. However, where the establishment of a central office station in this service is not feasible, rural subscriber stations may be authorized to communicate with and through a base station in the Paging and Radiotelephone Service.

(b) Central office stations may communicate only with rural subscriber stations.