

§ 22.905

and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html.

(2) Provide AMPS, upon request, to subscribers and roamers using such cellular telephones while such subscribers are located in any portion of the cellular system's CGSA where facilities have been constructed and service to subscribers has commenced. See also § 20.12 of this chapter. Cellular licensees must allot sufficient system resources such that the quality of AMPS provided, in terms of geographic coverage and traffic capacity, is fully adequate to satisfy the concurrent need for AMPS availability.

[67 FR 77191, Dec. 17, 2002, as amended at 69 FR 18803, Apr. 9, 2004]

§ 22.905 Channels for cellular service.

The following frequency bands are allocated for assignment to service providers in the Cellular Radiotelephone Service.

(a) Channel Block A: 869–880 MHz paired with 824–835 MHz, and 890–891.5 MHz paired with 845–846.5 MHz.

(b) Channel Block B: 880–890 MHz paired with 835–845 MHz, and 891.5–894 MHz paired with 846.5–849 MHz.

[67 FR 77191, Dec. 17, 2002]

§ 22.907 Coordination of channel usage.

Licensees in the Cellular Radiotelephone Service must coordinate, with the appropriate parties, channel usage at each transmitter location within 121 kilometers (75 miles) of any transmitter locations authorized to other licensees or proposed by tentative selectees or other applicants, except those with mutually exclusive applications.

(a) Licensees must cooperate and make reasonable efforts to resolve technical problems that may inhibit effective and efficient use of the cellular radio spectrum; however, licensees are not obligated to suggest extensive changes to or redesign other licensees' cellular systems. Licensees must make reasonable efforts to avoid blocking

47 CFR Ch. I (10–1–10 Edition)

the growth of other cellular systems that are likely to need additional capacity in the future.

(b) If technical problems are addressed by an agreement or operating agreement between the licensees that would result in a reduction of quality or capacity of either system, the licensees must notify the Commission by updating FCC Form 601.

[59 FR 59507, Nov. 17, 1994, as amended at 63 FR 68951, Dec. 14, 1998]

§ 22.909 Cellular markets.

Cellular markets are standard geographic areas used by the FCC for administrative convenience in the licensing of cellular systems. Cellular markets comprise Metropolitan Statistical Areas (MSAs) and Rural Service Areas (RSAs). All cellular markets and the counties they comprise are listed in Public Notice Report No. CL-92-40 "Common Carrier Public Mobile Services Information, Cellular MSA/RSA Markets and Counties", dated January 24, 1992, DA 92-109, 7 FCC Rcd 742 (1992).

(a) *MSAs*. Metropolitan Statistical Areas are 306 areas, including New England County Metropolitan Areas and the Gulf of Mexico Service Area (water area of the Gulf of Mexico, border is the coastline), defined by the Office of Management and Budget, as modified by the FCC.

(b) *RSAs*. Rural Service Areas are 428 areas, other than MSAs, established by the FCC.

§ 22.911 Cellular geographic service area.

The Cellular Geographic Service Area (CGSA) of a cellular system is the geographic area considered by the FCC to be served by the cellular system. The CGSA is the area within which cellular systems are entitled to protection and within which adverse effects for the purpose of determining whether a petitioner has standing are recognized.

(a) *CGSA determination*. The CGSA is the composite of the service areas of all of the cells in the system, excluding any area outside the cellular market boundary, except as provided in paragraph (c) of this section, and excluding any area within the CGSA of another cellular system. The service area of a cell is the area within its service area

boundary (SAB). The distance to the SAB is calculated as a function of effective radiated power (ERP) and antenna center of radiation height above average terrain (HAAT), height above sea level (HASL) or height above mean sea level (HAMSL).

(1) Except as provided in paragraphs (a)(2) and (b) of this section, the distance from a cell transmitting antenna to its SAB along each cardinal radial is calculated as follows:

$$d = 2.531 \times h^{0.34} \times p^{0.17}$$

where:

d is the radial distance in kilometers
h is the radial antenna HAAT in meters
p is the radial ERP in Watts

(2) The distance from a cell transmitting antenna located in the Gulf of Mexico Service Area (GMSA) to its SAB along each cardinal radial is calculated as follows:

$$d = 6.895 \times h^{0.30} \times p^{0.15}$$

Where:

d is the radial distance in kilometers
h is the radial antenna HAAT in meters
p is the radial ERP in Watts

(3) The value used for h in the formula in paragraph (a)(2) of this section must not be less than 8 meters (26 feet) HASL (or HAMSL, as appropriate for the support structure). The value used for h in the formula in paragraph (a)(1) of this section must not be less than 30 meters (98 feet) HAAT, except that for unserved area applications proposing a cell with an ERP not exceeding 10 Watts, the value for h used in the formula in paragraph (a)(1) of this section to determine the service area boundary for that cell may be less than 30 meters (98 feet) HAAT, but not less than 3 meters (10 feet) HAAT.

(4) The value used for p in the formulas in paragraphs (a)(1) and (a)(2) of this section must not be less than 0.1 Watt or 27 dB less than (1/500 of) the maximum ERP in any direction, whichever is more.

(5) Whenever use of the formula in paragraph (a)(1) of this section pursuant to the exception contained in paragraph (a)(3) of this section results in a calculated distance that is less than 5.4 kilometers (3.4 miles), the radial distance to the service area boundary is deemed to be 5.4 kilometers (3.4 miles).

(6) The distance from a cell transmitting antenna to the SAB along any radial other than the eight cardinal radials is calculated by linear interpolation of distance as a function of angle.

(b) *Alternative CGSA determination.* If a carrier believes that the method described in paragraph (a) of this section produces a CGSA that departs significantly ($\pm 20\%$ in the service area of any cell) from the geographic area where reliable cellular service is actually provided, the carrier may submit, as an exhibit to an application for modification of the CGSA using FCC Form 601, a depiction of what the carrier believes the CGSA should be. Such submissions must be accompanied by one or more supporting propagation studies using methods appropriate for the 800–900 MHz frequency range, including all supporting data and calculations, and/or by extensive field strength measurement data. For the purpose of such submissions, cellular service is considered to be provided in all areas, including “dead spots”, between the transmitter location and the locus of points where the predicted or measured median field strength finally drops to 32 dB μ V/m (i.e. does not exceed 32 dB μ V/m further out). If, after consideration of such submissions, the FCC finds that adjustment to a CGSA is warranted, the FCC may grant the application.

(1) The alternative CGSA determination must define the CGSA in terms of distances from the cell sites to the 32 dB μ V/m contour along the eight cardinal radials, with points in other azimuthal directions determined by the method given in paragraph (a)(6) of this section. The distances used for the cardinal radials must be representative of the coverage within the 45° sectors, as depicted by the alternative CGSA determination.

(2) If an uncalibrated predictive model is used to depict the CGSA, the alternative CGSA determination must identify factors (e.g. terrain roughness or features) that could plausibly account for the difference between actual coverage and that defined by the formula in paragraph (a)(1) of this section. If actual measurements or a measurement-calibrated predictive model are used to depict the CGSA, and this fact