- (c) [Reserved]
- (d) Vessels registered for use under a Hawaii longline limited access permit may not have on board at any time during a trip for which notification to NMFS under §665.803(a) indicated that deep-setting would be done any float lines less than 20 meters in length or light sticks. As used in this paragraph "float line" means a line used to suspend the main longline beneath a float and "light stick" means any type of light emitting device, including any fluorescent "glow bead," chemical, or electrically powered light that is affixed underwater to the longline gear.
 - (e) [Reserved]
- (f) Any owner or operator of a vessel registered for use under any longline permit issued under §665.801 must use only circle hooks sized 18/0 or larger, with an offset not to exceed 10 degrees, when shallow-setting north of the Equator (0° lat.). As used in this paragraph, an offset circle hook sized 18/0 or larger is one with an outer diameter at its widest point no smaller than 1.97 inches (50 mm) when measured with the eye of the hook on the vertical axis (y-axis) and perpendicular to the horizontal axis (x-axis). As used in this paragraph, the allowable offset is measured from the barbed end of the hook, and is relative to the parallel plane of the eyed-end, or shank, of the hook when laid on its side.
- (g) Any owner or operator of a vessel registered for use under any longline permit issued under §665.801 must use only mackerel-type bait when shallow-setting north of the Equator (0° lat.). As used in this paragraph, mackerel-type bait means a whole fusiform fish with a predominantly blue, green or gray back and predominantly gray, silver or white lower sides and belly.
- (h) Owners and operators of vessels registered for use under a Hawaii longline limited access permit may make sets only of the type (shallow-setting or deep-setting) indicated in the notification to NMFS pursuant to §665.803(a).
- (i) Vessels registered for use under Hawaii longline limited access permits may not be used to engage in shallowsetting north of the Equator (0° lat.) any time during which the shallow-set component of the longline fishery is

closed pursuant to paragraph (b)(2)(ii) of this section.

(j) Owners and operators of vessels registered for use under a Hawaii longline limited access permit may land or possess no more than 10 swordfish from a fishing trip for which the permit holder notified NMFS under §665.803(a) that the vessel would engage in a deep-setting trip.

§665.814 Protected species workshop.

- (a) Each year, both the owner and the operator of a vessel registered for use under any longline permit issued under §665.801 must attend and be certified for completion of a workshop conducted by NMFS on interaction mitigation techniques for sea turtles, seabirds and other protected species.
- (b) A protected species workshop certificate will be issued by NMFS annually to any person who has completed the workshop.
- (c) An owner of a vessel registered for use under any longline permit issued under §665.801 must have a valid protected species workshop certificate issued by NMFS to the owner of the vessel, in order to maintain or renew their vessel registration.
- (d) An owner and an operator of a vessel registered for use under any longline permit issued under §665.801 must have on board the vessel a valid protected species workshop certificate issued by NMFS to the operator of the vessel, or a legible copy thereof.

§ 665.815 Pelagic longline seabird mitigation measures.

- (a) Seabird mitigation techniques. When deep-setting or shallow-setting north of 23° N. lat. or shallow-setting south of 23° N. lat., owners and operators of vessels registered for use under a Hawaii longline limited access permit, must either side-set according to paragraph (a)(1) of this section, or fish in accordance with paragraph (a)(2) of this section.
- (1) Side-setting. Owners and operators of vessels opting to side-set under this section must fish according to the following specifications:
- (i) The mainline must be deployed as far forward on the vessel as practicable, and at least 1 m (3.3 ft) forward from the stern of the vessel;