

meetings shall be recorded and available at the facility for review by a Minerals Management Service representative.

**§§ 250.607–250.608 [Reserved]**

**§ 250.609 Well-workover structures on fixed platforms.**

Derricks, masts, substructures, and related equipment shall be selected, designed, installed, used, and maintained so as to be adequate for the potential loads and conditions of loading that may be encountered during the operations proposed. Prior to moving a well-workover rig or well-servicing equipment onto a platform, the lessee shall determine the structural capability of the platform to safely support the equipment and proposed operations, taking into consideration the corrosion protection, age of the platform, and previous stresses to the platform.

**§ 250.610 Diesel engine air intakes.**

No later than May 31, 1989, diesel engine air intakes shall be equipped with a device to shut down the diesel engine in the event of runaway. Diesel engines which are continuously attended shall be equipped with either remote operated manual or automatic shutdown devices. Diesel engines which are not continuously attended shall be equipped with automatic shutdown devices.

[53 FR 10690, Apr. 1, 1988, as amended at 54 FR 50616, Dec. 8, 1989. Redesignated at 63 FR 29479, May 29, 1998]

**§ 250.611 Traveling-block safety device.**

After May 31, 1989, all units being used for well-workover operations which have both a traveling block and a crown block shall be equipped with a safety device which is designed to prevent the traveling block from striking the crown block. The device shall be checked for proper operation weekly and after each drill-line slipping operation. The results of the operational check shall be entered in the operations log.

**§ 250.612 Field well-workover rules.**

When geological and engineering information available in a field enables the District Manager to determine specific operating requirements, field well-workover rules may be established on the District Manager's initiative or in response to a request from a lessee. Such rules may modify the specific requirements of this subpart. After field well-workover rules have been established, well-workover operations in the field shall be conducted in accordance with such rules and other requirements of this subpart. Field well-workover rules may be amended or canceled for cause at any time upon the initiative of the District Manager or upon the request of a lessee.

**§ 250.613 Approval and reporting for well-workover operations.**

(a) No well-workover operation except routine ones, as defined in § 250.601 of this part, shall begin until the lessee receives written approval from the District Manager. Approval for these operations must be requested on Form MMS-124, Application for Permit to Modify.

(b) You must submit the following with Form MMS-124:

(1) A brief description of the well-workover procedures to be followed, a statement of the expected surface pressure, and type and weight of workover fluids;

(2) When changes in existing subsurface equipment are proposed, a schematic drawing of the well showing the zone proposed for workover and the workover equipment to be used;

(3) Where the well-workover is in a zone known to contain H<sub>2</sub>S or a zone where the presence of H<sub>2</sub>S is unknown, information pursuant to § 250.490 of this part; and

(4) Payment of the service fee listed in § 250.125.

(c) The following additional information shall be submitted with Form MMS-124 if completing to a new zone is proposed:

(1) Reason for abandonment of present producing zone including supportive well test data, and

(2) A statement of anticipated or known pressure data for the new zone.