

§ 285.709

CVA or project engineer must inform you; and

(2) If you accept the modifications, then you must also inform MMS.

§ 285.709 When conducting onsite fabrication inspections, what must the CVA or project engineer verify?

(a) To comply with § 285.708(a)(3), the CVA or project engineer must make periodic onsite inspections while fabrication is in progress and must verify the following fabrication items, as appropriate:

(1) Quality control by lessee (or grant holder) and builder;

(2) Fabrication site facilities;

(3) Material quality and identification methods;

(4) Fabrication procedures specified in the Fabrication and Installation Report, and adherence to such procedures;

(5) Welder and welding procedure qualification and identification;

(6) Structural tolerances specified, and adherence to those tolerances;

(7) Nondestructive examination requirements and evaluation results of the specified examinations;

(8) Destructive testing requirements and results;

(9) Repair procedures;

(10) Installation of corrosion-protection systems and splash-zone protection;

(11) Erection procedures to ensure that overstressing of structural members does not occur;

(12) Alignment procedures;

(13) Dimensional check of the overall structure, including any turrets, turret-and-hull interfaces, any mooring line and chain and riser tensioning line segments; and

(14) Status of quality-control records at various stages of fabrication.

(b) For any floating facilities, the CVA or project engineer must ensure that any requirements of the U.S. Coast Guard for structural integrity and stability (e.g., verification of center of gravity) have been met. The CVA or project engineer must also consider:

(1) Foundations, foundation pilings and templates, and anchoring systems; and

(2) Mooring or tethering systems.

30 CFR Ch. II (7-1-11 Edition)

§ 285.710 When conducting onsite installation inspections, what must the CVA or project engineer do?

To comply with § 285.708(a)(4), the CVA or project engineer must make periodic onsite inspections while installation is in progress and must, as appropriate, verify, witness, survey, or check, the installation items required by this section.

(a) The CVA or project engineer must verify, as appropriate, all of the following:

(1) Loadout and initial flotation procedures;

(2) Towing operation procedures to the specified location, and review the towing records;

(3) Launching and uprighting activities;

(4) Submergence activities;

(5) Pile or anchor installations;

(6) Installation of mooring and tethering systems;

(7) Final deck and component installations; and

(8) Installation at the approved location according to the Facility Design Report and the Fabrication and Installation Report.

(b) For a fixed or floating facility, the CVA or project engineer must verify that proper procedures were used during the following:

(1) The loadout of the jacket, decks, piles, or structures from each fabrication site; and

(2) The actual installation of the facility or major modification and the related installation activities.

(c) For a floating facility, the CVA or project engineer must verify that proper procedures were used during the following:

(1) The loadout of the facility;

(2) The installation of foundation pilings and templates, and anchoring systems; and

(3) The installation of the mooring and tethering systems.

(d) The CVA or project engineer must conduct an onsite survey of the facility after transportation to the approved location.

(e) The CVA or project engineer must spot-check the equipment, procedures,