

Environmental Protection Agency

Pt. 63, Subpt. II, App. A

**APPENDIX A TO SUBPART II OF PART 63—
VOC DATA SHEET¹**

*Properties of the Coating “As Supplied” by the
Manufacturer²*

Coating Manufacturer: _____
Coating Identification: _____
Batch Identification: _____
Supplied To: _____

Properties of the coating as supplied¹ to
the customer:

- A. Coating Density: (D_c)_s _____ g/L
[] ASTM D1475-90* [] Other³
B. Total Volatiles: (m_v)_s _____ Mass Percent
[] ASTM D2369-93 or 95* [] Other³

- C. Water Content: 1. (m_w)_s _____ Mass Percent
[] ASTM D3792-91* [] ASTM D4017-81,
90, or 96a* [] Other³
2. (v_w)_s _____ Volume Percent
[] Calculated [] Other³
D. Organic Volatiles: (m_o)_s _____ Mass Percent
E. Nonvolatiles: (v_n)_s _____ Volume Percent
[] Calculated [] Other³
F. VOC Content (VOC)_s:
1. _____ g/L solids (nonvolatiles)
2. _____ g/L coating (less water and exempt
compounds)
G. Thinner Density: D_m _____ g/L
ASTM _____ [] Other³

Remarks: (use reverse side)

Signed: _____ Date: _____

[60 FR 64336, Dec. 15, 1995, as amended at 65
FR 62216, Oct. 17, 2000]

¹Adapted from EPA-340/1-86-016 (July 1986),
p. II-2.

²The subscript “s” denotes each value is
for the coating “as supplied” by the manu-
facturer.

*Incorporation by reference—see §63.14.

³Explain the other method used under
“Remarks.”