### § 63.7902

months that each container is vaportight according to the procedures in §63.925(a) and have records documenting the test results.

- (e) You must demonstrate initial compliance of each container determined under paragraph (b) of this section to require Container Level 3 controls if you have submitted as part of your notification of compliance status, specified in §63.7950, a signed statement that you have met the requirements in paragraphs (e)(1) and (2) of this section.
- (1) For each permanent total enclosure you use to comply with §63.7900, you have performed the verification procedure according to the requirements in §63.924(c)(1), and prepare records of the supporting calculations and measurements.
- (2) You have met each applicable requirement for demonstrating initial compliance with the emission limitations and work practice standards for a closed vent system and control device in §63.7926.

## §63.7902 What are my inspection and monitoring requirements for containers?

- (a) You must inspect each container using Container Level 1 or Container Level 2 controls according to the requirements in §63.926(a).
- (b) If you use Container Level 3 controls, you must meet requirements in paragraphs (b)(1) and (2) of this section, as applicable to your site remediation.
- (1) You must perform the verification procedure for each permanent total enclosure annually according to the requirements in §63.924(c)(1).
- (2) You must monitor and inspect each closed vent system and control device according to the requirements in §63.7927 that apply to you.

# §63.7903 How do I demonstrate continuous compliance with the emissions limitations and work practice standards for containers?

- (a) You must demonstrate continuous compliance with the emissions limitations and work practice standards in §63.7990 applicable to your affected containers by meeting the requirements in paragraphs (b) through (e) of this section.
- (b) You must demonstrate continuous compliance with the requirement

to determine the applicable container control level specified in §63.7990(b) for each affected tank by meeting the requirements in paragraphs (b)(1) through (3) of this section.

- (1) Keeping records of the quantity and design capacity for each type of container used for your site remediation and subject to §63.7886(b)(1)(ii).
- (2) For containers subject to  $\S63.7886(b)(1)(ii)$  with a design capacity greater than  $0.46~m^3$  and not using Container Level 2 or Container Level 3 controls, meeting the requirements in paragraphs (b)(2)(i) and (ii) of this section.
- (i) Keeping records of the maximum vapor pressure or total organic concentration for the remediation material placed in the containers, as applicable to the conditions in §63.7900(b)(3)(i) or (ii) for which your containers qualify to use Container Level 1 controls.
- (ii) Performing a new determination whenever changes to the remediation material placed in the containers could potentially cause the maximum vapor pressure or total organic concentration to increase to a level that is equal to or greater than the conditions specified in §63.7900(b)(3)(i) or (ii), as applicable to your containers. You must keep records of each determination.
- (3) Keeping records to document compliance with the requirements according to the requirements in §63.7952.
- (c) You must demonstrate continuous compliance for each container determined to require Container Level 1 controls by meeting the requirements in paragraphs (c)(1) through (5) of this section.
- (1) Operating and maintaining covers for each container according to the requirements in  $\S 63.922(d)$ .
- (2) Inspecting each container annually according to the requirements in \$63.926(a)(2).
- (3) Emptying or repairing each container according to the requirements in §63.926(a)(3).
- (4) Keeping records of an inspection that includes the information in paragraphs (a)(4)(i) and (ii) of this section.
  - (i) Date of each inspection; and
- (ii) If a defect is detected during an inspection, the location of the defect, a description of the defect, the date of

### **Environmental Protection Agency**

detection, the corrective action taken to repair the defect, and if repair is delayed, the reason for any delay and the date completion of the repair is expected.

- (5) Keeping records to document compliance with the requirements according to the requirements in §63.7952.
- (d) You must demonstrate continuous compliance for each container determined to require Container Level 2 controls by meeting the requirements in paragraphs (d)(1) through (6) of this section.
- (1) Transferring remediation material in and out of the container according to the requirements in §63.923(c).
- (2) Operating and maintaining container covers according to the requirements in §63.923(d).
- (3) Inspecting each container annually according to the requirements in  $\S 63.926(a)(2)$ .
- (4) Emptying or repairing containers according to the requirements in §63.926(a)(3).
- (5) Keeping records of each inspection that include the information in paragraphs (d)(5)(i) and (ii) of this section.
  - (i) Date of each inspection; and
- (ii) If a defect is detected during an inspection, the location of the defect, a description of the defect, the date of detection, the corrective action taken to repair the defect, and if repair is delayed, the reason for any delay and the date completion of the repair is expected.
- (6) Keeping records to document compliance with the requirements of this subpart according to the requirements in §63.7952.
- (e) You must demonstrate continuous compliance for each container determined to require Container Level 3 controls by meeting the requirements in paragraphs (e)(1) through (4) of this section.
- (1) Performing the verification procedure for the enclosure annually according to the requirements in §63.685(i).
- (2) Recording the information specified in §63.696(f).
- (3) Meeting each applicable requirement for demonstrating continuous compliance with the emissions limitations and work practice standards for a closed vent system and control device in §63.7928.

(4) Keeping records to document compliance with the requirements of this subpart according to the requirements in §63.7952.

#### SUBFACE IMPOUNDMENTS

#### § 63.7905 What emissions limitations or work practice standards must I meet for surface impoundments?

- (a) You must control HAP emissions from each new and existing surface impoundment subject to §63.7886(b)(1)(iii) according to emissions limitations and work practice standards in this section that apply to your affected surface impoundments.
- (b) For each affected surface impoundment, you must install and operate air pollution controls that meet either of the options in paragraphs (b)(1) or (2) of this section.
- (1) Install and operate a floating membrane cover according to the requirements in §63.942; or
- (2) Install and operate a cover vented through a closed vent system to a control device according to the requirements in §63.943. You must meet the emissions limitations and work practice standards in §63.7925 that apply to your closed vent system and control device.
- (c) As provided in §63.6(g), you may request approval from the EPA to use an alternative to the work practice standards in this section that apply to your surface impoundments. If you request for permission to use an alternative to the work practice standards, you must submit the information described in §63.6(g)(2).

# § 63.7906 How do I demonstrate initial compliance with the emissions limitations or work practice standards for surface impoundments?

- (a) You must demonstrate initial compliance with the emissions limitations and work practice standards in §63.7905 that apply to your affected surface impoundments by meeting the requirements in paragraphs (b) and (c) of this section, as applicable to your surface impoundments.
- (b) You must demonstrate initial compliance of each surface impoundment using a floating membrane cover according to §63.7905(b)(1) if you have submitted as part of your notification