

standard conditions for temperature and pressure (0 °C and 101.3 kPa), and these conditions must be used consistently throughout all calculations.

(b) *Engine test conditions.* Measure the absolute temperature (designated as *T* and expressed in Kelvin) of the engine air at the inlet to the engine, and the dry atmospheric pressure (designated as *p* and expressed in kPa), and determine the parameter *f* according to the following provisions:

(1) Naturally aspirated and mechanically supercharged engines:

$$f = \frac{99}{p_s} \times \left( \frac{T}{298} \right)^{0.7}$$

(2) Turbocharged engine with or without cooling of inlet air:

$$f = \left( \frac{99}{p_s} \right)^{0.7} \times \left( \frac{T}{298} \right)^{1.5}$$

(c) For a test to be recognized as valid, the parameter *f* shall be between the limits as shown below:

$$0.98 < f < 1.02$$

[59 FR 31335, June 17, 1994. Redesignated at 63 FR 56995, Oct. 23, 1998]

APPENDIX A TO SUBPART D OF PART 89—  
TABLES

TABLE 1—ABBREVIATIONS USED IN SUBPART D

CLD .....	Chemiluminescent detector.
CO .....	Carbon monoxide.
CO <sub>2</sub> .....	Carbon dioxide.
HC .....	Hydrocarbons.
HCLD .....	Heated chemiluminescent detector.
HFID .....	Heated flame ionization detector.
GC .....	Gas chromatograph.
NDIR .....	Non-dispersive infra-red analyzer.
NIST .....	National Institute for Standards and Testing.
NO .....	Nitric Oxide.
NO <sub>2</sub> .....	Nitrogen Dioxide.
NO <sub>x</sub> .....	Oxides of nitrogen.
O <sub>2</sub> .....	Oxygen.

TABLE 2—SYMBOLS USED IN SUBPARTS D AND E

Symbol	Term	Unit
conc .....	Concentration (ppm by volume) .....	ppm
f .....	Engine specific parameter considering atmospheric conditions .....	
F <sub>FCH</sub> .....	Fuel specific factor for the carbon balance calculation .....	
F <sub>FD</sub> .....	Fuel specific factor for exhaust flow calculation on dry basis .....	
F <sub>FH</sub> .....	Fuel specific factor representing the hydrogen to carbon ratio .....	
F <sub>FW</sub> .....	Fuel specific factor for exhaust flow calculation on wet basis .....	
FR .....	Rate of fuel consumed .....	g/h
G <sub>AIRW</sub> .....	Intake air mass flow rate on wet basis .....	kg/h
G <sub>AIRD</sub> .....	Intake air mass flow rate on dry basis .....	kg/h
G <sub>EXHW</sub> .....	Exhaust gas mass flow rate on wet basis .....	kg/h
G <sub>FUEL</sub> .....	Fuel mass flow rate .....	kg/h
H .....	Absolute humidity (water content related to dry air) .....	g/kg
i .....	Subscript denoting an individual mode .....	
K <sub>H</sub> .....	Humidity correction factor .....	
L .....	Percent torque related to maximum torque for the test mode .....	%
mass .....	Pollutant mass flow .....	g/h
n <sub>q,i</sub> .....	Engine speed (average at the i'th mode during the cycle) .....	1/min
P <sub>s</sub> .....	Dry atmospheric pressure .....	kPa
P <sub>a</sub> .....	Test ambient saturation vapor pressure at ambient temperature .....	kPa
P .....	Observed brake power output uncorrected .....	kW
P <sub>AUX</sub> .....	Declared total power absorbed by auxiliaries fitted for the test .....	kW
P <sub>M</sub> .....	Maximum power measured at the test speed under test conditions .....	kW
P <sub>i</sub> .....	P <sub>i</sub> = P <sub>M,i</sub> + P <sub>AUX,i</sub> .....	
P <sub>B</sub> .....	Total barometric pressure (average of the pre-test and post-test values) .....	kPa
P <sub>v</sub> .....	Saturation pressure at dew point temperature .....	kPa
R <sub>a</sub> .....	Relative humidity of the ambient air .....	%
S .....	Dynamometer setting .....	kW
T .....	Absolute temperature at air inlet .....	K
T <sub>he</sub> .....	Air temperature after the charge air cooler (if applicable) (average) .....	K
T <sub>clout</sub> .....	Coolant temperature outlet (average) .....	K
T <sub>bd</sub> .....	Absolute dewpoint temperature .....	K
T <sub>d,i</sub> .....	Torque (average at the i'th mode during the cycle) .....	N-m
T <sub>SC</sub> .....	Temperature of the intercooled air .....	K
T <sub>ref</sub> .....	Reference temperature .....	K
V <sub>EXHD</sub> .....	Exhaust gas volume flow rate on dry basis .....	m <sup>3</sup> /h
V <sub>AIRW</sub> .....	Intake air volume flow rate on wet basis .....	m <sup>3</sup> /h
P <sub>B</sub> .....	Total barometric pressure .....	kPa
V <sub>EXHW</sub> .....	Exhaust gas volume flow rate on wet basis .....	m <sup>3</sup> /h
WF .....	Weighing factor .....	

TABLE 2—SYMBOLS USED IN SUBPARTS D AND E—Continued

Symbol	Term	Unit
WF <sub>E</sub> .....	Effective weighing factor	

TABLE 3—MEASUREMENT ACCURACY AND CALIBRATION FREQUENCY

No.	Item	Calibration accuracy <sup>1</sup>	Calibration frequency
1	Engine speed .....	±2% .....	30 days.
2	Torque .....	Larger of ±2% of point or ±1% of engine maximum.	30 days.
3	Fuel consumption (raw measurement) .....	±2% of engine maximum .....	30 days.
4	Air consumption (raw measurement) .....	±2% of engine maximum .....	As required.
5	Coolant temperature .....	±2°K .....	As required.
6	Lubricant temperature .....	±2°K .....	As required.
7	Exhaust backpressure .....	±1.0% of engine maximum ...	As required.
8	Inlet depression .....	1.0% of engine maximum .....	As required.
9	Exhaust gas temperature .....	±15°K .....	As required.
10	Air inlet temperature (combustion air) .....	±2°K .....	As required.
11	Atmospheric pressure .....	±0.5% .....	As required.
12	Humidity (combustion air) (g of H <sub>2</sub> O/Kg of dry air) .....	±0.5 .....	As required.
13	Fuel temperature .....	±2°K .....	As required.
14	Temperature with regard to dilution tunnel .....	±2°K .....	As required.
15	Dilution air humidity (g of H <sub>2</sub> O/Kg of dry air) .....	±0.5 .....	As required.
16	HC analyzer .....	±2% .....	Monthly or as required.
17	CO analyzer .....	±2% .....	Once per 60 days or as re- quired.
18	NO <sub>x</sub> analyzer .....	±2% .....	Monthly or as required.
19	Methane analyzer .....	±2% .....	Monthly or as required.
20	NO <sub>x</sub> converter efficiency check .....	90% .....	Monthly.
21	CO <sub>2</sub> analyzer .....	±2% .....	Once per 60 days or as re- quired.

<sup>1</sup> All accuracy requirements pertain to the final recorded value which is inclusive of the data acquisition system.

TABLE 4—FEDERAL TEST FUEL SPECIFICATIONS

Item	Procedure (ASTM) <sup>1</sup>	Value (type 2-D)
Cetane .....	D613-95 .....	40-48
Distillation Range:		
IBP, °C .....	D86-97 .....	171-204
10% point, °C .....	86-97 .....	204-238
50% point, °C .....	86-97 .....	243-282
90% point, °C .....	86-97 .....	293-332
EP, °C .....	86-97 .....	321-366
Gravity, API .....	D287-92 .....	32-37
Total Sulfur, %mass .....	D129-95 or D2622-98 .....	0.03-0.40
Hydrocarbon composition:		
Aromatics, %vol .....	D1319-98 or D5186-96 .....	<sup>2</sup> 10
Paraffins, Naphthenes, Olefins .....	D1319-98 .....	( <sup>3</sup> )
Flashpoint, °C (minimum) .....	D93-97 .....	54
Viscosity @ 38°C, Centistokes .....	D445-97 .....	2.0-3.2

<sup>1</sup> All ASTM procedures in this table have been incorporated by reference. See § 89.6.

<sup>2</sup> Minimum.  
<sup>3</sup> Remainder.