### **Environmental Protection Agency**

WATER JET WEAVING—Continued

Pollutant or pollutant property	BPT limitations	
	Maximum for any 1 day	Average of daily values for 30 con- secutive days
COD	21.3	13.7
TSS	5.5	2.5
ph	(1)	(1)

<sup>1</sup> Within the range 6.0 to 9.0 at all times.

### §410.33 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT):

**GENERAL PROCESSING** 

	BAT limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
COD	2.8	1.4

WATER JET WEAVING

	BAT limitations	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
COD	21.3	13.7

# §410.34 Pretreatment standards for existing sources (PSES).

Any existing source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

### §410.40

## § 410.35 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

GENERAL PROCESSING

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
BOD5	1.4	0.7
COD	2.8	1.4
TSS	1.4	0.7
pH	(1)	(1)

<sup>1</sup> Within the range 6.0 to 9.0 at all times.

WATER JET WEAVING

	NSPS	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
BOD5	8.9	4.6
COD	21.3	13.7
TSS	5.5	2.5
рН	(1)	(1)

<sup>1</sup> Within the range 6.0 to 9.0 at all times.

### §410.36 Pretreatment standards for new sources (PSNS).

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

§410.37 Effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

### Subpart D—Woven Fabric Finishing Subcategory

### § 410.40 Applicability; description of the woven fabric finishing subcategory.

The provisions of this subpart are applicable to process wastewater discharges resulting from the following