

§ 415.423

SUBPART AP—HYDROGEN CYANIDE

Pollutant or pollutant property	BPT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
TSS	8.6	3.2
Cyanide A	0.10	0.021
Total Cyanide	0.65	0.23
pH	(¹)	(¹)

¹ Within the range 6.0 to 10.5.

§ 415.423 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT):

SUBPART AP—HYDROGEN CYANIDE

Pollutant or pollutant property	BAT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
Cyanide A	0.10	0.021
Total Cyanide	0.65	0.23
Total Residual Chlorine	0.086	0.051

§ 415.424 [Reserved]

§ 415.425 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

SUBPART AP—HYDROGEN CYANIDE

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
TSS	8.6	3.2
Cyanide A	0.10	0.021

40 CFR Ch. I (7-1-09 Edition)

SUBPART AP—HYDROGEN CYANIDE—Continued

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
Total Cyanide	0.65	0.23
Total Residual Chlorine	0.086	0.051
Ph	(¹)	(¹)

¹ Within the range 6.0 to 10.5.

§ 415.426 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following Pretreatment Standards for New Sources (PSNS):

SUBPART AP—HYDROGEN CYANIDE

Pollutant or pollutant property	PSNS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Milligrams per liter	
Cyanide A	1.7	0.36
Total Cyanide	11	4.0

In cases where POTWs find it necessary to impose mass limitations, the following equivalent mass limitations are provided as an alternate: The limitations for Cyanide A and Total Cyanide are the same as specified in § 415.425.

[47 FR 55227, Dec. 8, 1982]

§ 415.427 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations are the same for TSS and pH as specified in § 415.422.