

**Environmental Protection Agency**

**§ 420.136**

the best practicable control technology currently available (BPT):

(a) *Direct-reduced iron.*

**SUBPART M—EFFLUENT LIMITATIONS (BPT)**

Pollutant	Maximum daily <sup>1</sup>	Maximum monthly avg. <sup>1</sup>
TSS .....	0.00998	0.00465
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> Pounds per thousand pound of product.  
<sup>2</sup> Within the range of 6.0 to 9.0.

(b) *Forging operations.*

**SUBPART M—EFFLUENT LIMITATIONS (BPT)**

Pollutant	Maximum daily <sup>1</sup>	Maximum monthly avg. <sup>1</sup>
O&G (as HEM) .....	0.00746	0.00446
TSS .....	0.0123	0.00508
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> Pounds per thousand pound of product.  
<sup>2</sup> Within the range of 6.0 to 9.0.

(c) *Briquetting.* There shall be no discharge of process wastewater pollutants to waters of the U.S.

**§ 420.133 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available control technology economically achievable (BAT):

(a) *Direct-reduced iron.* [Reserved]

(b) *Forging operations.* [Reserved]

(c) *Briquetting.* There shall be no discharge of process wastewater pollutants.

**§ 420.134 New source performance standards (NSPS).**

New sources subject to this subpart must achieve the following new source performance standards (NSPS), as applicable.

(a) *Direct-reduced iron.*

**SUBPART M—NEW SOURCE PERFORMANCE STANDARDS (NSPS)**

Pollutant	Maximum daily <sup>1</sup>	Maximum monthly avg. <sup>1</sup>
TSS .....	0.00998	0.00465
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> Pounds per thousand pound of product.  
<sup>2</sup> Within the range of 6.0 to 9.0.

(b) *Forging operations.*

**SUBPART M—NEW SOURCE PERFORMANCE STANDARDS (NSPS)**

Pollutant	Maximum daily <sup>1</sup>	Maximum monthly avg. <sup>1</sup>
O&G (as HEM) .....	0.00746	0.00446
TSS .....	0.0123	0.00508
pH .....	( <sup>2</sup> )	( <sup>2</sup> )

<sup>1</sup> Pounds per thousand pound of product.  
<sup>2</sup> Within the range of 6.0 to 9.0.

(c) *Briquetting.* There shall be no discharge of process wastewater pollutants to waters of the U.S.

**§ 420.135 Pretreatment standards for existing sources (PSES).**

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart that introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and must achieve the following pretreatment standards for existing sources (PSES):

(a) *Direct-reduced iron.* [Reserved]

(b) *Forging operations.* [Reserved]

(c) *Briquetting.* There shall be no discharge of process wastewater pollutants to POTWs.

**§ 420.136 Pretreatment standards for new sources (PSNS).**

Except as provided in 40 CFR 403.7, any new source subject to this subpart that introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and must achieve the following pretreatment standards for new sources (PSNS):

(a) *Direct-reduced iron.* [Reserved]

(b) *Forging operations.* [Reserved]

(c) *Briquetting.* There shall be no discharge of process wastewater pollutants to POTWs.