## § 420.85

# 40 CFR Ch. I (7-1-09 Edition)

## SUBPART H

	New source ance sta	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS Cyanide Chromium Nickel pH	0.0949 0.00102 0.00136 0.00122	0.0407 0.000339 0.000542 0.000407 (1)

<sup>&</sup>lt;sup>1</sup> Within the range of 6.0 to 9.0.

## (2) Continuous.

#### SUBPART H

	New source perform- ance standards	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS Cyanide Chromium Nickel	0.532 0.00569 0.00759 0.00683	0.228 0.00190 0.00304 0.00228

<sup>&</sup>lt;sup>1</sup> Within the range of 6.0 to 9.0.

# $\$\,420.85$ Pretreatment standards for existing sources (PSES).

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources.

(a) Salt bath descaling, oxidizing—(1) Batch, sheet and plate.

#### SUBPART H

	Pretreatment standards for existing sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
Chromium	0.00292 0.00263	0.00117 0.000876

(2) Batch, rod and wire.

## SUBPART H

	Pretreatment standards for existing sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
ChromiumNickel	0.00175 0.00158	0.000701 0.000526

 $(3) \ Batch, \ pipe \ and \ tube.$ 

## SUBPART H

CODI AUTI TI		
	Pretreatment standard for existing sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
Chromium	0.00709 0.00638	0.00284 0.00213

## (4) Continuous.

## SUBPART H

	Pretreatment standards for existing sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
Chromium	0.00138 0.00124	0.000551 0.000413

(b) Salt bath descaling, reducing—(1) Batch.

# SUBPART H

	Pretreatmen for existing	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
Cyanide	0.00102 0.00136 0.00122	0.000339 0.000542 0.000407

## **Environmental Protection Agency**

## (2) Continuous.

## SUBPART H

	Pretreatment standards for existing sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product)	
Cyanide	0.00569 0.00759 0.00683	0.00190 0.00304 0.00228

 $[47~\mathrm{FR}~23284,~\mathrm{May}~27,~1982;~47~\mathrm{FR}~41739,~\mathrm{Sept}.~22,~1982]$ 

# § 420.86 Pretreatment standards for new sources (PSNS).

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources.

(a) Salt bath descaling, oxidizing—(1) Batch, sheet and plate.

#### SUBPART H

	Pretreatment standards for new sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
Chromium	0.00292 0.00263	0.00117 0.000876

 $(2) \ Batch, \ rod \ and \ wire.$ 

## SUBPART H

	Pretreatment standards for new sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
Chromium	0.00175 0.00158	0.000701 0.000526

(3) Batch, pipe and tube.

## SUBPART H

	Pretreatment standard for new sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
Chromium	0.00709 0.00638	0.00284 0.00213

## (4) Continuous.

## SUBPART H

	Pretreatment standards for new sources	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily val- ues for 30 consecu- tive days
	Kg/kkg (pounds per 1,000 lb) of product	
Chromium	0.00138 0.00124	0.000551 0.000413

(b) Salt bath descaling, reducing—(1) Batch.

#### SUBPART H

	Pretreatme ards for ne	
Pollutant or pollutant property	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
Cyanide	0.00102 0.00136 0.00122	0.000339 0.000542 0.000407

## $(2)\ Continuous.$

## SUBPART H

Pollutant or pollutant property	Pretreatment stand- ards for new sources	
	Maximum for any 1 day	Average of daily values for 30 con- secutive days
	Kg/kkg (pounds per 1,000 lb) of product	
yanide	0.00569 0.00759	0.00190 0.00304