#### 40 CFR Ch. I (7-1-09 Edition)

#### §421.186

sources. The mass of wastewater pollutants in primary and secondary germanium and gallium process wastewater introduced into a POTW must not exceed the following values:

#### (a) Still liquor.

### PSES FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Maximum for any 1 day	Maximum for monthly average
	ds per million f germanium
131.70 26.46 91.98	58.59 12.60 38.43 1.254.00
	for any 1 day mg/kg (pound pounds) o chlorinated 131.70 26.46

# (b) Chlorinator wet air pollution control.

# PSES FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million f germanium
Arsenic	27.530	12.250
Lead	5.531	2.634
Zinc	19.230	8.034
Fluoride	461.000	262.100

#### (c) Germanium hydrolysis filtrate.

# PSES FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million f germanium
Arsenic	39.440	17.550
Lead	7.925	3.774
Zinc	27.550	11.510
Fluoride	660.500	375.500

#### (d) Acid wash and rinse water.

# PSES FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million f germanium
Arsenic	325.50 65.40	144.80 31.14
Zinc	227.40	94.99
Fluoride	5,450.00	3,099.00

#### (e) Gallium hydrolysis filtrate.

# PSES FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million of gallium
Arsenic	70.450 14.160 49.220 1,180.000	31.350 6.742 20.560 670.800

#### (f) Solvent extraction raffinate.

# PSES FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

	aximum r any 1 day	Maximum for monthly average
po	ounds) of uced by s	ds per million gallium pro- colvent extrac-
enicdd	39.330 7.904 27.480 658.700	17.500 3.764 11.480 374.500
tic	39.33 7.90 27.48	30 04 80

## § 421.186 Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources. The mass of wastewater pollutants in primary and secondary germanium and gallium process wastewater introduced into a POTW shall not exceed the following values:

(a) Still Liquor.

#### **Environmental Protection Agency**

### PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds of chlorinated	
Arsenic Lead Zinc Fluoride	131.70 26.46 91.98 2,205.00	58.59 12.60 38.43 1,254.00

# (b) Chlorinator Wet Air Pollution Control.

# PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds of chlorinated	
Arsenic	27.530 5.531 19.230 461.000	12.250 2.634 8.034 262.100

### (c) Germanium Hydrolysis Filtrate.

# PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds of hydrolyzed	
ArsenicLeadZincFluoride	39.440 7.925 27.550 660.500	17.550 3.774 11.510 375.500

#### (d) Acid Wash and Rinse Water.

## PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds of washed	ds per/million f germanium
Arsenic	325.50	144.80
Lead	65.40	31.14
Zinc	227.40	94.99
Fluoride	5,450.00	3,099.00

(e) Gallium Hydrolysis Filtrate.

### PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million ium hydrolyzed
Arsenic Lead Zinc Fluoride	70.450 14.160 49.220 1,180.000	31.350 6.742 20.560 670.800

#### (f) Solvent Extraction Raffinate.

# PSNS FOR THE PRIMARY AND SECONDARY GERMANIUM AND GALLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		s per million gallium pro- vent extraction
ArsenicLeadZincFluoride	39.330 7.904 27.480 658.700	17.500 3.764 11.480 374.500

#### §421.187 [Reserved]

### Subpart Q—Secondary Indium Subcategory

Source: 50 FR 38353, Sept. 20, 1985, unless otherwise noted.

### § 421.190 Applicability: Description of the secondary indium subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of indium at secondary indium facilities processing spent electrolyte solutions and scrap indium metal raw materials.

#### § 421.191 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

#### §§ 421.192-421.193 [Reserved]

# § 421.194 Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Displacement Supernatant.