§421.217

PSNS FOR THE PRIMARY MOLYBDENUM AND RHENIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of molybdenum sulfide roasted	
Arsenic	0.995 0.201 0.394 0.587 [Reserved] 95.440 25.060	0.444 0.093 0.265 0.265 [Reserved]. 41.960 14.250

[50 FR 38355, Sept. 20, 1985, as amended at 55 FR 31702, 31703, Aug. 3, 1990]

§421.217 [Reserved]

Subpart T—Secondary Molybdenum and Vanadium Subcategory

Source: $50 \ \mathrm{FR} \ 38357$, Sept. $20, \ 1985$, unless otherwise noted.

§ 421.220 Applicability: Description of the secondary molybdenum and vanadium subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of molybdenum or vanadium by secondary molybdenum and vanadium facilities.

§ 421.221 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§ 421.222 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

(a) Leach tailings.

BPT LIMITATIONS FOR THE SECONDARY MOLYBDENUM AND VANADIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of technica grade molybdenum plus vanadium plus pure grade molybdenum pro- duced	
Arsenic	40.778	18.145
Chromium	8.585	3.512
Lead	8.195	3.902
Nickel	37.460	24.779
Iron	23.410	11.902
Molybdenum	[Reserved]	[Reserved]
Ammonia (as N)	8078.000	3551.000
Total Suspended Solids	799.950	380.460
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Molybdenum filtrate solvent extraction raffinate.

BPT LIMITATIONS FOR THE SECONDARY MOLYBDENUM AND VANADIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of technica grade molybdenum plus vanadium plus pure grade molybdenum pro- duced	
Arsenic	121.720	54.162
Chromium	25.625	10.483
Lead	24.460	11.648
Nickel	111.819	73.964
Iron	69.887	35.526
Molybdenum	[Reserved]	[Reserved]
Ammonia (as N)	24114.000	10600.000
Total Suspended Solids	2387.800	1135.660
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

(c) Vanadium decomposition wet air pollution control.

BPT LIMITATIONS FOR THE SECONDARY MOLYBDENUM AND VANADIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of vanadium produced by decomposi- tion	
Arsenic	0.000	0.000
Chromium	0.000	0.000
Lead	0.000	0.000
Nickel	0.000	0.000
Iron	0.000	0.000
Molybdenum	0.000	0.000

Environmental Protection Agency

BPT LIMITATIONS FOR THE SECONDARY MOLYB-DENUM AND VANADIUM SUBCATEGORY—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Ammonia (as N)	0.000	0.000
Total suspended solids	0.000	0.000
pH	(1)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(d) Molybdenum drying wet air pollution control.

BPT LIMITATIONS FOR THE SECONDARY MOLYBDENUM AND VANADIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of molybdenum produced	
Arsenic	0.000 0.000 0.000 0.000 0.000 0.000 0.000	0.000 0.000 0.000 0.000 0.000 0.000 0.000

¹ Within the range of 7.5 to 10.0 at all times.

BPT LIMITATIONS FOR THE SECONDARY MOLYBDENUM AND VANADIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of pure molyb- denum produced	
Arsenic Chromium Lead Nickel Iron Molybdenum Ammonia (as N) Total Suspended Solids	48.655 10.243 9.778 44.698 27.936 [Reserved] 9638.000 954.480	21.650 4.190 4.656 29.566 14.201 [Reserved] 4237.000 453.960
pH	(1)	(1)

¹ Within the range of 7.5 to 10.0 at all times.

[50 FR 38357, Sept. 20, 1985, as amended at 55 FR 31703, Aug. 3, 1990]

§ 421.223 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Leach Tailings.

BAT LIMITATIONS FOR THE SECONDARY
MOLYBDENUM AND VANADIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of technical grade molybdenum plus vanadium plus pure grade molybdenum pro- duced	
Arsenic	27.120	12.097
Chromium	7.219	2.927
Lead	5.463	2.536
Nickel	10.731	7.219
Iron	23.413	11.902
Molybdenum	[Reserved]	[Reserved]
Ammonia (as N)	8078.000	3551.000

(b) Molybdenum filtrate solvent extraction raffinate.

BAT LIMITATIONS FOR THE SECONDARY MOLYBDENUM AND VANADIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of technical grade molybdenum plus vanadium plus pure grade molybdenum pro- duced	
Avania	80.952	20.100
Arsenic		36.108
Chronium	21.548	8.736
Lead	16.306	7.571
Nickel	32.031	21.548
Iron	69.887	35.526
Molybdenum	[Reserved]	[Reserved]
Ammonia (as N)	24114.000	10600.000

(c) Vanadium decomposition wet air pollution control.

⁽e) Pure Grade Molybdenum.