Environmental Protection Agency

PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average	
	kg/1,000 kkg (pounds per mil- lion pounds) of metal poured		
Copper (T)	0.304	0.166	
Lead (T)	0.209	0.103	
Zinc (T)	0.3	0.114	
TTO	0.821	0.268	
Oil and grease for alternate			
monitoring)	11.8	3.94	

§ 464.46 Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources.

(a) Casting Quench Operations.

PSNS

Maximum for any 1 day	Maximum for monthly average	
kg/1,000 kkg (pounds per mil- lion pounds) of metal poured		
0.0344 0.0237	0.0187 0.0116	
0.093	0.0129 0.0304 0.446	
	kg/1,000 kkg (plion pound poured 0.0344 0.0237 0.0339	

(b) Die Casting Operations.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	kg/1,000 kkg (pounds per million pounds) of metal poured	
Copper (T)	0.0066 0.0046 0.0066 0.0074 0.0196	0.0036 0.0022 0.0025 0.0026 0.0064
Oil and grease (for alternate monitoring)	0.0196	0.0064

 $\hbox{ (c)} \ \ \textit{Melting} \ \ \textit{Furnace} \ \ \textit{Scrubber} \ \ \textit{Operations}.$

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	kg/62.3 million per billion scrubbed	Sm³ (pounds SCF) of air
Copper (T)	1.56 1.07 1.54 1.74 3.95	0.852 0.527 0.588 0.608 1.29
monitoring)	60.8	20.3

(d) Mold Cooling Operations.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	kg/1,000 kkg (pounds per mil- lion pounds) of metal poured	
Copper (T) Lead (T)	0.304 0.209	0.166 0.103
Zinc (T)	0.203	0.103
TTO \	0.821	0.268
Oil and grease (for alternate		
monitoring)	11.8	3.94

 $[50~\mathrm{FR}~45247,~\mathrm{Oct.}~30,~1985;~51~\mathrm{FR}~21762,~\mathrm{June}~16,~1986]$

§ 464.47 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology. [Reserved]

PART 465—COIL COATING POINT SOURCE CATEGORY

GENERAL PROVISIONS

Sec.

465.01 Applicability.

465.02 General definitions.

465.03 Monitoring and reporting requirements.

465.04 Compliance date for PSES.

Subpart A—Steel Basis Material Subcategory

- 465.10 Applicability; description of the steel basis material subcategory.
- 465.11 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 465.12 Effluent limitations representing the degree of effluent reduction attainable