§ 503.25

methane gas during the period that the sewage sludge unit is active.

- (2) When a final cover is placed on a sewage sludge unit at closure, the concentration of methane gas in air in any structure within the surface disposal site shall not exceed 25 percent of the lower explosive limit for methane gas for three years after the sewage sludge unit closes and the concentration of methane gas in air at the property line of the surface disposal site shall not exceed the lower explosive limit for methane gas for three years after the sewage sludge unit closes, unless otherwise specified by the permitting authority.
- (k) A food crop, a feed crop, or a fiber crop shall not be grown on an active sewage sludge unit, unless the owner/operator of the surface disposal site demonstrates to the permitting authority that through management practices public health and the environment are protected from any reasonably anticipated adverse effects of pollutants in sewage sludge when crops are grown.
- (1) Animals shall not be grazed on an active sewage sludge unit, unless the owner/operator of the surface disposal site demonstrates to the permitting authority that through management practices public health and the environment are protected from any reasonably anticipated adverse effects of pollutants in sewage sludge when animals are grazed.
- (m) Public access to a surface disposal site shall be restricted for the period that the surface disposal site contains an active sewage sludge unit and for three years after the last active sewage sludge unit in the surface disposal site closes.
- (n)(1) Sewage sludge placed on an active sewage sludge unit shall not contaminate an aquifer.

(2) Results of a ground-water monitoring program developed by a qualified ground-water scientist or a certification by a qualified ground-water scientist shall be used to demonstrate that sewage sludge placed on an active sewage sludge unit does not contaminate an aquifer.

§ 503.25 Operational standards—pathogens and vector attraction reduction.

- (a) Pathogens—sewage sludge (other than domestic septage). The Class A pathogens requirements in §503.32(a) or one of the Class B pathogen requirements in §503.32 (b)(2) through (b)(4) shall be met when sewage sludge is placed on an active sewage sludge unit, unless the vector attraction reduction requirement in §503.33(b)(11) is met.
- (b) Vector attraction reduction—sewage sludge (other than domestic septage). One of the vector attraction reduction requirements in §503.33 (b)(1) through (b)(11) shall be met when sewage sludge is placed on an active sewage sludge unit.
- (c) Vector attraction reduction—domestic septage. One of the vector attraction reduction requirement in §503.33 (b)(9) through (b)(12) shall be met when domestic septage is placed on an active sewage sludge unit.

§ 503.26 Frequency of monitoring.

(a) Sewage sludge (other than domestic septage). (1) The frequency of monitoring for the pollutants in Tables 1 and 2 of \$503.23; the pathogen density requirements in \$503.32(a) and in \$503.32(b)(2); and the vector attraction reduction requirements in \$503.33(b)(1) through (b)(4) and \$503.33(b)(7) through (b)(8) for sewage sludge placed on an active sewage sludge unit shall be the frequency in Table 1 of \$503.26.

TABLE 1 OF § 503.26—FREQUENCY OF MONITORING—SURFACE DISPOSAL

Amount of sewage sludge ¹ (metric tons per 365 day period)	Frequency
Greater than zero but less than 290 Equal to or greater than 290 but less than 1,500 Equal to or greater than 1,500 but less than 15,000 Equal to or greater than 15,000	

¹ Amount of sewage sludge placed on an active sewage sludge unit (dry weight basis)

Environmental Protection Agency

- (2) After the sewage sludge has been monitored for two years at the frequency in Table 1 of this section, the permitting authority may reduce the frequency of monitoring for pollutant concentrations and for the pathogen density requirements in \$503.32(a)(5)(ii) and (a)(5)(iii).
- (b) Domestic septage. If the vector attraction reduction requirements in §503.33(b)(12) are met when domestic septage is placed on an active sewage sludge unit, each container of domestic septage shall be monitored for compliance with those requirements.
- (c) Air. Air in structures within a surface disposal site and at the property line of the surface disposal site shall be monitored continuously for methane gas during the period that the surface disposal site contains an active sewage sludge unit on which the sewage sludge is covered and for three years after a sewage sludge unit closes when a final cover is placed on the sewage sludge.

(Approved by the Office of Management and Budget under control number 2040–0157)

[58 FR 9387, Feb. 19, 1993, as amended at 64 FR 42570, Aug. 4, 1999]

§ 503.27 Recordkeeping.

- (a) When sewage sludge (other than domestic septage) is placed on an active sewage sludge unit:
- (1) The person who prepares the sewage sludge shall develop the following information and shall retain the information for five years.
- (i) The concentration of each pollutant listed in Table 1 of §503.23 in the sewage sludge when the pollutant concentrations in Table 1 of §503.23 are met.
- (ii) The following certification statement:

I certify, under penalty of law, that the information that will be used to determine compliance with the pathogen requirements (insert §503.32(a), §503.32(b)(2), §503.32(b)(3), or §503.32(b)(4) when one of those requirements is met) and the vector attraction reduction requirement in (insert one of the vector attraction reduction requirements in §503.33 (b)(1) through (b)(8) if one of those requirements is met) was prepared under my direction and supervision in accordance with the system designed to ensure that qualified personnel properly gather and evaluate this information. I am aware that there are significant penalties for false

certification including the possibility of fine and imprisonment.

- (iii) A description of how the pathogen requirements in 503.32 (a), (b)(2), (b)(3), or (b)(4) are met when one of those requirements is met.
- (iv) A description of how one of the vector attraction reduction requirements in §503.33 (b)(1) through (b)(8) is met when one of those requirements is met.
- (2) The owner/operator of the surface disposal site, shall develop the following information and shall retain that information for five years.
- (i) The concentration of each pollutant listed in Table 2 of §503.23 in the sewage sludge when the pollutant concentrations in Table 2 of §503.23 are met or when site-specific pollutant limits in §503.23(b) are met.
- (ii) The following certification statement:

I certify, under penalty of law, that the information that will be used to determine compliance with the management practices in §503.24 and the vector attraction reduction requirement in (insert one of the re-§503.33(b)(9) quirements in through §503.33(b)(11) if one of those requirements is met) was prepared under my direction and supervision in accordance with the system designed to ensure that qualified personnel properly gather and evaluate this information. I am aware that there are significant penalties for false certification including the possibility of fine and imprisonment.

- (iii) A description of how the management practices in §503.24 are met.
- (iv) A description of how the vector attraction reduction requirements in §503.33 (b)(9) through (b)(11) are met if one of those requirements is met.
- (b) When domestic septage is placed on a surface disposal site:
- (1) If the vector attraction reduction requirements in §503.33(b)(12) are met, the person who places the domestic septage on the surface disposal site shall develop the following information and shall retain the information for five years:
- (i) The following certification statement:

I certify, under penalty of law, that the information that will be used to determine compliance with the vector attraction reduction requirements in \$503.33(b)(12) was prepared under my direction and supervision in