

[74 FR 51414, Oct. 6, 2009, as amended at 76 FR 18414, Apr. 4, 2011]

TABLE 2 OF SUBPART EC TO PART 60—TOXIC EQUIVALENCY FACTORS

| Dioxin/furan congener | Toxic equivalency factor |
|---|--------------------------|
| 2,3,7,8-tetrachlorinated dibenzo-p-dioxin | 1 |
| 1,2,3,7,8-pentachlorinated dibenzo-p-dioxin | 0.5 |
| 1,2,3,4,7,8-hexachlorinated dibenzo-p-dioxin | 0.1 |
| 1,2,3,7,8,9-hexachlorinated dibenzo-p-dioxin | 0.1 |
| 1,2,3,6,7,8-hexachlorinated dibenzo-p-dioxin | 0.1 |
| 1,2,3,4,6,7,8-heptachlorinated dibenzo-p-dioxin | 0.01 |
| octachlorinated dibenzo-p-dioxin | 0.001 |
| 2,3,7,8-tetrachlorinated dibenzofuran | 0.1 |
| 2,3,4,7,8-pentachlorinated dibenzofuran | 0.5 |
| 1,2,3,7,8-pentachlorinated dibenzofuran | 0.05 |
| 1,2,3,4,7,8-hexachlorinated dibenzofuran | 0.1 |
| 1,2,3,6,7,8-hexachlorinated dibenzofuran | 0.1 |
| 1,2,3,7,8,9-hexachlorinated dibenzofuran | 0.1 |
| 2,3,4,6,7,8-hexachlorinated dibenzofuran | 0.1 |
| 1,2,3,4,6,7,8-heptachlorinated dibenzofuran | 0.01 |
| 1,2,3,4,7,8,9-heptachlorinated dibenzofuran | 0.01 |
| Octachlorinated dibenzofuran | 0.001 |

TABLE 3 TO SUBPART EC OF PART 60—OPERATING PARAMETERS TO BE MONITORED AND MINIMUM MEASUREMENT AND RECORDING FREQUENCIES

| Operating parameters to be monitored | Minimum frequency | | Control system | | |
|--|-------------------|----------------|--|--------------|---|
| | Data measurement | Data recording | Dry scrubber followed by fabric filter | Wet scrubber | Dry scrubber followed by fabric filter and wet scrubber |
| Maximum operating parameters: | | | | | |
| Maximum charge rate | Continuous | 1xhour | ✓ | ✓ | ✓ |
| Maximum fabric filter inlet temperature. | Continuous | 1xminute | ✓ | | ✓ |
| Maximum flue gas temperature. | Continuous | 1xminute | ✓ | ✓ | |
| Minimum operating parameters: | | | | | |
| Minimum secondary chamber temperature. | Continuous | 1xminute | ✓ | ✓ | ✓ |
| Minimum dioxin/furan sorbent flow rate. | Hourly | 1xhour | ✓ | | ✓ |
| Minimum HCl sorbent flow rate. | Hourly | 1xhour | ✓ | | ✓ |
| Minimum mercury (Hg) sorbent flow rate. | Hourly | 1xhour | ✓ | | ✓ |
| Minimum pressure drop across the wet scrubber or minimum horsepower or amperage to wet scrubber. | Continuous | 1xminute | | ✓ | ✓ |
| Minimum scrubber liquor flow rate. | Continuous | 1xminute | | ✓ | ✓ |
| Minimum scrubber liquor pH. | Continuous | 1xminute | | ✓ | ✓ |