§61.306

for a source that has an initial startup date after the effective date.

- (1) Periods of operation where there were exceedances of monitored parameters recorded under §61.305(b).
- (2) All periods recorded under §61.305(c)(1) when the vent stream is diverted from the control device.
- (3) All periods recorded under §61.305(d) when the steam generating unit or process heater was not operating.
- (4) All periods recorded under §61.305(e) in which the pilot flame of the flare was absent.
- (5) All times recorded under §61.305(c)(2) when maintenance is performed on car-sealed valves, when the car seal is broken, and when the valve position is changed.
- (g) The owner or operator of an affected facility shall keep the vaportightness documentation required under §61.302 (d) and (e) on file at the affected facility in a permanent form available for inspection.
- (h) The owner or operator of an affected facility shall update the documentation file required under §61.302 (d) and (e) for each tank truck, railear, or marine vessel at least once per year to reflect current test results as determined by the appropriate method. The owner or operator shall include, as a minimum, the following information in this documentation:
 - (1) Test title:
- (2) Tank truck, railcar, or marine vessel owner and address;
- (3) Tank truck, railcar, or marine vessel identification number;
 - (4) Testing location;
 - (5) Date of test;
 - (6) Tester name and signature;
- (7) Witnessing inspector: name, signature, and affiliation; and
- (8) Test results, including, for railcars and tank trucks, the initial pressure up to which the tank was pressured at the start of the test.
- (i) Each owner or operator of an affected facility complying with §61.300(b) or §61.300(d) shall record the following information. The first year after promulgation the owner or operator shall submit a report containing the requested information to the Director of the Emission Standards Division, (MD-13), U.S. Environmental Protec-

tion Agency, Research Triangle Park, North Carolina 27711. After the first year, the owner or operator shall continue to record; however, no reporting is required. The information shall be made available if requested. The information shall include, as a minimum:

- (1) The affected facility's name and address;
- (2) The weight percent of the benzene loaded:
- (3) The type of vessel loaded (i.e., tank truck, railcar, or marine vessel); and
- (4) The annual amount of benzene loaded into each type of vessel.

[55 FR 8341, Mar. 7, 1990, as amended at 65 FR 62159, Oct. 17, 2000]

§61.306 Delegation of authority.

- (a) In delegating implementation and enforcement authority to a State under section 112(d) of the Act, the authorities contained in paragraph (b) of this section shall be retained by the Administrator and not transferred to a State.
- (b) Authorities which will not be delegated to States: No restrictions.

Subparts CC-EE [Reserved]

Subpart FF—National Emission Standard for Benzene Waste Operations

Source: 55 FR 8346, Mar. 7, 1990, unless otherwise noted.

§ 61.340 Applicability.

- (a) The provisions of this subpart apply to owners and operators of chemical manufacturing plants, coke byproduct recovery plants, and petroleum refineries.
- (b) The provisions of this subpart apply to owners and operators of hazardous waste treatment, storage, and disposal facilities that treat, store, or dispose of hazardous waste generated by any facility listed in paragraph (a) of this section. The waste streams at hazardous waste treatment, storage, and disposal facilities subject to the provisions of this subpart are the benzene-containing hazardous waste from any facility listed in paragraph (a) of