

## § 154.9

*Remote group alarm* means an audible and visual alarm that alerts when an alarm condition exists but does not identify that condition.

*Secondary barrier* means the liquid resisting outer boundary of a cargo containment system when the cargo containment system includes two boundaries.

*Semi-membrane tank* is a cargo tank that is not self-supporting and that can expand and contract due to thermal, hydrostatic, and pressure loadings. It consists of flat surfaces, supported through insulation by the adjacent hull structure, and shaped corners that connect the flat surfaces.

*Service space* means a space outside the cargo area that is used for a galley, pantry containing cooking appliances, locker or store room, workshop except those in machinery spaces, and similar spaces and trunks to those spaces.

*Shut-off valve* is a valve that closes a pipeline and provides nominal metal to metal contact between the valve operating parts, including the disc and gate, and the valve body.

*Specific gravity* (p) means the ratio of the density of the cargo at the design temperature to the density of water at 4 °C (39 °F).

*Tank cover* is the structure protecting those parts of the cargo containment system that protrude through the weather deck and providing continuity to the deck structure.

*Tank dome* means the uppermost portion of the cargo tank. For below deck cargo containment systems, it means the uppermost portion of the cargo tank that protrudes through the weather deck or through the tank cover.

*Toxic cargoes* includes the following liquefied gases from Table 4 (follows §154.1872):

Acetaldehyde  
Ammonia, anhydrous  
Dimethylamine  
Ethylamine  
Ethyl chloride  
Ethylene oxide  
Methyl bromide  
Methyl chloride  
Sulfur dioxide  
Vinyl chloride

*Vapor pressure* means the absolute equilibrium pressure of the saturated

## 46 CFR Ch. I (10–1–11 Edition)

vapor above the liquid, expressed in kPa (psia), at a specific temperature.

*Void space* means an enclosed space in the cargo area outside of the cargo containment system, except a hold space, ballast space, fuel oil tank, cargo pump or compressor room, or any space used by personnel.

*1974 Safety Convention* stands for the International Convention on Safety of Life at Sea, 1974, done at London, November 1, 1974.

### § 154.9 Issuance of documents.

The Coast Guard issues an endorsed Certificate of Inspection to a U.S. flag vessel or an endorsed Certificate of Compliance to a foreign flag vessel that meets this part.

### § 154.12 Existing gas vessel: Endorsements and requirements.

(a) Except an existing gas vessel under paragraph (b), (c), or (d) of this section, an existing gas vessel must meet subpart C of this part if the owner desires a document endorsed for the carriage of a cargo listed in Table 4 (follows §154.1872).

(b) If an existing gas vessel is issued a document by the Coast Guard before November 1, 1987 that is endorsed for the carriage of a cargo listed in Table 4 (follows §154.1872), and the owner desires the same endorsement on a re-issued document, the vessel must—

(1) Continue to meet the same design and construction standards under which the Coast Guard issued the original document; and

(2) Meet paragraph (e) of this section.

(c) If an existing gas vessel is issued a document by the Coast Guard before November 1, 1987 that is endorsed for the carriage of a cargo listed in Table 4 (follows §154.1872), and the owner desires an endorsement for a different cargo listed in that table, the vessel must—

(1) Continue to meet the same design and construction standards under which the Coast Guard issued the original document;

(2) Meet paragraph (e) of this section;

(3) Meet subpart D for the different cargo; and

(4) Meet any additional requirements of this part that the Commandant (CG–