

operates on an assigned frequency in the 890-940 MHz band and has not been certificated, may continue to be used by the licensee without certification provided such transmitter continues otherwise to comply with the applicable rules and regulations of the Commission.

(e) Certification or verification is not required for portable transmitters operating with peak output power not greater than 250 mW. If operation of such equipment causes harmful interference the FCC may, at its discretion, require the licensee to take such corrective action as is necessary to eliminate the interference.

(f) After July 15, 1996, the manufacturer (except for export) or importation of equipment employing digital modulation techniques in the 3700-4200, 5925-6425, 6525-6875, 10,550-10,680 and 10,700-11,700 MHz bands must meet the minimum payload capacity requirements of § 101.141.

(g) After April 1, 2005, the manufacturer (except for export) or importation of equipment for operation in the 21,200-23,600 MHz band must meet:

(1) The 0.001% frequency tolerance requirement for digital systems in § 101.107(a) or the 0.03-0.003% frequency tolerance for analog systems; and

(2) For equipment employing digital modulation techniques, the minimum bit rate requirements of § 101.141(a).

(h) 71,000-76,000 MHz; 81,000-86,000 MHz. For equipment employing digital modulation techniques, the minimum bit rate requirement is 0.125 bit per second per Hz.

(i) 92,000-94,000 MHz; 94,100-95,000 MHz. For equipment employing digital modulation techniques, the minimum bit rate requirement is 1.0 bit per second per Hz.

[63 FR 36611, July 7, 1998, as amended at 65 FR 59358, Oct. 5, 2000; 67 FR 43038, June 26, 2002; 68 FR 4958, Jan. 31, 2003; 70 FR 29998, May 25, 2005]

§ 101.141 Microwave modulation.

(a) Microwave transmitters employing digital modulation techniques and operating below 25.25 GHz (except for MVDDS stations in the 12,200-12,700 MHz band) must, with appropriate multiplex equipment, comply with the following additional requirements:

(1) The bit rate, in bits per second, must be equal to or greater than the bandwidth specified by the emission designator in Hertz (*e.g.*, to be acceptable, equipment transmitting at a 20 Mb/s rate must not require a bandwidth of greater than 20 MHz), except the bandwidth used to calculate the minimum rate may not include any authorized guard band.

(i) Stations authorized prior to December 1, 1988 may install equipment after that date with no minimum bit rate. Equipment applied for or authorized prior to April 1, 2005 in the 21.2-23.6 GHz band may be installed with no minimum bit rate.

(ii) However, any digital equipment applied for after April 1, 2005 and equipment replacing existing equipment in the 21.2-23.6 GHz band must meet the bit rate standard.

(2) Equipment to be used for voice transmission placed in service, authorized, or applied for on or before June 1, 1997 in the 2110 to 2130 and 2160 to 2180 MHz bands must be capable of satisfactory operation within the authorized bandwidth to encode at least 96 voice channels. Equipment placed in service, authorized, or applied for on or before June 1, 1997 in the 3700-4200, 5925-6425 (30 MHz bandwidth), and 10,700-11,700 MHz (30 and 40 MHz bandwidths) bands must be capable of satisfactory operation within the authorized bandwidth to encode at least 1152 voice channels. These required loading levels may be reduced by a factor of 1/N provided that N transmitters may be operated satisfactorily, over the same radio path, within an authorized bandwidth less than, or equal to, the maximum authorizable bandwidth (*e.g.*, the 1152 channel requirement may be reduced to 576 if two transmitters can be satisfactorily operated over the same path within the maximum bandwidth). Where certificated equipment is designed to operate on the same frequency in a cross polarized configuration to meet the above capacity requirements, the Commission will require, at the time additional transmitters are authorized, that both polarizations of a frequency be used before a new frequency assignment is made, unless a single transmitter installation

§ 101.141

47 CFR Ch. I (10–11 Edition)

was found to be justified by the Commission at the time it authorized the first transmitter.

(3) The following capacity and loading requirements must be met for equipment applied for, authorized, and placed in service after June 1, 1997 in the 3700–4200 MHz (4 GHz), 5925–6425 and 6525–6875 MHz (6 GHz), 10,550–10,680 MHz (10 GHz), and 10,700–11,700 MHz (11 GHz) bands:

| Nominal channel bandwidth (MHz) | Minimum payload capacity (Mbits/s) ¹ | Minimum traffic loading payload (as percent of payload capacity) | Typical utilization ² |
|---------------------------------|---|--|----------------------------------|
| 0.400 | 1.54 | N/A | 1 DS-1 |
| 0.800 | 3.08 | N/A | 2 DS-1 |
| 1.25 | 3.08 | N/A | 2 DS-1 |
| 1.60 | 6.17 | N/A | 4 DS-1 |
| 2.50 | 6.17 | N/A | 4 DS-1 |
| 3.75 | 12.3 | N/A | 8 DS-1 |
| 5.0 | 18.5 | N/A | 12 DS-1 |
| 10.0 | 44.7 | ³ 50 | 1 DS-3/STS-1 |
| 20.0 | 89.4 | ³ 50 | 2 DS-3/STS-1 |
| 30.0 (11 GHz) | 89.4 | ³ 50 | 2 DS-3/STS-1 |
| 30.0 (6 GHz) .. | 134.1 | ³ 50 | 3 DS-3/STS-1 |
| 40.0 | 134.1 | ³ 50 | 3 DS-3/STS-1 |

¹ Per polarization

² DS and STS refer to the number of voice circuits a channel can accommodate. 1 DS-1 = 24 voice circuits; 2 DS-1 = 48; 4 DS-1 = 96; 8 DS-1 = 192; 12 DS-1 = 288; 1 DS-3/STS-1 = 672; 2 DS-3/STS-1 = 1344; 3 DS-3/STS-1 = 2016.

³ This loading requirement must be met within 30 months of licensing. If two transmitters simultaneously operate on the same frequency over the same path, the requirement is reduced to 25 percent.

(4) If a transmitter is authorized to operate in a bandwidth that is not listed in paragraph (a)(3) of this section, it must meet the minimum payload capacity and traffic loading requirements of the next largest channel bandwidth listed in the table; *e.g.*, if the authorized bandwidth is 3.5 MHz, the minimum payload capacity must be 12.3 Mbits/s.

(5) Transmitters carrying digital motion video motion material are exempt from the requirements specified in paragraphs (a)(2) and (a)(3) of this section, provided that at least 50 percent of the payload is digital video motion material and the minimum bit rate specified in paragraph (a)(1) of this section is met. In the 6, 10, and 11 GHz bands, concatenation of multiple contiguous channels is permitted for channels of equal bandwidth on center frequencies, provided no other channels are available and the minimum payload capacity requirements are met.

(6) Digital systems using bandwidths of 10 MHz or larger will be considered 50 percent loaded when the following condition is met: at least 50 percent of their total DS-1 capacity is being used. A DS-1 channel is being used when it has been connected to a DS-0/DS-1 multiplexer. For non-DS-0 services, such as, but not limited to, video or broadband data transmission, the next largest DS-1 equivalent will be considered for the computation of a loading percentage.

(7) For digital systems, minimum payload capacities shall be expressed in numbers of DS-1s, DS-3s or STS-1s. The payload capacity required by the Commission shall correspond to commercially available equipment.

(b) For purposes of compliance with the emission limitation requirements of §101.111(a)(2) and the requirements of paragraph (a) of this section, digital modulation techniques are considered as being employed when digital modulation occupies 50 percent or more to the total peak frequency deviation of a transmitted radio frequency carrier. The total peak frequency deviation will be determined by adding the deviation produced by the digital modulation signal and the deviation produced by any frequency division multiplex (FDM) modulation used. The deviation (D) produced by the FDM signal must be determined in accordance with §2.202(f) of this chapter.

(c) Analog Modulation. Except for video transmission, an application for an initial working channel for a given route will not be accepted for filing where the anticipated loading (within five years for voice, or other period subject to reasonable projection) is less than the minimum specified for the following frequency bands. Absent extraordinary circumstances, applications proposing additional frequencies over existing routes will not be granted unless it is shown that the traffic load will shortly exhaust the capacity of the existing equipment. Where no construction of radio facilities is requested, licensees must submit this evidence with their filing of any necessary authority required pursuant to section 214 of the Communications Act and part 63 of this chapter.

| Frequency band (MHz) | Minimum number of voice channels (4 KHz or equivalent) |
|---|--|
| 3700 to 4200 (20 MHz bandwidth) | 900 |
| 5925 to 6425 (10 MHz bandwidth) | 300 |
| 5925 to 6425 (20 MHz bandwidth) | 600 |
| 5925 to 6425 (30 MHz bandwidth) | 900 |
| 6525 to 6875 (10 MHz bandwidth) | 300 |
| 10,700 to 11,700 (10 MHz bandwidth) | 300 |
| 10,700 to 11,700 (20 MHz bandwidth) | 600 |
| 10,700 to 11,700 (30 MHz bandwidth) | 900 |
| 10,700 to 11,700 (40 MHz bandwidth) | 900 |

[61 FR 26677, May 28, 1996, as amended at 62 FR 24583, May 6, 1997; 63 FR 36611, July 7, 1998; 65 FR 59358, Oct. 5, 2000; 67 FR 43039, June 26, 2002; 68 FR 4958, Jan. 31, 2003]

EFFECTIVE DATE NOTE: At 76 FR 59572, Sept. 27, 2011, §101.141 was amended by revising paragraph (a)(3) introductory text and by adding the entry “25.0 89.4³⁵⁰ 2 DS-3/STS-1”, effective October 27, 2011. For the convenience of the user, the added and revised text is set forth as follows:

| Nominal channel bandwidth (MHz) | Minimum Payload capacity (Mbits/s) ¹ | Minimum traffic payload (as percent of payload capacity) | Typical utilization ² |
|---------------------------------|---|--|----------------------------------|
| 25.0 | 89.4 | ³⁵⁰ 2 DS-3/STS-1. | |

* * * * *

§101.143 Minimum path length requirements.

(a) The distance between end points of a fixed link in the private operational fixed point-to-point and the common carrier fixed point-to-point microwave services must equal or exceed the value set forth in the table below or the EIRP must be reduced in accordance with the equation set forth below:

| Frequency band (MHz) | Minimum path length (km) |
|------------------------|--------------------------|
| Below 1,850 | N/A |
| 1,850 to 7,125 | 17 |
| 10,550 to 13,250 | 5 |
| Above 17,700 | N/A |

(b) For paths shorter than those specified in the table in paragraph (a) of this section, the EIRP shall not exceed

§ 101.141 Microwave modulation.

(a) * * *
 (3) The following capacity and loading requirements must be met for equipment applied for, authorized, and placed in service after June 1, 1997 in 3700-4200 MHz (4 GHz), 5925-6425, 6525-6875 MHz (6 GHz), 6875-7125 MHz (7 GHz), 10,550-10,680 MHz (10 GHz), 10,700-11700 MHz (11 GHz), and 12,700-13,150 MHz (13 GHz) bands, except during anomalous signal fading. During anomalous signal fading, licensees may adjust to a modulation specified in their authorization if such modulation is necessary to allow licensees to maintain communications, even if the modulation will not comply with the capacity and loading requirements specified in this paragraph. Links that use equipment capable of adjusting modulation must be designed using generally accepted multipath fading and rain fading models to meet the specified capacity and loading requirements at least 99.95% of the time, in the aggregate of both directions in a two-way link.

* * * * *

the value derived from the following equation:

$$EIRP = MAXEIRP - 40 \log(A/B) \text{ dBW}$$

Where: EIRP = The new maximum EIRP (equivalent isotropically radiated power) in dBW. MAXEIRP = Maximum EIRP as set forth in the Table in Section 101.113(a).
 A = Minimum path length from the Table above for the frequency band in kilometers.
 B = The actual path length in kilometers.

NOTE TO PARAGRAPH (b): For transmitters using Automatic Transmitter Power Control, EIRP corresponds to the maximum transmitter power available, not the coordinated transmit power or the nominal transmit power.

(c) Upon an appropriate technical showing, applicants and licensees unable to meet the minimum path length requirement may be granted an exception to these requirements.