### Federal Aviation Administration, DOT

- (b) Reciprocating engine installations. Operating limitations relating to the following must be established for reciprocating engine installations:
- (1) Horsepower or torque, r.p.m., manifold pressure, and time at critical pressure altitude and sea level pressure altitude for—
- (i) Maximum continuous power (relating to unsupercharged operation or to operation in each supercharger mode as applicable); and
- (ii) Takeoff power (relating to unsupercharged operation or to operation in each supercharger mode as applicable).
  - (2) Fuel grade or specification.
- (3) Cylinder head and oil temperatures.
- (4) Any other parameter for which a limitation has been established as part of the engine type certificate except that a limitation need not be established for a parameter that cannot be exceeded during normal operation due to the design of the installation or to another established limitation.
- (c) *Turbine engine installations*. Operating limitations relating to the following must be established for turbine engine installations:
- (1) Horsepower, torque or thrust, r.p.m., gas temperature, and time for—
- (i) Maximum continuous power or thrust (relating to augmented or unaugmented operation as applicable).
- (ii) Takeoff power or thrust (relating to augmented or unaugmented operation as applicable).
  - (2) Fuel designation or specification.
- (3) Any other parameter for which a limitation has been established as part of the engine type certificate except that a limitation need not be established for a parameter that cannot be exceeded during normal operation due to the design of the installation or to another established limitation.
- (d) Ambient temperature. An ambient temperature limitation (including limitations for winterization installations, if applicable) must be established as the maximum ambient atmospheric temperature established in accordance with §25.1043(b).

[Amdt. 25-72, 55 FR 29786, July 20, 1990]

#### § 25.1522 Auxiliary power unit limitations.

If an auxiliary power unit is installed in the airplane, limitations established for the auxiliary power unit, including categories of operation, must be specified as operating limitations for the airplane.

[Amdt. 25-72, 55 FR 29786, July 20, 1990]

#### §25.1523 Minimum flight crew.

The minimum flight crew must be established so that it is sufficient for safe operation, considering—

- (a) The workload on individual crewmembers:
- (b) The accessibility and ease of operation of necessary controls by the appropriate crewmember; and
- (c) The kind of operation authorized under § 25.1525.

The criteria used in making the determinations required by this section are set forth in appendix D.

[Doc. No. 5066, 29 FR 18291, Dec. 24, 1964, as amended by Amdt. 25–3, 30 FR 6067, Apr. 29, 1965]

#### $\S 25.1525$ Kinds of operation.

The kinds of operation to which the airplane is limited are established by the category in which it is eligible for certification and by the installed equipment.

# § 25.1527 Ambient air temperature and operating altitude.

The extremes of the ambient air temperature and operating altitude for which operation is allowed, as limited by flight, structural, powerplant, functional, or equipment characteristics, must be established.

[Doc. No. 2000-8511, 66 FR 34024, June 26, 2001]

## § 25.1529 Instructions for Continued Airworthiness.

The applicant must prepare Instructions for Continued Airworthiness in accordance with appendix H to this part that are acceptable to the Administrator. The instructions may be incomplete at type certification if a program exists to ensure their completion prior to delivery of the first airplane or